



## SASSO 40 round wallwasher

recessed 2 lamps


**EN** Round recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

**DE** Runder Einbaustrahler; werkzeuglose Montage im Montageset durch Kugelschnappsystem; Oberfläche lackiert; mit umlaufendem Rand; zweiflammig; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI  $\geq$  90 / 2 SDCM (initial MacAdam)  
 bis zu 109 lm/W  
 L85 / 50000 h  
 DALI-2, nicht dimmbar  
 front IP20

### Types



### Farbe



### Montage Set



### Lichtverteilung



wallwasher/  
wallwasher floor  
inset



## SASSO 40 round wallwasher




### WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
2x7.0 W,	2700 K	2x760 lm	109 lm/W	0 4 8 - 2 8 4 0 9 1 <input checked="" type="checkbox"/> A
36 Vf,	3000 K	2x716 lm	103 lm/W	0 4 8 - 2 8 4 0 0 1 <input checked="" type="checkbox"/> A
200 mA	3500 K	2x746 lm	107 lm/W	0 4 8 - 2 8 4 0 2 1 <input checked="" type="checkbox"/> A
	4000 K	2x716 lm	103 lm/W	0 4 8 - 2 8 4 0 1 1 <input checked="" type="checkbox"/> A



The data values for the luminaire luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour traffic white, matt silver.

## Mounting accessories (required)



### MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L-W-H (mm)

122-60-13

ORDER CODE


0 4 8 - 2 8 9 8 3 1  A

## Electrical accessories (required)

### POWER SUPPLY 200 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
15 W   DALI-2	η 87 %	165-29-21	0 0 2 - 9 0 7 4 0
10 W   non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 4

## Electrical accessories (optional)



### DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
160 W   PC2	220-240 V AC	η 94 %	72-90-63	0 0 5 - 6 5 2 0 2 1 0

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

### DIN RAIL LED DRIVER

TYPE	L-W-H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36-88-59	0 0 5 - 6 1 2 1 0 3 0

200 - 1050 mA settable const. current | 2x42W | 48V DC | U OUT 10-40V

### POWER SUPPLY PRE-WIRED with junction box DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
450 mA	η 87 %	0 0 2 - 9 0 7 5 0 A
200 mA	η 87 %	0 0 2 - 9 0 7 4 9 A

## Order options

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7		
gold dust RAL 260-M	9		


**POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2**

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450 mA	η 87 %	185-30-21	0 0 2 - 9 0 7 5 0
200 mA	η 87 %		0 0 2 - 9 0 7 4 9

**Order options**

COLOUR	<input checked="" type="checkbox"/>	COLOUR	<input checked="" type="checkbox"/>
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7		
gold dust RAL 260-M	9		