



SASSO 60 round wallwasher/floor

recessed 1 lamp


EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

DE Runder Einbaustrahler; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90 / 2 SDCM (initial MacAdam)
 bis zu 118 lm/W
 L85 / 50000 h
 DALI-2, nicht dimmbar
 front IP20

Types



Farbe



Montage Set



Lichtverteilung



wallwasher/
wallwasher floor
inset



60 mm
recessed depth
(non DIM)



quick mounting
in soft acoustic
ceilings



SASSO 60 round wallwasher/floor




WALLWASHER FLOOR CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---------|--------------|-----------|----------|---|
| 8.9 W, | 2700 K | 1050 lm | 118 lm/W | 0 4 8 - 2 6 4 1 9 1 <input checked="" type="checkbox"/> W |
| 36 Vf, | 3000 K | 985 lm | 111 lm/W | 0 4 8 - 2 6 4 1 0 1 <input checked="" type="checkbox"/> W |
| 250 mA | 3500 K | 1030 lm | 116 lm/W | 0 4 8 - 2 6 4 1 2 1 <input checked="" type="checkbox"/> W |
| | 4000 K | 985 lm | 111 lm/W | 0 4 8 - 2 6 4 1 1 1 <input checked="" type="checkbox"/> W |



Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

| TYPE | L-W-H (mm) | ORDER CODE |
|---------------------------|------------|-----------------------|
| non DIM cable ø 4 – 12 mm | 105-58-30 | 0 0 5 - 2 5 3 1 1 1 0 |
| DALI cable ø 4 – 12 mm | 105-58-30 | 0 0 5 - 2 5 5 1 1 1 0 |

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings


| COLOUR | PLASTERBOARD CEILING THICKNESS | Ø-H (mm) | ORDER CODE |
|---------------|--------------------------------|----------|-----------------------|
| traffic white | 12.5/15/25 mm | 73-29 | 0 4 8 - 2 6 9 6 1 1 7 |

for SASSO 60 round | SPIO 60 downlight




MOUNTING SET trimless for soft acoustic ceilings

| COLOUR | CEILING THICKNESS | Ø-H (mm) | ORDER CODE |
|---------------|-------------------|----------|-----------------------|
| traffic white | 25-40 mm | 80-25 | 0 4 8 - 2 6 9 6 1 9 7 |



MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm

| COLOUR | Ø-H (mm) | ORDER CODE |
|---------------|----------|-----------------------|
| traffic white | 80-27 | 0 4 8 - 2 6 9 6 3 9 7 |
| jet black | 80-27 | 0 4 8 - 2 6 9 6 3 9 8 |




MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

| COLOUR | Ø-H (mm) | ORDER CODE |
|-----------------|----------|-----------------------|
| traffic white | 80-40 | 0 4 8 - 2 6 9 6 3 1 7 |
| jet black | 80-40 | 0 4 8 - 2 6 9 6 3 1 8 |
| white aluminium | 80-40 | 0 4 8 - 2 6 9 6 3 1 G |

Order options


| COLOUR | <input checked="" type="checkbox"/> | COLOUR | |
|------------------------|-------------------------------------|-----------------|----------|
| jet black RAL 9005 | 1 | white aluminium | RAL 9006 |
| matt silver | 4 | traffic black | RAL 9017 |
| traffic white RAL 9016 | 7 | | |
| gold dust RAL 260-M | 9 | | |

Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING

| COLOUR | L-W-H (mm) | ORDER CODE |
|-----------------|-------------|-----------------------|
| white aluminium | 230-230-162 | 0 4 8 - 2 6 9 5 2 1 0 |



PRIMED CONCRETE MOUNTING HOUSING

| L-W-H (mm) | ORDER CODE |
|-------------|-----------------------|
| 614-307-120 | 0 4 8 - 2 6 9 5 1 1 0 |

order mounting set separately

Mounting tools accessories (optional)



MOUNTING TOOL for soft acoustic ceilings


| COLOUR | L-W-H (mm) | ORDER CODE |
|---------------|------------|-----------------------|
| traffic black | 77-77-35 | 0 4 8 - 2 6 9 5 9 1 8 |

Electrical accessories (required)

POWER SUPPLY 250 mA, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|----------------|------------|------------|-------------------|
| 10 W non DIM | η 80 % | 65-39-20 | 0 0 2 - 9 0 7 4 2 |
| 15 W DALI-2 | η 87 % | 165-29-21 | 0 0 2 - 9 0 7 4 8 |

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

| TYPE | INPUT VOLTAGE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|-------------|---------------|------------|------------|-----------------------|
| 160 W PC2 | 220-240 V AC | η 94 % | 72-90-63 | 0 0 5 - 6 5 2 0 2 1 0 |

Lifetime >100.000h @ 120W, 45°C ambient temp., cascable max. 3 devices

DIN RAIL LED DRIVER

| TYPE | L-W-H (mm) | ORDER CODE |
|--------------------------|------------|-----------------------|
| DALI-2 DT6 1-2 addresses | 36-88-59 | 0 0 5 - 6 1 2 1 0 3 0 |

200 - 1050 mA settable const. current | 2×42W | 48V DC | U OUT 10-40V

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

| TYPE | EFFICIENCY | ORDER CODE |
|-------------------------|------------|---------------------|
| 300 mA 15 W DALI-2 | η 87 % | 0 0 2 - 9 0 7 9 0 A |
| 250 mA 15 W DALI-2 | η 87 % | 0 0 2 - 9 0 7 4 8 A |
| 300 mA 15 W non DIM | η 84 % | 0 0 2 - 9 0 7 7 1 A |
| 250 mA 10 W non DIM | η 80 % | 0 0 2 - 9 0 7 4 2 A |

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L-W-H (mm) | ORDER CODE |
|--------|------------|------------|-------------------|
| 300 mA | η 87 % | 185-30-21 | 0 0 2 - 9 0 7 7 0 |
| 250 mA | η 87 % | 185-30-21 | 0 0 2 - 9 0 7 4 7 |

Order options

| COLOUR | <input checked="" type="checkbox"/> | COLOUR | |
|------------------------|-------------------------------------|-----------------|----------|
| jet black RAL 9005 | 1 | white aluminium | RAL 9006 |
| matt silver | 4 | traffic black | RAL 9017 |
| traffic white RAL 9016 | 7 | | |
| gold dust RAL 260-M | 9 | | |