



## Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
bis zu 113 lm/W
L80 / 75000 h
DALI-2, nicht dimmbar
front IP20

### Types




### Farben



### Montage Set



### Lichtverteilung



# **SASSO 60** round wallwasher

recessed 1 lamp

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

DE Runder Einbaustrahler; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe



wallwasher/
wallwasher floor
inset



60 mm
recessed depth
(non DIM)



quick mounting
in
soft acoustic
ceilings



## **SASSO 60** round wallwasher





### WALLWASHER CRI ≥ 90

| FIXTURE | COLOUR TEMP. | LUM. FLUX | EFFICACY | ORDER CODE |
|---|---|---|---|---|
| 8.9 W, | 2700 K | 945 lm | 107 lm/W | 0 4 8 - 2 6 4 1 9 1 ◪ A |
| 36 Vf, | 3000 K | 945 lm | 107 lm/W | 0 4 8 - 2 6 4 1 0 1 ◪ A |
| 250 mA | 3500 K | 984 lm | 111 lm/W | 0 4 8 - 2 6 4 1 2 1 ◪ A |
| | 4000 K | 1000 lm | 113 lm/W | 0 4 8 - 2 6 4 1 1 1 ◪ A |

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white.




## Electrical mounting accessories (optional)





### THROUGH WIRING CONNECTION BOX

| TYPE | L·W·H (mm) | ORDER CODE |
|---|---|---|
| non DIM cable ø 4 – 12 mm | 105·58·30 | 0 0 5 - 2 5 3 1 1 1 0 |
| DALI cable ø 4 – 12 mm | 105·58·30 | 0 0 5 - 2 5 5 1 1 1 0 |

Linect®-Ready


## Mounting accessories (required)




### MOUNTING SET trimless for plasterboard ceilings


| COLOUR | PLASTERBOARD CEILING THICKNESS | Ø·H (mm) | ORDER CODE |
|---|---|---|---|
| traffic white | 12.5/15/20/25 mm | 73·29 | 0 4 8 - 2 6 9 6 1 1 7 |

for SASSO 60 round | SPIO 60 downlight





### MOUNTING SET trimless for soft acoustic ceilings

| TYPE | COLOUR | CEILING THICKNESS | Ø·H (mm) | ORDER CODE |
|---|---|---|---|---|
| For Rockfon Mono® Acoustic | traffic white | 25-40 mm | 80·25 | 0 4 8 - 2 6 9 6 1 9 7 |




### MOUNTING SET with trim for soft acoustic ceilings, 25-40 mm, For Rockfon Mono® Acoustic

| COLOUR | Ø·H (mm) | ORDER CODE |
|---|---|---|
| traffic white | 80·27 | 0 4 8 - 2 6 9 6 3 9 7 |
| jet black | 80·27 | 0 4 8 - 2 6 9 6 3 9 8 |




### MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm

| COLOUR | Ø·H (mm) | ORDER CODE |
|---|---|---|
| traffic white | 80·40 | 0 4 8 - 2 6 9 6 3 1 7 |
| jet black | 80·40 | 0 4 8 - 2 6 9 6 3 1 8 |
| white aluminium | 80·40 | 0 4 8 - 2 6 9 6 3 1 G |

## Order options

| COLOUR | ◪ |
|---|---|
| jet black RAL 9005 | 1 |
| matt silver | 4 |
| traffic white RAL 9016 | 7 |
| gold dust RAL 260-M | 9 |


| COLOUR | |
|---|---|
| white aluminium | RAL 9006 |
| traffic black | RAL 9017 |

## Mounting accessories (optional)




**EXPOSED CONCRETE MOUNTING HOUSING**

| COLOUR | L·W·H (mm) | ORDER CODE |
|---|---|---|
| white aluminium | 230·230·162 | 048-269521 0 |





**PRIMED CONCRETE MOUNTING HOUSING**

| L·W·H (mm) | ORDER CODE |
|---|---|
| 614·307·120 | 048-269511 0 |

order mounting set separately

## Mounting tools accessories (optional)




**MOUNTING TOOL** for soft acoustic ceilings

| COLOUR | L·W·H (mm) | ORDER CODE |
|---|---|---|
| traffic black | 77·77·35 | 048-269591 8 |


## Electrical accessories (required)

**POWER SUPPLY** 250 mA, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 10 W \| non DIM | η 80 % | 65·39·20 | 002-907 42 |
| 15 W \| DALI-2 | η 87 % | 165·29·21 | 002-907 48 |

2 power supplies for 2 lamps variants necessary

## Electrical accessories (optional)




**DIN RAIL POWER SUPPLY BASIC** 48 V

| TYPE | INPUT VOLTAGE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|---|
| 160 W \| PC2 | 220-240 V AC | η 94 % | 72·90·63 | 005-652021 0 |

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

**DIN RAIL LED DRIVER**

| TYPE | L·W·H (mm) | ORDER CODE |
|---|---|---|
| DALI-2 DT6 1-2 addresses / DT8 1 adress | 36·88·59 | 005-612103 0 |

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10–40 V SELV

**POWER SUPPLY PRE-WIRED with junction box** 198-264 V AC, PC2

| TYPE | EFFICIENCY | ORDER CODE |
|---|---|---|
| 300 mA \| 15 W \| DALI-2 | η 87 % | 002-907 90 A |
| 250 mA \| 15 W \| DALI-2 | η 87 % | 002-907 48 A |
| 300 mA \| 15 W \| non DIM | η 84 % | 002-907 71 A |
| 250 mA \| 10 W \| non DIM | η 80 % | 002-907 42 A |

2 power supplies for 2 lamps variants necessary

**Order options**

| COLOUR | |
|---|---|
| white aluminium | RAL 9006 |
| traffic black | RAL 9017 |

**POWER SUPPLY with loop through function** DALI-2, 15 W, 198-264 V AC, PC2

| TYPE | EFFICIENCY | L·W·H (mm) | ORDER CODE |
|---|---|---|---|
| 300 mA | η 87 % | 185·30·21 | 0 0 2 - 9 0 7 7 0 |
| 250 mA | η 87 % | 185·30·21 | 0 0 2 - 9 0 7 4 7 |

2 power supplies for 2 lamps variants necessary