




Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM (initial MacAdam)
bis zu 117 lm/W
L80 / 75000 h
DALI-2, nicht dimmbar
front IP20

Types



Farben



Montage Set



Lichtverteilung



SASSO 60 square wallwasher

recessed 2 lamps

EN Square recessed spotlight; installation without tools in mounting set with ball catch system; surface lacquered; with trim; double lamps; asymmetric radiation characteristic; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; no multiple shadows; efficient LEDs with very good colour rendering

DE Quadratischer Einbaustrahler; werkzeuglose Montage im Montageset durch Kugelschnappsystem; Oberfläche lackiert; mit umlaufendem Rand; zweiflammig; asymmetrische Abstrahlcharakteristik; mit speziell berechnetem, asymmetrischem Reflektor für homogene vertikale Beleuchtungsstärken; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe




wallwasher/
wallwasher floor
inset



60 mm
recessed depth




CRI ≥ 95 2
SDCM
(optional)



SASSO 60 square wallwasher

CRI ≥ 90 | 2 SDCM | III | DALI 1 ADDR. | X-PERT




WALLWASHER CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.9 W,	2700 K	1950 lm	110 lm/W	048-265191 A
36 Vf,	3000 K	1940 lm	110 lm/W	048-265101 A
250 mA	3500 K	2020 lm	114 lm/W	048-265121 A
	4000 K	2060 lm	117 lm/W	048-265111 A

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to colour matt silver, traffic white. 2 insets necessary, order code only applies to 1 inset

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L·W·H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105·58·30	005-253110
DALI cable ø 4 – 12 mm	105·58·30	005-255110

Linect®-Ready

Mounting accessories (required)



MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm

L·W·H (mm)	ORDER CODE
147·81·35	048-269931 1


Electrical accessories (required)

POWER SUPPLY 250 mA, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
10 W | non DIM	η 80 %	65·39·20	002-90742
15 W | DALI-2	η 87 %	165·29·21	002-90748

2 power supplies for 2 lamps variants necessary

Electrical accessories (optional)



DIN RAIL POWER SUPPLY BASIC 48 V

TYPE	INPUT VOLTAGE	EFFICIENCY	L·W·H (mm)	ORDER CODE
160 W | PC2	220-240 V AC	η 94 %	72·90·63	005-652021 0

Lifetime >100.000 h @ 120 W, 45°C ambient temp., cascadable max. 3 devices

DIN RAIL LED DRIVER

TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses / DT8 1 adress	36·88·59	005-612103 0

200 -1050 mA settable const. current | 2 × 42 W | 48 V DC | U OUT 10 – 40 V SELV

Order options

COLOUR		COLOUR	
jet black RAL 9005	1	traffic white RAL 9016	7
matt silver	4	jet black RAL 9005	8
traffic white RAL 9016	7	white aluminium RAL 9006	G
gold dust RAL 260-M	9		

POWER SUPPLY PRE-WIRED with junction box 198-264 V AC, PC2

TYPE	EFFICIENCY	ORDER CODE
300 mA | 15 W | DALI-2	η 87 %	0 0 2 - 9 0 7 9 0 A
250 mA | 15 W | DALI-2	η 87 %	0 0 2 - 9 0 7 4 8 A
300 mA | 15 W | non DIM	η 84 %	0 0 2 - 9 0 7 7 1 A
250 mA | 10 W | non DIM	η 80 %	0 0 2 - 9 0 7 4 2 A

2 power supplies for 2 lamps variants necessary

POWER SUPPLY with loop through function DALI-2, 15 W, 198-264 V AC, PC2

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
300 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 7 0
250 mA	η 87 %	185·30·21	0 0 2 - 9 0 7 4 7

2 power supplies for 2 lamps variants necessary