



Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
 CRI ≥ 90 / 2 SDCM (initial MacAdam)
 UGR ≤ 10 , UGR ≤ 16 , UGR ≤ 19
 bis zu 136 lm/W
 L90 / 50000 h
 DALI-2, nicht dimmbar
 front IP20

Types

trim



138x63



101x63

trimless



122x47



85x47

Farben



Montage Set



Lichtverteilung



UNICO L2 / L3

recessed

EN Rectangular recessed multi-downlight made of die-cast aluminium; equipped with two (L2) / three (L3) individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering


DE Rechteckiger Einbau-Multi-Downlight aus Aluminiumdruckguss; bestückt mit zwei (L2) / drei (L3) individuell wählbaren oder fix definierten, anwendungsspezifischen Optiken; werkzeuglose Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit unterschiedlichen symmetrischen Lichtverteilungen; oder mit asymmetrischer Lichtverteilung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe




one luminaire
multiple scenes



up to 145 lm/W
(high efficiency)



black & chrome
reflector



tunable white
2700 – 5000 K
(optional)



UNICO L2



SPOT ROUND 19°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	626 lm	101 lm/W	0 9 0 - 7 L 2 9 ◆ K 0 ■ 4 1
	3000 K	626 lm	101 lm/W	0 9 0 - 7 L 2 0 ◆ K 0 ■ 4 1
	3500 K	652 lm	105 lm/W	0 9 0 - 7 L 2 2 ◆ K 0 ■ 4 1
	4000 K	665 lm	107 lm/W	0 9 0 - 7 L 2 1 ◆ K 0 ■ 4 1

MEDIUM ROUND 34°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	676 lm	109 lm/W	0 9 0 - 7 L 2 9 ◆ B 0 ■ 4 1
	3000 K	676 lm	109 lm/W	0 9 0 - 7 L 2 0 ◆ B 0 ■ 4 1
	3500 K	705 lm	114 lm/W	0 9 0 - 7 L 2 2 ◆ B 0 ■ 4 1
	4000 K	719 lm	116 lm/W	0 9 0 - 7 L 2 1 ◆ B 0 ■ 4 1

FLOOD ROUND 47°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	723 lm	117 lm/W	0 9 0 - 7 L 2 9 ◆ C 0 ■ 4 1
	3000 K	723 lm	117 lm/W	0 9 0 - 7 L 2 0 ◆ C 0 ■ 4 1
	3500 K	753 lm	121 lm/W	0 9 0 - 7 L 2 2 ◆ C 0 ■ 4 1
	4000 K	768 lm	124 lm/W	0 9 0 - 7 L 2 1 ◆ C 0 ■ 4 1

WIDE FLOOD ROUND 67°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	734 lm	118 lm/W	0 9 0 - 7 L 2 9 ◆ D 0 ■ 4 1
	3000 K	734 lm	118 lm/W	0 9 0 - 7 L 2 0 ◆ D 0 ■ 4 1
	3500 K	764 lm	123 lm/W	0 9 0 - 7 L 2 2 ◆ D 0 ■ 4 1
	4000 K	780 lm	126 lm/W	0 9 0 - 7 L 2 1 ◆ D 0 ■ 4 1

MEDIUM SQUARE 32°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	659 lm	106 lm/W	0 9 0 - 7 L 2 9 ◆ E 0 ■ 4 1
	3000 K	659 lm	106 lm/W	0 9 0 - 7 L 2 0 ◆ E 0 ■ 4 1
	3500 K	686 lm	111 lm/W	0 9 0 - 7 L 2 2 ◆ E 0 ■ 4 1
	4000 K	700 lm	113 lm/W	0 9 0 - 7 L 2 1 ◆ E 0 ■ 4 1

FLOOD SQUARE 55°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	735 lm	119 lm/W	0 9 0 - 7 L 2 9 ◆ F 0 ■ 4 1
	3000 K	735 lm	119 lm/W	0 9 0 - 7 L 2 0 ◆ F 0 ■ 4 1
	3500 K	766 lm	124 lm/W	0 9 0 - 7 L 2 2 ◆ F 0 ■ 4 1
	4000 K	781 lm	126 lm/W	0 9 0 - 7 L 2 1 ◆ F 0 ■ 4 1

Order options

CONTROL	◆	COLOUR	■	COLOUR	
non DIM	1	black reflector	B	jet black	RAL 9005
DALI-2	3	chrome reflector	0	traffic white	RAL 9016

RECTANGULAR MEDIUM 31°x67°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	708 lm	114 lm/W	0 9 0 - 7 L 2 9 ◆ R 0 ■ 4 1
	3000 K	708 lm	114 lm/W	0 9 0 - 7 L 2 0 ◆ R 0 ■ 4 1
	3500 K	738 lm	119 lm/W	0 9 0 - 7 L 2 2 ◆ R 0 ■ 4 1
	4000 K	752 lm	121 lm/W	0 9 0 - 7 L 2 1 ◆ R 0 ■ 4 1

WIDE FLOOD SQUARE 70°, CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	740 lm	119 lm/W	0 9 0 - 7 L 2 9 ◆ G 0 ■ 4 1
	3000 K	740 lm	119 lm/W	0 9 0 - 7 L 2 0 ◆ G 0 ■ 4 1
	3500 K	771 lm	124 lm/W	0 9 0 - 7 L 2 2 ◆ G 0 ■ 4 1
	4000 K	786 lm	127 lm/W	0 9 0 - 7 L 2 1 ◆ G 0 ■ 4 1

WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	570 lm	92 lm/W	0 9 0 - 7 L 2 9 ◆ A 0 0 4 2
	3000 K	570 lm	92 lm/W	0 9 0 - 7 L 2 0 ◆ A 0 0 4 2
	3500 K	594 lm	96 lm/W	0 9 0 - 7 L 2 2 ◆ A 0 0 4 2
	4000 K	606 lm	98 lm/W	0 9 0 - 7 L 2 1 ◆ A 0 0 4 2

WALL FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
6.2 W	2700 K	671 lm	108 lm/W	0 9 0 - 7 L 2 9 ◆ W 0 ■ 4 2
	3000 K	671 lm	108 lm/W	0 9 0 - 7 L 2 0 ◆ W 0 ■ 4 2
	3500 K	699 lm	113 lm/W	0 9 0 - 7 L 2 2 ◆ W 0 ■ 4 2
	4000 K	713 lm	115 lm/W	0 9 0 - 7 L 2 1 ◆ W 0 ■ 4 2

**UNICO L3****SPOT ROUND 19°, CRI ≥ 90**

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	939 lm	108 lm/W	0 9 0 - 7 L 3 9 ◆ K 0 ■ 4 1
	3000 K	939 lm	108 lm/W	0 9 0 - 7 L 3 0 ◆ K 0 ■ 4 1
	3500 K	978 lm	112 lm/W	0 9 0 - 7 L 3 2 ◆ K 0 ■ 4 1
	4000 K	998 lm	115 lm/W	0 9 0 - 7 L 3 1 ◆ K 0 ■ 4 1

MEDIUM ROUND 34°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	1010 lm	116 lm/W	0 9 0 - 7 L 3 9 ◆ B 0 ■ 4 1
	3000 K	1010 lm	116 lm/W	0 9 0 - 7 L 3 0 ◆ B 0 ■ 4 1
	3500 K	1060 lm	122 lm/W	0 9 0 - 7 L 3 2 ◆ B 0 ■ 4 1
	4000 K	1080 lm	124 lm/W	0 9 0 - 7 L 3 1 ◆ B 0 ■ 4 1

Order options

CONTROL	◆	COLOUR	■	COLOUR
non DIM	1	black reflector	B	jet black
DALI-2	3	chrome reflector	0	traffic white

RAL 9005

RAL 9016

FLOOD ROUND 47°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	1080 lm	124 lm/W	0 9 0 - 7 L 3 9  C 0  4 1
	3000 K	1080 lm	124 lm/W	0 9 0 - 7 L 3 0  C 0  4 1
	3500 K	1130 lm	130 lm/W	0 9 0 - 7 L 3 2  C 0  4 1
	4000 K	1150 lm	132 lm/W	0 9 0 - 7 L 3 1  C 0  4 1

WIDE FLOOD ROUND 67°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	1100 lm	126 lm/W	0 9 0 - 7 L 3 9  D 0  4 1
	3000 K	1100 lm	126 lm/W	0 9 0 - 7 L 3 0  D 0  4 1
	3500 K	1150 lm	132 lm/W	0 9 0 - 7 L 3 2  D 0  4 1
	4000 K	1170 lm	134 lm/W	0 9 0 - 7 L 3 1  D 0  4 1

MEDIUM SQUARE 32°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	988 lm	114 lm/W	0 9 0 - 7 L 3 9  E 0  4 1
	3000 K	988 lm	114 lm/W	0 9 0 - 7 L 3 0  E 0  4 1
	3500 K	1030 lm	118 lm/W	0 9 0 - 7 L 3 2  E 0  4 1
	4000 K	1050 lm	121 lm/W	0 9 0 - 7 L 3 1  E 0  4 1

FLOOD SQUARE 55°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	1100 lm	126 lm/W	0 9 0 - 7 L 3 9  F 0  4 1
	3000 K	1100 lm	126 lm/W	0 9 0 - 7 L 3 0  F 0  4 1
	3500 K	1150 lm	132 lm/W	0 9 0 - 7 L 3 2  F 0  4 1
	4000 K	1170 lm	134 lm/W	0 9 0 - 7 L 3 1  F 0  4 1

WIDE FLOOD SQUARE 70°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	1110 lm	128 lm/W	0 9 0 - 7 L 3 9  G 0  4 1
	3000 K	1110 lm	128 lm/W	0 9 0 - 7 L 3 0  G 0  4 1
	3500 K	1160 lm	133 lm/W	0 9 0 - 7 L 3 2  G 0  4 1
	4000 K	1180 lm	136 lm/W	0 9 0 - 7 L 3 1  G 0  4 1


WALLWASHER chrome reflector, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
8.7 W	2700 K	856 lm	98 lm/W	0 9 0 - 7 L 3 9  A 0 0 4 1
	3000 K	856 lm	98 lm/W	0 9 0 - 7 L 3 0  A 0 0 4 1
	3500 K	891 lm	102 lm/W	0 9 0 - 7 L 3 2  A 0 0 4 1
	4000 K	909 lm	104 lm/W	0 9 0 - 7 L 3 1  A 0 0 4 1

Order options

CONTROL		COLOUR		COLOUR	
non DIM	1	black reflector	B	jet black	RAL 9005
DALI-2	3	chrome reflector	0	traffic white	RAL 9016

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready


Mounting accessories (required)



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L-W-H (mm)	ORDER CODE
12.5/15/20/25 mm	85-47-47	0 9 0 - 7 L 2 0 1 0 0

for UNICO L2 and UNICO wall recessed 1 lamp



MOUNTING SET trimless for plasterboard ceilings

PLASTERBOARD CEILING THICKNESS	L-W-H (mm)	ORDER CODE
12.5/15/20/25 mm	122-47-47	0 9 0 - 7 L 3 0 1 0 0

for UNICO L3



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L-W-H (mm)	ORDER CODE
jet black	101-63-30	0 9 0 - 7 L 2 0 2 0 B
traffic white	101-63-30	0 9 0 - 7 L 2 0 2 0 W

for UNICO L2 and UNICO wall recessed 1 lamp



MOUNTING SET with trim for intermediate ceilings, 2-25 mm

COLOUR	L-W-H (mm)	ORDER CODE
jet black	138-63-30	0 9 0 - 7 L 3 0 2 0 B
traffic white	138-63-30	0 9 0 - 7 L 3 0 2 0 W

for UNICO L3

Mounting tools accessories (optional)

DISMOUNTING TOOL

L-W-H (mm)	ORDER CODE
70-30-2	0 9 0 - 0 0 2 1 0 0

Order options

CONTROL		COLOUR		COLOUR	
non DIM	1	black reflector	B	jet black	RAL 9005
DALI-2	3	chrome reflector	0	traffic white	RAL 9016

Benaki Museum Shop, Navarino Agora

Griechenland

Architekt

STUDIOLAV and
Kostantia Manthou

Fotograf

Manos Chatzikonstantis



Verwendete Produkte



**UNICO L2 / L3 basic
recessed**



**UNICO L2 / L3
recessed**





Forschungsbau Weltbeziehungen Universität Erfurt

Deutschland

Lighting Design
lichtraum

Fotograf
Steven Neukirch
Fotografie



Verwendete Produkte



LENO surface



**UNICO L2 / L3 basic
recessed**



**UNICO L2 / L3
recessed**

