
XAL 23


EN DE

News



Contents

MOVE IT 10
installation track



recessed trimless **12** | surface square **12** | suspended square **14** | suspended round **14** | pole square / round **16**


4

linear insets




SPOT LINE direct **20** | OPAL direct **20** | DARKLIGHT direct **20** | indirect **20**

decorative insets



TILA **24** | TARO **32** | GIRA **36** | NOBA **40**


TUBO 60
surface



system **48** | CONEX system **48** | suspended | system **48** | CONEX system **48**

44


SETA
ceiling



system **48** | CONEX system **48** | suspended | system **48** | CONEX system **48**

44

MITA
ceiling



circle **58** | suspended **64**

54

SPIO
recessed



20 downlight **72** | 20 wallwasher **72** | 60 downlight **76** | 60 adjustable **76**

68


SQUADRO
recessed



wallwasher **84** | track | wallwasher **88**

80


BO
intrack



32 2/3 lamps **96** | 45 2/3 lamps **96** | 55 1/2 lamps **96**

92

VARO
track



80 S **104** | 110 S **108**

102


MILA
ceiling



system **116**

112


FRAME 40
recessed trim



system **124** | system **130**

120


MINO 40
ceiling



system **128** | system **130** | suspended | 40 system **128** | 40 system **130**

120

Elegance on track



MOVE IT 10 system


EN MOVE IT 10 is a particularly slim track system. The dimmable low-voltage track, available as a recessed, surface-mounted, suspended or pole version, is impressive thanks to its unusually slender cross-section. Both the round and square forms have a clear width of only 10 mm. MOVE IT 10's design is minimalistic. The insets' adapter are fully hidden in the track. The tracks are available in black, white and chrome (standard for the round version). They are connected by Corner or Curve elements for an edgy or softly rounded appearance. Extend MOVE IT 10 with various linear or design-oriented insets for maximum planning freedom for your interior concept.

DE Eine besonders schlanke Stromschiene – das ist MOVE IT 10. Die dimmbare Niedervolt-Stromschiene, als Einbau-, Anbau-, abgehängte oder Pole Variante verfügbar, besticht durch ihren ungewöhnlich schlanken Querschnitt: Sowohl in runder als auch in eckiger Form misst ihre lichte Breite lediglich 10 mm. Das minimalistische Design setzt sich auch in den Adaptern fort, die vollständig in den Schienen verschwinden. Die Schienen sind in den Farben Schwarz, Weiß und Chrom (bei der runden Variante) erhältlich. Verbunden werden sie durch Corner-, oder Curve-Elemente zu wahlweise klaren Ecken oder weichen Rundungen. MOVE IT 10 kann mit verschiedenen linearen oder designorientierten Einsätzen erweitert werden – für größte Freiheit bei der Planung Ihres Interior Konzepts.


Types




Mountings



Configurations



Light distributions



Mounting options

EN Depending on the desired appearance and installation, the 48 V track system is available as a trimless recessed-mounted, surface-mounted, suspended or pole version.

DE Je nach gewünschter Erscheinung und Montage ist das 48 V-Stromschienensystem als randlose Einbau-, Anbau-, abgehängte oder als Pole Variante verfügbar.





Create individual arrangements


EN Let your creativity run wild and arrange MOVE IT 10 at will. Special Curve and Corner elements enable the straight tracks to be connected to form harmonious curves or precise corners. Since all elements fit together, you can configure your ideal bespoke system.


DE Lassen Sie Ihrer Kreativität freien Lauf und arrangieren Sie MOVE IT 10 nach Ihren Vorstellungen. Durch spezielle Curve- und Corner-Elemente lassen sich die geradlinigen Schienen zu harmonischen Kurven oder präzisen Ecken verbinden. Da alle Elemente zueinander passen, können Sie das System individuell nach Wunsch und verfügbarem Platz konfigurieren.

Track shapes

EN In both the round and square form, the track opens options for flexible application. Their track diameter is only 29 mm, presenting a reduced and sleek appearance. Many insets offer an optional flush adapter to create an even, visually calm ceiling appearance.

DE In runder und eckiger Form bietet die Stromschiene flexible Einsatzmöglichkeiten. Ihr Durchmesser misst bis zu 29 mm – für eine reduzierte und edle Optik. Viele Insets verfügen über einen bündigen Adapter, wodurch ein ebenes, optisch ruhiges Deckenbild entsteht.





Colour variety

EN The tracks are available in the colours black and white, delivering discreet elegance. The round track comes additionally in chrome. In addition, for some insets you have the choice between the trend colours chrome, rose gold, gun metal, brushed aluminium and brushed brass.

DE Dezente Eleganz: Die Stromschienen sind in den Farben Schwarz und Weiß erhältlich. Die runde Schiene ist zudem in der Farbe Chrom verfügbar. Zusätzlich haben Sie bei einigen Insets die Wahl zwischen den Trendfarben Chrom, Roségold, Gun Metal, Aluminum gebürstet und Messing gebürstet.

Installation tracks

recessed square	●
surface square	○ ●
suspended square	○ ●
suspended round	○ ● ◢
pole square	○ ●
pole round	○ ● ◢

Decorative insets

GIRA	○ ●
NOBA	○ ● ◌ ◌ ◌ ◌ ◌
TARO	○ ● ◌ ◌ ◌ ◌ ◌
TILA	○ ● ◌ ◌ ◌ ◌ ◌




white black brushed aluminium gun metal brushed brass chrome rose gold





Mounting variety


EN With precise corners or harmonious curves, the MOVE IT 10 system sets no limits to creativity. Elegant insets for different applications make the track system even more flexible.

DE Egal ob mit präzisen Ecken oder harmonischen Kurven, das MOVE IT 10 System setzt der Kreativität keine Grenzen. Elegante Insets für verschiedene Anwendungen machen das Schienensystem noch flexibler.









Connector overview

EN A large selection of different connectors – in L-, T-, X-shape – provides even more flexibility. With the Ceiling to Wall Connector, roof slopes with different angles can also be realised.

DE Für noch mehr Flexibilität sorgt eine große Auswahl an unterschiedlichen Verbindern – in L-, T-, X-Form. Mit dem Ceiling to Wall Connector lassen sich zudem Dachschrägen mit verschiedenen Winkeln realisieren.

1 Linear Connector



2 L-Connector




3 T-Connector



4 X-Connector




5 Flex Connector



6 Ceiling to Wall Connector




7 Level Connector



EN With the Level Connector, two tracks that are placed on top of each other can now be mechanically and electrically connected to each other. This creates new application possibilities.

DE Mit dem Level Connector können nun zwei Schienen, die übereinander geführt werden, mechanisch und elektrisch miteinander verbunden werden. Dadurch entstehen spannende neue Anwendungsmöglichkeiten.





8 Pass Through Connector



EN With the Pass Through Connector (patent pending) the direct and indirect light insets in the H-track can be electrically connected to each other.

DE Mit dem, zum Patent angemeldeten, Pass Through Connector können die direkten und indirekten Lichteinsätze in der H-Schiene elektrisch miteinander verbunden werden.





DESIGN AWARD 2023

MOVE IT 10 system

recessed trimless / surface


EN Thin extruded aluminium profile with 16 mm (trimless) or 11 mm (surface) height and 10 mm width groove; optionally for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5 mm ceiling thickness; MOVE IT 10 trimless profile with processing protection against penetration of filler; or for wall-/ceiling surface mounting; designed for continuous lighting systems; flexible system design through L, T or X connectors or by means of FLEX or LEVEL connectors; with integrated power track profile for take off of supply voltage and DALI-2 signal; surface anodised or powder coated; insets can be installed flexibly and without tools by means of clip mount

DE Niedriges Aluminiumstrangpressprofil mit 16 mm (trimless) bzw. 11 mm (surface) Höhe und 10 mm Fugenbreite; wahlweise für den randlosen Einbau in Gipskartondecken (Wand- oder Deckenmontage) mit 12,5 mm Deckenstärke; MOVE IT 10 trimless Profil mit Verarbeitungsschutz gegen Eintringen von Spachtelmasse; oder für Wand-/Deckenanbaumontage; ausgelegt für durchgehende Lichtsysteme; flexibler Systemaufbau durch L-, T- oder X-Verbinder bzw. mittels FLEX- oder LEVEL-Verbinder; mit integriertem Stromschienenprofil für Abnahme von Versorgungsspannung und DALI-2 Signal; Oberfläche eloxiert bzw. pulverbeschichtet; flexible und werkzeuglose Montage der Einsätze durch Clipverschluss


Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
L90 @ 50 000 h
DALI-2


Types



Configurations



Colours



custom cut on building site

Order options

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

Options on request


CONNECTOR

T connector mechanical
T connector electrical
X connector mechanical
X connector electrical

only for recessed trimless

MOVE IT 10 trimless


DALI-2 | 48V | TRACK max. 6,67 A | pending | CB pending



INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-111303 8
2100	channel	030-111503 8
3100	channel	030-111703 8
custom cut	channel	E83610 · · · · 8

*incl. plasterin protection cover




END CAPS / CONNECTORS

TYPE	ORDER CODE
end caps (pair)	030-112001 8
linear connector electrical	030-210113
L connector electrical	030-211113
linear connector mechanical	030-113401 8
L connector mechanical	030-113501 8

more electrical and mechanical connectors see p. 19


MOVE IT 10 surface

DALI-2 | 48V | TRACK max. 6,67 A | pending | CB pending



INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-121303
2100	channel	030-121503
3100	channel	030-121703
custom cut	channel	E83620 · · · ·
R 300	curve channel	030-123103
R 500	curve channel	030-123203



END CAPS / CONNECTORS


TYPE	ORDER CODE
end caps (pair)	030-122001
linear connector electrical	030-210113
L connector electrical	030-211113
T connector electrical	030-212113
X connector electrical	030-213113
linear connector mechanical	030-123401
L connector mechanical	030-123501
T connector mechanical	030-123601
X connector mechanical	030-123701

more electrical and mechanical connectors see p. 19

Accessories

BLIND COVER

L (mm)		ORDER CODE
1100	blind cover	030-100301
2100	blind cover	030-100501
3100	blind cover	030-100701
custom cut	blind cover	E83600 · · · ·



ELECTRICAL ACCESSORIES

TYPE	ORDER CODE
power feeder (only for surface)	030-252303
internal power feeder (incl. cable 2000 mm)	030-252503



DESIGN AWARD 2023

MOVE IT 10 system

suspended


EN Thin extruded aluminium profile with 10 mm width groove; choice of angular (38 mm height) or tubular (28 mm height) design; for suspended mounting (cable suspension, height adjustment without tools, incl. black feed); with integrated power track profile on both sides for take off of supply voltage and DALI-2 signal; power supply and DALI-2 signal for both power tracks with only one feed by means of pass-through connector; designed for continuous lighting systems; flexible system design through L, T or X connectors or by means of LEVEL connectors; surface anodised or powder coated; insets can be installed flexibly and without tools by means of clip mount

DE Niedriges Aluminiumstrangpressprofil mit 10 mm Fugenbreite; wahlweise kantige (38 mm Höhe) bzw. tubulare (28 mm Höhe) Bauform; für abgehängte Montage (Seilabhängung, werkzeuglose Höhenverstellung, inkl. schwarzer Einspeiseleitung); mit beidseitig integriertem Stromschienenprofil für Abnahme von Versorgungsspannung und DALI-2 Signal; Spannungsversorgung und DALI-2 Signal für beide Stromschienen mit nur einer Einspeisung durch pass through Verbinder; ausgelegt für durchgehende Lichtsysteme; flexibler Systemaufbau durch L-, T- oder X-Verbinder bzw. mittels LEVEL-Verbinder; Oberfläche eloxiert bzw. pulverbeschichtet; flexible und werkzeuglose Montage der Einsätze durch Clipverschluss


Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
L90 @ 50 000 h
DALI-2

Types




Configurations



Colours





custom cut on building site

Order options

CONTROL
DALI-2

MATERIAL COLOUR
○ traffic white RAL 9016 — 7
● jet black RAL 9005 — 8


MATERIAL COLOUR CABLE SUSPENSION
chrome — 4
● jet black RAL 9005 — 8

Options on request

MATERIAL COLOUR MOVE IT 10 ROUND
chrome

MOVE IT 10 square suspended

DALI-2 | 48V | TRACK max. 6,67 A | pending | CB pending



INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-131303
2100	channel	030-131503
3100	channel	030-131703
custom cut	channel	E83630
R 300	curve channel	030-133103
R 500	curve channel	030-133203


END CAPS / CONNECTORS

TYPE	ORDER CODE
end caps (pair)	030-132001
linear connector electrical	030-210113
L connector electrical	030-211113
T connector electrical	030-212113
X connector electrical	030-213113
linear connector mechanical	030-133401
L connector mechanical	030-133501
T connector mechanical	030-133601
X connector mechanical	030-133701

more electrical and mechanical connectors see page 19

MOVE IT 10 round suspended

DALI-2 | 48V | TRACK max. 6,67 A | pending | CB pending



INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-141303
2100	channel	030-141503
3100	channel	030-141703
custom cut	channel	E83640
R 300	curve channel	030-143103
R 500	curve channel	030-143203

END CAPS / CONNECTORS

TYPE	ORDER CODE
end caps (pair)	030-142001
linear connector electrical	030-210113
L connector electrical	030-211113
T connector electrical	030-212113
X connector electrical	030-213113
linear connector mechanical	030-143401
L connector mechanical	030-143501
T connector mechanical	030-143601
X connector mechanical	030-143701


more electrical and mechanical connectors see page 19

Accessories

BLIND COVER see page 17

INDIRECT LIGHT INSET see page 17

CABLE SUSPENSION / CANOPY / ELECTRICAL ACCESSORIES



TYPE	L (mm)	ORDER CODE
cable suspension	1500	030-223001
cable susp. linear connector	1500	030-221001
cable susp. linear conn. electrical	1500	030-222001
canopy square	90·90·22	005-231121
canopy round	ø90·22	005-260003
internal power feeder (incl. cable 2000 mm)		030-252503
pass through connector electrical (pair)		030-217113

more electrical and mechanical connectors see page 19




MOVE IT 10 system

pole

EN Thin extruded aluminium profile with 10 mm width groove; choice of angular (38 mm height) or tubular (28 mm height) design; for vertical and horizontal mounting; easy installation of the mounting set, incl. feed; with integrated power track profile on both sides for take off of supply voltage and DALI-2 signal; power supply and DALI-2 signal for both power tracks with only one feed by means of pass-through connector; designed for continuous lighting systems; flexible system design through L, T or X connectors or by means of LEVEL connectors; surface anodised or powder coated; insets can be installed flexibly and without tools by means of clip mount

DE Niedriges Aluminiumstrangpressprofil mit 10 mm Fugenbreite; wahlweise kantige (38 mm Höhe) bzw. tubulare (28 mm Höhe) Bauform; für vertikale und horizontale Montage; einfache Installation des Montagesets, inkl. Einspeisung; mit beidseitig integriertem Stromschienenprofil für Abnahme von Versorgungsspannung und DALI-2 Signal; Spannungsversorgung und DALI-2 Signal für beide Stromschienen mit nur einer Einspeisung durch pass through Verbinder; ausgelegt für durchgehende Lichtsysteme; flexibler Systemaufbau durch L-, T- oder X-Verbinder bzw. mittels LEVEL-Verbinder; Oberfläche eloxiert bzw. pulverbeschichtet; flexible und werkzeuglose Montage der Einsätze durch Clipverschluss




custom cut on building site


Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
L90 @ 50 000 h
DALI-2

Types



Mounting types



Colours

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

Options on request

MATERIAL COLOUR
MOVE IT 10 ROUND

chrome

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black

MOVE IT 10 square pole

DALI-2 · 48 V · TRACK max. 6,67 A · pending · CB pending



INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-131303
2100	channel	030-131503
3100	channel	030-131703
custom cut	channel	E83630



MOUNTING SET

TYPE	ORDER CODE
floor to ceiling set (pair)	030-134101
wall to wall set (pair)	030-134101
floor to wall set (wall bracket 400 mm incl. end cap)	030-134201
ceiling set (incl. end cap)	030-134301

MOVE IT 10 round pole

DALI-2 · 48 V · TRACK max. 6,67 A · pending · CB pending



INSTALLATION TRACK

L (mm)		ORDER CODE
1100	channel	030-141303
2100	channel	030-141503
3100	channel	030-141703
custom cut	channel	E83640




MOUNTING SET

TYPE	ORDER CODE
floor to ceiling set (pair)	030-144101
wall to wall set (pair)	030-144101
floor to wall set (wall bracket 400 mm incl. end cap)	030-144201
ceiling set (incl. end cap)	030-144301

LIGHT INSET 10

CRI ≥ 90 · RG 0 IEC 62471 · DALI 1 ADDR. · 48 V · pending · CB pending




INDIRECT incl. feeder

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
15 W	2700 K	1370 lm	1000	030-6330::38B
	3000 K	1450 lm		
	4000 K	1530 lm		
30 W	2700 K	2750 lm	2000	030-6370::38B
	3000 K	2900 lm		
	4000 K	3050 lm		

Accessories

BLIND COVER

L (mm)		ORDER CODE
1100	blind cover	030-100301
2100	blind cover	030-100501
3100	blind cover	030-100701
custom cut	blind cover	E83600



ELECTRICAL ACCESSORIES

TYPE	ORDER CODE
internal power feeder (incl. cable 2000 mm)	030-252503
pass through connector electrical (pair)	030-217113



ELECTRICAL accessories

MOVE IT 10 system


EN Mechanical and electrical connectors to MOVE IT 10 system; in L-, T- or X-shape; or FLEX, CEILING TO WALL or LEVEL connectors, as well as PASS THROUGH connectors; for flexible system design; different converters for the entire MOVE IT system

DE Mechanische und elektrische Verbinder zu MOVE IT 10 system; in L-, T- oder X-Form; bzw. FLEX-, CEILING TO WALL- oder LEVEL-Verbinder, sowie PASS THROUGH-Verbinder; für flexiblen Systemaufbau; unterschiedliche Konverter für gesamtes MOVE IT system

Types

1. **Linear Connector**
2. **L-Connector**
3. **T-Connector**
4. **X-Connector**
5. **Flex Connector**
6. **Ceiling to Wall Connector**
7. **Level Connector**
8. **Pass Through Connector**

Configurations



Colours



Order options

CONNECTOR MECHANICAL T

recessed*	1
surface	2
suspended square	3
suspended round	4

*T- and X-connector on request

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white* RAL 9016	7
● jet black RAL 9005	8

*not for mechanical recessed trimless


Options on request

CONNECTOR

T connector electrical
T connector mechanical
X connector electrical
X connector mechanical


only for recessed trimless

Electrical accessories




LINEAR CONNECTOR

TYPE	ORDER CODE
linear connector electrical	030-210113
linear connector mechanical	030-1T3401




L CONNECTOR

TYPE	ORDER CODE
L connector electrical	030-211113
L connector mechanical	030-1T3501




T CONNECTOR

TYPE	ORDER CODE
T connector electrical	030-212113
T connector mechanical	030-1T3601




X CONNECTOR

TYPE	ORDER CODE
X connector electrical	030-213113
X connector mechanical	030-1T3701




FLEX CONNECTOR

TYPE	ORDER CODE
flex connector electrical	030-214113



CEILING TO WALL CONNECTOR

TYPE	ORDER CODE
ceiling to wall connector electrical	030-216113



LEVEL CONNECTOR


TYPE	ORDER CODE
level connector electrical	030-215113



PASS THROUGH CONNECTOR

TYPE	ORDER CODE
pass through connector electrical (pair)	030-217113


electrical connection from direct to indirect and vice versa



POWER FEEDER

TYPE	ORDER CODE
power feeder (only for surface)	030-252303
internal power feeder (incl. cable 2000 mm)	030-252503

POWER SUPPLY EXTERNAL supply 220-240 V AC, 48 V, 50-60 Hz




TYPE	EFFICIENCY	MOUNTING	L·W·H (mm)	ORDER CODE
60 W ⧈ PC II	η 88 %	external	163·43·32	002-62133
150 W ⧈ PC II	η 92 %	external	350·30·18	002-62135
250 W ⧈ PC II	η 93 %	external	400·40·22	002-62139

ENEC approved, incl. feeder cable 2000 mm

POWER SUPPLY BASIC 48 V


220–240 V | 50–60 Hz | ⧈ PC II | Lifetime @ 120 W, 45° ambient temp.
cascadable max. 3 devices




TYPE	EFFICIENCY / LIFETIME	W·H·D (mm)	ORDER CODE
160 W	η 94.5 % / > 100.000 h	72·90·63	005-6520210

DIN RAIL POWER SUPPLY PRO 48 V

220–240 V | 50–60 Hz | ⏚ PC I | MTBF @ 55° ambient temperature
cascadable max. 5 devices (240 W) or 3 devices (480 W)



TYPE	EFFICIENCY / MTBF	W·H·D (mm)	ORDER CODE
240 W	η 92 % / > 400.000 h	60·125·100	005-6220110
480 W	η 93 % / > 350.000 h	120·125·100	005-6220210




Quickinfo


2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 105 lm / W
DALI-2

Types


spot line




opal



darklight




indirect



Colour

Light distributions



Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2


MATERIAL COLOUR

● jet black RAL 9005

LIGHT OPTIC


spot line
opal high performance
darklight
indirect

LIGHT INSET 10




SPOT LINE

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
8.5 W	2700 K	420 lm	300	030-6110 :: 38M
	3000 K	460 lm		
	4000 K	480 lm		




OPAL HIGH PERFORMANCE

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5 W	2700 K	520 lm	500	030-6120 :: 38H
	3000 K	520 lm		
	4000 K	525 lm		



DARKLIGHT

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
5.7 W	2700 K	280 lm	300	030-6210 :: 38M
	3000 K	280 lm		
	4000 K	285 lm		




INDIRECT incl. feeder

INS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
15 W	2700 K	1370 lm	1000	030-6330 :: 38M
	3000 K	1450 lm		
	4000 K	1530 lm		
30 W	2700 K	2750 lm	2000	030-6370 :: 38M
	3000 K	2900 lm		
	4000 K	3050 lm		

DESIGN AWARD 2023

SPOT LINE / OPAL / DARKLIGHT

linear inset 10




flush mounted

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black

Private Residence
Visualisation





DESIGN AWARD 2023


TILA
decorative inset 10

Quickinfo


2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 81 lm / W
DALI-2

Types

adjustable rod



suspended



Colours




Light distributions

TILA 16




TILA 22 / 32





365° rotatable
135° tiltable



free positioning by cable and hook



flush adapter mounting

Order options

HOUSING HEIGHT TILA 16 L

80 mm	0
600 mm	1

HOUSING HEIGHT TILA 22 L

100 mm	3
300 mm	4

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
brushed aluminium	6
chrome	4

MATERIAL COLOUR ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE TILA 16

medium 20°	M
flood 40°	F

BEAM ANGLE TILA 22 / 32

spot 14°	S
medium 24°	M
flood 45°	F


Options on request

MATERIAL COLOUR

gun metal	
brushed brass	
rose gold	


INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour white, medium

TILA 16



ADJUSTABLE


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
5 W	2700 K	230 lm	030-6500 ⁘ 3 ◪ ▲
	3000 K	240 lm	
	4000 K	250 lm	



SUSPENDED


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
5 W	2700 K	230 lm	030-66 L 0 ⁘ 3 ◪ ▲
	3000 K	240 lm	
	4000 K	250 lm	

TILA 22



ADJUSTABLE


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
10.5 W	2700 K	415 lm	030-6530 ⁘ 3 ◪ ▲
	3000 K	440 lm	
	4000 K	460 lm	



SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
10.5 W	2700 K	415 lm	030-66 L 0 ⁘ 3 ◪ ▲
	3000 K	440 lm	
	4000 K	460 lm	

TILA 32



ADJUSTABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	720 lm	030-6560 ⁘ 3 ◪ ▲
	3000 K	850 lm	
	4000 K	900 lm	

Mounting accessories



HOOK ceiling mounted

TYPE	Ø·H (mm)	ORDER CODE
hook	16·30	030-100001 ■

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø·H (mm)	ORDER CODE
TILA 22	20·3	007-1965118
TILA 32	30·3	007-1965168

Jewellery Shop
Visualisation



Private Residence
Visualisation





Private Residence
Visualisation





DESIGN AWARD 2023


TARO
decorative inset 10

Quickinfo


2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 83 lm / W
DALI-2

Types

square track



round track



Colours



Light distributions

TARO 32



TARO 45





wallwasher floor 360° rotatable



wallwasher floor

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2

MATERIAL COLOUR

traffic white RAL 9016	7
jet black RAL 9005	8
brushed aluminium	6
chrome	4

BEAM ANGLE TARO 32

spot 18°	S
medium 23°	M
flood 37°	F

BEAM ANGLE TARO 45

medium 24°	M
flood 39°	F

Options on request


MATERIAL COLOUR

- gun metal
- brushed brass
- rose gold

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour white, medium


TARO 32

CRI ≥90 · DALI 1 ADDR. · 48 V · pending · CB pending



DOWNLIGHT SQUARE TRACK

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	720 lm	030-6700 3 ◪ ▲
	3000 K	860 lm	
	4000 K	900 lm	




DOWNLIGHT ROUND TRACK

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	720 lm	030-6740 3 ◪ ▲
	3000 K	860 lm	
	4000 K	900 lm	


TARO 45

CRI ≥90 · DALI 1 ADDR. · 48 V · pending · CB pending



DOWNLIGHT SQUARE TRACK

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15 W	2700 K	1000 lm	030-6710 3 ◪ ▲
	3000 K	1100 lm	
	4000 K	1150 lm	




DOWNLIGHT ROUND TRACK

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
15 W	2700 K	1000 lm	030-6750 3 ◪ ▲
	3000 K	1100 lm	
	4000 K	1150 lm	


TARO 45 wallwasher floor

360° · CRI ≥90 · DALI 1 ADDR. · 48 V · pending · CB pending



DOWNLIGHT SQUARE TRACK

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
9 W	2700 K	530 lm	030-6780 3 ◪ W
	3000 K	570 lm	
	4000 K	580 lm	



DOWNLIGHT ROUND TRACK

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
9 W	2700 K	530 lm	030-6790 3 ◪ W
	3000 K	570 lm	
	4000 K	580 lm	


Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
TARO 32	30·4	007-1965168
TARO 45	42·3	007-1965188

Jewellery Shop
Visualisation






Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 79 lm / W
DALI-2

Type



Colours

Light distributions



Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL


DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE

medium 20°	M
flood 40°	F




GIRA

360° | CRI ≥ 90 | DALI 1 ADDR. | 48 V | pending | CB pending

DOWNLIGHT ROTATABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
19 W	2700 K	1350 lm	0 3 0 - 6 4 1 0 ⁘ 3 ◪ ▲
	3000 K	1400 lm	
	4000 K	1450 lm	

GIRA wallwasher floor



360° | CRI ≥ 90 | DALI 1 ADDR. | 48 V | pending | CB pending

WALLWASHER FLOOR ROTATABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11 W	2700 K	730 lm	0 3 0 - 6 4 3 0 ⁘ 3 ◪ W
	3000 K	770 lm	
	4000 K	800 lm	

DESIGN AWARD 2023

GIRA
decorative inset 10


360°
rotatable


wallwasher
floor


INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour white, medium

Private Residence
Visualisation












NOBA
decorative inset 10

Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 110 lm / W
DALI-2

Types



Colours



Light distribution



Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2

MATERIAL COLOUR

traffic white RAL 9016	7
jet black RAL 9005	8
brushed aluminium	6
chrome	4

MATERIAL COLOUR ACCESSORIES

traffic white RAL 9016	7
jet black RAL 9005	8

BEAM ANGLE

direct 80°


Options on request

MATERIAL COLOUR

- gun metal
- brushed brass
- rose gold


INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for CRI ≥ 90, colour white

NOBA 40



SPOTLIGHT ADJUSTABLE


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.5 W	2700 K	465 lm	030-680030
	3000 K	480 lm	
	4000 K	500 lm	



DOWNLIGHT SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.5 W	2700 K	465 lm	030-690030
	3000 K	480 lm	
	4000 K	500 lm	


NOBA 50



DOWNLIGHT SUSPENDED


INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
9 W	2700 K	695 lm	030-691030
	3000 K	725 lm	
	4000 K	760 lm	

NOBA 60



SPOTLIGHT ADJUSTABLE

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
10 W	2700 K	715 lm	030-682030
	3000 K	745 lm	
	4000 K	780 lm	



DOWNLIGHT SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
10 W	2700 K	715 lm	030-692030
	3000 K	745 lm	
	4000 K	780 lm	


Mounting accessories



HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16·30	030-100001

Private Residence
Visualisation





Perfect allrounder



TUBO / SETA 60 CONEX system

EN TUBO and SETA make a name for themselves as uniform and minimalist lighting system luminaires that can be flexibly joined by various connecting elements. The luminaires are available for wall and ceiling mounting, as well as in suspended pendant versions. Thanks to their opal cover, the TUBO system luminaire delivers uniform ambient illumination and the characteristic beam angle of up to 340° ensures a soft ceiling illumination that helps build a pleasant room atmosphere. SETA system luminaire's reflectors are particularly noteworthy and have been optimised for office spaces and designed for working at screens. The indirect light component creates a pleasant, homogeneous ceiling illumination for every work area. The CONEX connector (patent pending) grants the system a high degree of flexibility. As a mechanical and electrical L-, T-, and X-shaped connecting element, it allows implementation of geometric shapes over several levels.

DE Als Systemleuchten punkten TUBO und SETA als einheitliche und minimalistische Lichtsysteme, die durch verschiedene Verbindungselemente flexibel aneinandergereiht werden können. Die Leuchten sind für Wand- und Deckenmontage als auch in abgehängten Pendelvarianten erhältlich. Durch das Opal-Cover sorgt die TUBO Systemleuchte für eine gleichmäßige Grundausleuchtung und der charakteristische Abstrahlwinkel von bis zu 340° sorgt für eine leichte Deckenaufhellung, welche eine positive Raumatmosphäre unterstützt. Besonders hervorzuheben sind die eigens für Büroräumlichkeiten optimierten Reflektoren der SETA Systemleuchte, die speziell für Bildschirmarbeit konzipiert wurde. Durch den Indirektlichtanteil entsteht eine für jeden Arbeitsbereich angenehme, homogene Deckenaufhellung. Der zum Patent angemeldete CONEX Verbinder verleiht dem System hohe Flexibilität. Als mechanisches und elektrisches Verbindungselement in L-, T- und X-Form lassen sich geometrische Formen über mehrere Ebenen realisieren.

Type



60

Mountings




surface suspended

System configurations



linear L T X

Light distributions





opal reflector (UGR ≤ 19) direct direct indirect indirect


Connector CONEX

EN The patent pending CONEX connector system for the TUBO 60 system now offers even more design freedom. With the flexible lighting system, geometric shapes or exciting light sculptures can be created. Thanks to the mechanical and electrical connectors in L, T and X shapes, a visually uniform lighting system is created. In combination with the SETA system, various areas of application are possible - whether as corridor, office luminaire or visual guidance system.

DE Das zum Patent angemeldete CONEX Verbindungssystem für das TUBO 60 System bietet nun noch mehr Gestaltungsfreiraum. Mit dem flexiblen Beleuchtungssystem lassen sich geometrische Formen oder spannende Lichtskulpturen kreieren. Dank der mechanischen und elektrischen Verbindungselemente in L-, T- und X-Form entsteht ein optisch einheitliches Lichtsystem. In Kombination mit dem SETA System erschließen sich verschiedene Anwendungsbereiche – ob als Korridor-, Office-Leuchte oder visuelles Leitsystem.







Easy mounting


EN CONEX system luminaires are electrically and mechanical connected by a simple plug-in connection. This makes the installation of a complex lighting system simple, quick, and straightforward.

DE CONEX Systemleuchten werden durch eine simple Steckverbindung elektrisch und mechanisch verbunden. Dadurch ist die Montage eines komplexen Lichtsystems denkbar einfach, rasch und unkompliziert durchführbar.

340° light distribution

EN With its 340° beam pattern and opal cover, TUBO System delivers homogeneous illumination as well as slight ceiling brightening. This makes the system luminaire perfect for places where pleasant ambient lighting is desired, such as reception areas, corridors, or foyers.

DE Durch ihre 340° Abstrahlcharakteristik und Opal-Abdeckung erzielt TUBO System eine homogene Beleuchtung sowie eine leichte Deckenaufhellung. Dadurch ist die Systemleuchte perfekt geeignet für Orte, an denen eine angenehme Grundausleuchtung gewünscht ist, wie Empfangsbereiche, Flure oder Foyers.





Work-friendly light

EN As an office luminaire, SETA guarantees illumination that is compliant with workplace standards (up to UGR ≤ 16). Custom glare-free reflectors and the selected use of blind covers direct the light precisely to the work surface and reduce reflections. The direct / indirect version comes with special lens technology that distributes the indirect light component homogeneously and broadly towards the ceiling.


DE SETA als Office-Leuchte garantiert eine normgerechte Ausleuchtung von Arbeitsplätzen (bis zu UGR ≤ 16). Speziell entblendete Reflektoren und der gezielte Einsatz von Blind-Covers richten das Licht zielgenau auf die Arbeitsfläche und reduzieren Spiegelungen. Bei der direkt / indirekt Variante, verteilt eine spezielle Linsentechnik den sehr breit ausstrahlenden Indirektlichtanteil homogen an der Decke.

Advanced sensor technology

EN Special sensors expand the product family SETA with smart lighting control and collection of insightful data. The ESSENTIAL sensor enables dynamic adjustment of the lighting to ambient brightness and room activity. The SENSE version also measures values such as temperature, air quality, humidity and noise level. These data not only provide important insights into the ambient conditions and use of rooms, but also support energy savings in the long term.

DE Spezielle Sensoren erweitern die Produktfamilie SETA um smarte Lichtsteuerung. Der ESSENTIAL-Sensor ermöglicht die dynamische Anpassung der Beleuchtung an Umgebungshelligkeit und Raumaktivität. Die SENSE-Variante misst außerdem Werte wie Temperatur, Luftqualität, Luftfeuchtigkeit und Geräuschpegel. Diese Daten liefern nicht nur wichtige Erkenntnisse über die Umgebungsbedingungen und Nutzung von Räumen, sondern unterstützen langfristig Energieeinsparungen.






Indirect version

EN SETA indirect stands for the minimalist design of the product family and expands it with an indirect luminaire that provides homogeneous ceiling lighting. This creates a pleasant room feeling and the possibility to illuminate ceiling patterns harmoniously.

DE Die SETA indirect steht für das minimalistische Design der Produktfamilie und erweitert diese um eine Indirekt-Leuchte, welche für eine homogene Deckenaufhellung sorgt. So entsteht ein angenehmes Raumgefühl und die Möglichkeit, Deckenmuster harmonisch zu beleuchten.



reddot winner 2023

DESIGN AWARD 2022

TUBO / SETA 60 CONEX system

surface / suspended


EN Cylindrical lighting system in aluminium; powder coated; ceiling surface mounting or suspended mounting; height adjustment without tools; with transparent feeder cable; electrical connection of the luminaires via plug/socket system; optionally connectors (L-, T- or X-shape); luminaire connection rotatable around its own axis, which means that any spatial angle can be realized; optionally cylindrical HPO (High Performance Opal) cover or high gloss reflector with faceted design; light control via high quality lens system for homogeneous illumination (HPO); direct, indirect or direct / indirect light distribution (reflector); indirect light component with integrated PC boards and high quality lens system for homog. ceiling illumination, separately controllable; energy-eff. LEDs - very good colour rendering

DE Zylindrisches Lichtsystem aus Aluminium; pulverbeschichtet; Deckenanbau oder abgehängte Montage; werkzeuglose Höhenverstellung; inkl. transp. Einspeiseleitung; elektrische Verbindung der Leuchten mittels Buchse/Stecker System; optionale Verbinder (L-, T- oder X-Form); Leuchtenverbindung um eigene Achse drehbar, dadurch beliebige Raumwinkel realisierbar; wahlweise zylindr. HPO (High Performance Opal) Abdeckung oder hochglänzender Reflektor mit Facettenoptik; Lichtlenkung mittels hochwertiger Linsenoptik für homogene Ausleuchtung (HPO); direkte, indirekte bzw. direkt / indirekte Abstrahlcharakteristik (Reflektor); Indirektlichtanteil mit eigenen Platinen u. hochwertiger Linsenoptik für homog. Deckenaufhellung, separat steuerbar; energieeff. LEDs - sehr gute Farbwiedergabe


Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
UGR ≤ 19 / 65° ≤ 3000 cd/m²
opal up to 3230 lm / m
up to 160 lm / W
L90 @ 50 000 h
DALI-2
opal, reflector (UGR ≤ 19)

Types




CONEX connector




Colours




Light distributions






connector CONEX

combinable with TUBO & SETA



up to 160 lm / W (high efficiency)

DIN EN 12464-1 UGR ≤ 19



TUBO: direct 340° uniform illumination

SETA: direct and 170° indirect illumination

Order options

THROUGH WIRE TYPE

standard Ⓟ Ⓢ	2
CONEX L / T / X Ⓢ Ⓢ	3

between two CONEX connectors one CONEX luminaire or blind channel is needed

COLOUR TEMPERATURE

3000 K	5
4000 K	6

CONTROL

DALI-2

MATERIAL COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8

REFLECTOR COLOUR

⟋ chrome	R
● dark chrome	B

LUMINOUS FLUX value calculated for CRI ≥ 80, colour white, cover opal or reflector chrome



TUBO 60 surface / suspended

RG0 IEC 62471 · DALI 1 ADDR. · 220-240 V · X-PERT · X-PERT

OPAL 340° DIRECT

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
33 W	3000 K	3560 lm	1181	058-30o4::3◪O
	4000 K	3760 lm		
66 W	3000 K	7110 lm	2351	058-30o8::3◪O
	4000 K	7530 lm		
82 W	3000 K	8890 lm	2936	058-30o9::3◪O
	4000 K	9410 lm		





SETA 60 surface / suspended

UGR ≤19 · RG0 IEC 62471 · DALI 1 ADDR. · 220-240 V · X-PERT · X-PERT

REFLECTOR DIRECT

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
19.3 W	3000 K	2670 lm	1181	058-40o4::3◪■
	4000 K	3040 lm		
45 W	3000 K	6240 lm	2351	058-40o8::3◪■
	4000 K	7100 lm		
58 W	3000 K	8020 lm	2936	058-40o9::3◪■
	4000 K	9130 lm		



REFLECTOR DIRECT / INDIRECT

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
45 W (2×DALI)	3000 K	↧2670 / ↥3530 lm	1181	058-41o4::3◪■
	4000 K	↧3040 / ↥4010 lm		
92 W (2×DALI)	3000 K	↧6240 / ↥7050 lm	2351	058-41o8::3◪■
	4000 K	↧7100 / ↥8030 lm		
116 W (2×DALI)	3000 K	↧8020 / ↥8820 lm	2936	058-41o9::3◪■
	4000 K	↧9130 / ↥10000 lm		



INDIRECT

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
26.1 W	3000 K	3530 lm	1181	058-42o4::3◪
	4000 K	4010 lm		
52 W	3000 K	7050 lm	2351	058-42o8::3◪
	4000 K	8030 lm		
65 W	3000 K	8820 lm	2936	058-42o9::3◪
	4000 K	10000 lm		




BLIND CHANNEL incl. through wiring

L (mm)	ORDER CODE
585	058-49o203◪
1185	058-49o403◪
2351	058-49o803◪
2936	058-49o903◪


Accessories

see next page


Configuration example




Components




end cap
power feeder



middle
power feeder



L CONEX
power feeder




T CONEX
power feeder




linear
connector




end cap




L CONEX
connector




T CONEX
connector



X CONEX
connector



standard
luminaire



CONEX
luminaire

Order options

MATERIAL COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8

MATERIAL COLOUR CABLE SUSPENSION


chrome	0
● black	8

Accessories



END CAP


TYPE	ORDER CODE
end cap	058-301001



POWER FEEDER SURFACE

TYPE		ORDER CODE
end cap power feeder	Ⓟ	058-301021
middle power feeder*	ⓅⓅ	058-301121

*incl. feeder cable 5 × 1.5 mm²



POWER FEEDER SUSPENDED incl. feeder cable 5 × 1.5 mm²


TYPE		L (mm)	ORDER CODE
end cap power feeder	Ⓟ	1500	058-301041
middle power feeder*	ⓅⓅ	1500	058-301131
L CONEX power feeder**	ⓅⓅ	1500	058-301873
T CONEX power feeder**	ⓅⓅⓅ	1500	058-301883

*order cable suspension separately; **order CONEX cable suspension separately




LINEAR CONNECTOR

TYPE	ORDER CODE
linear connector mechanical	058-301311
linear connector mechanical & electrical ⓅⓈ	058-301312



LINEAR CONNECTOR SUSPENDED incl. cable suspension 1500 mm


TYPE	L (mm)	ORDER CODE
linear connector mechanical	1500	058-301321
linear connector mech. & electr. ⓅⓈ	1500	058-301322



CONEX CONNECTOR

TYPE	ORDER CODE
L CONEX connector mech. & electr. ⓅⓅ	058-301872
T CONEX connector mech. & electr. ⓅⓅⓅ	058-301882
X CONEX connector mech. & electr. ⓅⓅⓅⓅ	058-301892

order CONEX cable suspension separately



MOUNTING SET

TYPE	L (mm)	ORDER CODE
ceiling mounting set	75	058-301411
cable suspension	1500	058-301421
cable suspension angular max. 60°	1500	058-301431
CONEX cable suspension	1500	058-301811



CANOPY

TYPE	Ø·H (mm)	ORDER CODE
canopy	90·22	005-260003


for electrical system configuration see luminaire data sheet at xal.com




SENSOR DALI-2

TYPE		ORDER CODE
ESSENTIAL (brightness & presence)	ⓅⓅ	058-301911
SENSE (brightness, presence, temperature, sound pressure, humidity, CO_2)	ⓅⓅ	058-301921

XAL Headquarters Graz, AT





Discreet perfection




MITA


EN MITA combines high performance with a slim design language and its wide range of applications is impressive. The product family is available as recessed or surface-mounted luminaire in a round or square design as well as suspended version. All the versions of the luminaire have special reflectors for the best screen-compatible work lighting – perfect for use in offices or meeting rooms. The product family is available in the light colours 3000 K, 4000 K, or Tunable White. Optionally, the luminaire can be equipped with a presence and brightness sensor.

DE MITA vereint Leistungsstärke mit schlanker Formensprache und besticht durch vielfältige Einsatzmöglichkeiten. Die Produktfamilie ist als Einbau- oder Anbauleuchte in runder oder quadratischer Ausführung sowie als abgehängte Variante verfügbar. In allen Ausführungen verfügt die Leuchte über spezielle Reflektoren für bestes, bildschirmtaugliches Arbeitslicht – perfekt für den Einsatz in Büros oder Meetingräumen. Die Produktfamilie ist in den Lichtfarben 3000 K, 4000 K oder als Tunable White Option erhältlich. Optional kann die Leuchte mit einem Anwesenheits- und Helligkeitssensor ausgestattet werden.


Types




Mountings



Light distributions






Variety

EN MITA is characterised by an elegant design language with maximum efficiency and versatile application possibilities. The MITA product family is available as a recessed or surface-mounted luminaire in round and square versions, as well as a suspended variant. For a uniform ceiling appearance, the cover can simply be attached magnetically and is available as a reflector or opal cover.


DE MITA zeugt von eleganter Formensprache bei höchster Effizienz und besticht darüber hinaus durch ihre vielseitigen Einsatzmöglichkeiten. Die MITA Produktfamilie ist als Einbau- oder Anbauleuchte in runder sowie quadratischer Ausführung oder als abgehängte Variante erhältlich. Zudem ist MITA als Reflektor- oder Opal-Cover-Variante verfügbar. Für ein einheitliches Deckenbild kann die Abdeckung einfach magnetisch befestigt werden.



Advanced sensor technology

EN Special sensors expand the MITA product family with smart lighting control and collection of insightful data. The ESSENTIAL sensor enables dynamic adjustment of the lighting to ambient brightness and room activity. The SENSE sensor also measures values such as temperature, air quality, humidity and noise level. These data not only provide important insights into the ambient conditions and use of rooms, but also support energy savings in the long term.

DE Spezielle Sensoren erweitern die MITA Produktfamilie um smarte Lichtsteuerung. Der ESSENTIAL Sensor ermöglicht die dynamische Anpassung der Beleuchtung an Umgebungshelligkeit und Raumaktivität. Der SENSE Sensor misst außerdem Werte wie Temperatur, Luftqualität, Luftfeuchtigkeit und Geräuschpegel. Diese Daten liefern nicht nur wichtige Erkenntnisse über die Umgebungsbedingungen und Nutzung von Räumen, sondern unterstützen langfristig Energieeinsparungen.




ESSENTIAL sensor

- brightness
- presence


SENSE sensor

- brightness
- presence
- temperature
- humidity
- sound pressure
- CO_2



MITA suspended
opal
direct / indirect power

MITA suspended
reflector
direct / indirect power



MITA ceiling
opal
direct / indirect soft

MITA ceiling
reflector
direct / indirect soft

Light distribution

EN As an office luminaire, MITA guarantees the best possible working light. Special, glare-reduced reflectors direct the light precisely onto the work surface and reduce reflections. The opal cover ensures homogeneous room illumination. With the direct / indirect power version of the suspended luminaire, the indirect light component has a very wide beam and distributes the light evenly across the ceiling. The direct / indirect soft light component of the surface-mounted version produces a gentle and light ceiling illumination, making the luminaire appear to almost float.


DE Als Office-Leuchte garantiert MITA bestes Arbeitslicht. Speziell entblendete Reflektoren richten das Licht zielgenau auf die Arbeitsfläche und reduzieren Spiegelungen. Mit der Opal Abdeckung ist eine homogene Raumausleuchtung gegeben. Bei der direkt / indirekt power Variante der abgehängten Leuchte ist der Indirektlichtanteil sehr breit ausstrahlend und verteilt das Licht gleichmäßig an der Decke. Der direkt / indirekt soft Lichtanteil der Anbauvariante bewirkt eine sanfte und leichte Deckenaufhellung und lässt die Leuchte optisch beinahe schweben.



Discreet accentuation

EN MITA sets discreet accents for a pleasant room atmosphere. The product is available in black or white, and with or without a cover. The magnetic cover attaches easily and the indirect component provides gentle and light ceiling brightening.

DE MITA ceiling setzt diskrete Akzente für eine angenehme Raumatmosphäre. Sie ist erhältlich in Schwarz oder Weiß und wahlweise mit Abdeckung. Das Cover ist einfach magnetisch zu befestigen. Der Indirektanteil bewirkt eine sanfte und leichte Deckenaufhellung und lässt die Leuchte optisch beinahe schweben.







MITA circle

ceiling

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; luminaire housing set away from ceiling; electronic operating unit installed in the surface mounted housing; surface mounted housing aligned from the ring to the center; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high-gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; either with direct or direct / indirect light distribution; energy-efficient LEDs with very good colour rendering


DE Ringförmiger Leuchtenkörper aus Aluminiumdruckguss; extrem schlanke Bauform; Oberfläche pulverbeschichtet; Leuchtenkörper von der Decke abgesetzt; elektronisches Betriebsgerät im Anbaugehäuse verbaut; Anbaugehäuse vom Ring ins Zentrum ausgerichtet; optional: Blindabdeckung, mittels Magnet im Innenausschnitt befestigt, als Zubehör erhältlich; hochglänzender Reflektor mit Facettenoptik; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; wahlweise mit direkter bzw. direkt / indirekter Abstrahlcharakteristik; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
UGR ≤ 19 / 65° ≤ 1500 cd/m²
up to 158 lm/W
L90 @ 50 000 h
DALI-2, DALI-2 sensor
reflector (UGR ≤ 19), opal

Types

ceiling



Colours



luminaire reflector

Light distributions



direct direct indirect

Order options

COLOUR TEMPERATURE

3000 K	5
4000 K	6

CONTROL

DALI-2	3
DALI-2 ESSENTIAL sensor (brightness & presence)	B
DALI-2 SENSE sensor (brightness, presence, temp., sound pressure, humidity, CO_2)	P

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR COLOUR

⟋ chrome	R
● dark chrome	B

LIGHT OPTIC COVER

reflector (UGR ≤ 19)
opal


Options on request

COLOUR RENDERING INDEX

CRI ≥ 90




MITA circle 450 ceiling




REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4210 lm	074-751 1
	4000 K	4790 lm	
40 W	3000 K	5470 lm	074-752 1
	4000 K	6230 lm	




OPAL DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
24.9 W	3000 K	2770 lm	074-751 1 O
	4000 K	3150 lm	




REFLECTOR DIRECT / INDIRECT SOFT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	↧ 4220 / ↥ 72 lm	074-753 1
	4000 K	↧ 4800 / ↥ 82 lm	
40 W	3000 K	↧ 5490 / ↥ 94 lm	074-756 1
	4000 K	↧ 6240 / ↥ 107 lm	



OPAL DIRECT / INDIRECT SOFT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
24.9 W	3000 K	↧ 2700 / ↥ 136 lm	074-753 1 O
	4000 K	↧ 3080 / ↥ 155 lm	



Accessories

BLIND COVER

TYPE	ORDER CODE
MITA circle 450 ceiling	074-891162
MITA circle 450 ceiling sensor	074-891163



dark chrome reflector option



up to 158 lm / W (high efficiency)



sensor version available



version with opal cover




magnetic blind cover



DIN EN 12464-1 UGR ≤ 19

Light distribution



reflector (UGR ≤ 19)
direct

LUMINOUS FLUX value calculated for CRI ≥ 80, colour white, reflector chrome

Meeting room
Visualisation



Hallway
Visualisation





MITA circle

suspended

EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; either with direct or direct / indirect light distribution; energy-efficient LEDs with very good colour rendering


DE Ringförmiger Leuchtenkörper aus Aluminiumdruckguss; extrem schlanke Bauform; Oberfläche pulverbeschichtet; abgependelt; mit kürzbarer Pendelrohrabhängung (chrom), Einspeiseleitung in Pendelrohr; elektronisches Betriebsgerät im Baldachin verbaut; optional: Blindabdeckung, mittels Magnet im Innenausschnitt befestigt, als Zubehör erhältlich; hochglänzender Reflektor mit Facettenoptik; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; wahlweise mit direkter bzw. direkt / indirekter Abstrahlcharakteristik; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K
CRI ≥ 80, 3 SDCM
UGR ≤ 19 / 65° ≤ 1500 cd/m²
up to 160 lm/W
L90 @ 50 000 h
DALI-2, DALI-2 sensor
reflector (UGR ≤ 19), opal

Types

suspended



Colours



luminaire reflector

Light distributions



direct direct indirect



dark chrome reflector option



up to 160 lm / W (high efficiency)



sensor version available



version with opal cover



magnetic blind cover



DIN EN 12464-1 UGR ≤ 19

Order options

SUSPENSION

rod 1000 mm

COLOUR TEMPERATURE

3000 K	5
4000 K	6

CONTROL

DALI-2	3
DALI-2 ESSENTIAL sensor (brightness & presence)	B
DALI-2 SENSE sensor (brightness, presence, temp., sound pressure, humidity, CO_2)	P

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR COLOUR

⟋ chrome	R
● dark chrome	B

LIGHT OPTIC COVER

reflector (UGR ≤ 19)
opal

Options on request

SUSPENSION

rod 1000 mm white
rod 1000 mm black


COLOUR RENDERING INDEX

CRI ≥ 90

COLOUR TEMPERATURE

tunable white 2700 – 6500 K

LUMINOUS FLUX value calculated for CRI ≥ 80, colour white, reflector chrome



MITA circle 450 suspended

REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4210 lm	0 7 4 - 7 6 1 1
	4000 K	4790 lm	
41 W	3000 K	5470 lm	0 7 4 - 7 6 2 1
	4000 K	6230 lm	

OPAL DIRECT


SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
25.1 W	3000 K	2770 lm	0 7 4 - 7 6 1 1 O
	4000 K	3060 lm	

REFLECTOR DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
58 W	3000 K	↧ 4030 / ↥ 3780 lm	0 7 4 - 7 6 5 1
	4000 K	↧ 4600 / ↥ 4310 lm	

OPAL DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
58 W	3000 K	↧ 3140 / ↥ 3780 lm	0 7 4 - 7 6 5 1 O
	4000 K	↧ 3570 / ↥ 4310 lm	



Accessories

BLIND COVER

TYPE	ORDER CODE
MITA circle 450 suspended	0 7 4 - 8 9 1 1 6 2
MITA circle 450 suspended sensor	0 7 4 - 8 9 1 1 6 3

ALLPLAN Österreich GmbH
Graz, AT



Hidden talent




SPIO


EN Round, recessed SPIO spotlights bring special lighting to your rooms. The luminaire provides an impressive lighting effect, trimless or with a trim. The housing can be painted over, allowing the spotlight to blend seamlessly into the ceiling. The small light aperture of 10 mm makes the SPIO itself appear almost hidden – but the equally effective and calm overall impression is anything but invisible. The round, recessed spotlight is available with beam angles of 35° or 44° and can be rotated 360° in the housing and pivoted 30° in all directions. In addition, SPIO 20 is available with Wallwasher Floor optic, which creates an uniform wall illumination. These different lighting options mean that versatile designs for interiors are possible. SPIO is available in the light colours 2700 K, 3000 K, and 4000 K.

DE Mit den runden SPIO Einbaustrahlern bringen Sie eine besondere Beleuchtung in Ihre Räume. Die Leuchte sorgt für eine beeindruckende Lichtwirkung, randlos oder mit umlaufendem Rand. Das Gehäuse kann einfach überstrichen werden, wodurch sich der Strahler nahtlos ins Deckenbild einfügt. Die geringe Lichtaustrittsöffnung von 10 mm lässt SPIO selbst beinahe verborgen erscheinen – der effektvolle und ruhige Gesamteindruck ist jedoch alles andere als unsichtbar. Der runde Einbau-Spot ist mit den Ausstrahlwinkel von 35° oder 44° verfügbar und ist im Gehäuse um 360° drehbar und in alle Richtungen 30° schwenkbar. Zudem ist SPIO 20 mit Wallwasher Floor Optik verfügbar, wodurch eine gleichmäßige Wandaufhellung entsteht. Dadurch ergibt sich eine vielseitige Raumgestaltung mit unterschiedlichen Beleuchtungsmöglichkeiten. SPIO ist in den Lichtfarben 2700 K, 3000 K und 4000 K erhältlich.


Types



Mountings




Light distributions




High-efficiency lens

EN Large light output – almost unnoticed. SPIO has a special LFO lens, which is mounted at an exact distance from the light-emission surface, thus ensuring that no light beam appears on the inner surface of the housing. This reduces the light-emission surface, and SPIO illuminates the room almost unnoticed.

DE Großer Lichtoutput – nahezu unbemerkt. SPIO verfügt über eine spezielle LFO Linse, welche in einem exakten Abstand zur Lichtaustrittsfläche montiert wird. Dieser ist so bemessen, dass kein Lichtstrahl an der Innenfläche des Gehäuses auftritt. Dadurch wird die Lichtaustrittsfläche reduziert und SPIO beleuchtet den Raum nahezu unbemerkt.





Homogeneous appearance


EN SPIO is the right choice for a uniform ceiling appearance. Thanks to its extremely small light aperture of 10 mm, the recessed spotlight appears almost invisible. The effective lighting is rounded off by its minimalist design language.


DE Für ein einheitliches Deckenbild ist SPIO die richtige Wahl. Dank seiner ausgesprochen geringen Lichtaustrittsöffnung von 10 mm ist der Einbaustrahler beinahe unsichtbar. Die effektive Lichtwirkung wird abgerundet durch seine minimalistische Formensprache.

Light distribution

EN Despite its small emission surface, the recessed spotlight achieves a beam angle of either 35° or 44°. SPIO 20 is also available with Wallwasher Floor optic, which creates a homogeneous wall brightening effect. SPIO thus provides glare-free light and skilfully stages objects.

DE Trotz seiner geringen Austrittsfläche erreicht der Einbaustrahler einen Ausstrahlwinkel von wahlweise 35° oder 44°. SPIO 20 ist zudem mit Wallwasher Floor Optik erhältlich, wodurch eine homogene Wandaufhellung entsteht. Dadurch gibt SPIO blendfreies Licht und setzt Objekte gekonnt in Szene.





Smooth and invisible


EN The trimless SPIO 60 version can easily be maintained and adjusted thanks to its magnetic cover. The spotlight is completely fitted into a plasterboard ceiling. The recessed housing and ceiling can subsequently be painted over. The spots thus appear “invisible”, creating a homogeneous, effective overall impression.

DE Die randlose Variante von SPIO 60 ist durch die magnetische Abdeckplatte einfach zu warten und zu adjustieren. Der Strahler wird vollkommen in einer Gipskartondecke verbaut. Anschließend kann das Einbaugehäuse gemeinsam mit der Zimmerdecke überstrichen werden. Die Spots wirken dadurch „unsichtbar“ – es entsteht ein homogener wirkungsvoller Gesamteindruck.

Precise light adjustment

EN The adjustable version of SPIO 60, patent pending, can be moved in all directions thanks to a magnetic plate. The spotlight can thus both be rotated 360° and pivoted up to 30° in all directions. As a result, it offers the greatest flexibility in directing and guiding light exactly where it is desired.

DE Die zum Patent angemeldete adjustable Version von SPIO 60 kann aufgrund eines magnetischen Strahlerkopfes in alle Richtungen bewegt werden. Der Strahler kann zudem nicht nur um 360° gedreht, sondern auch um bis zu 30° in alle Richtungen geschwenkt werden. Dadurch bietet er größte Flexibilität in der Ausrichtung und Lenkung des Lichtes genau dorthin, wo es gewünscht ist.



SPIO 20

recessed


EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set with ball catch system or using snap spring closure; special mounting tool for easy installation of the trimless housing available as an accessory; for trimless installation in plasterboard ceilings; paintable light inset; shadow joint between light inset and mounting set optionally fillable; or with trim; with optional high quality lens system with precise radiation characteristic; or high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristics with different beam angles; uncluttered ceiling look through recessed lighting level; reduced light-emitting surface - only ø10 mm (DOWNLIGHT) or ø13 mm (WALLWASHER/FLOOR); no multiple shadows; energy-eff. LEDs - very good colour rendering

DE Runder Einbaustrahler aus Aluminiumdruckguss; werkzeuglose Montage im Montageset durch Kugelschnappsystem bzw. Schnappfederverschluss; spezielles Montagewerkzeug zur einfachen Installation des randlosen Gehäuses als Zubehör erhältlich; für randlosen Einbau in Gipskartondecken; überstreichbarer Lichteinsatz; Schattenfuge zwischen Lichteinsatz und Montageset optional verspachtelbar; oder mit umlaufendem Rand; wahlweise mit hochwertiger Linsenoptik mit präziser Abstrahlcharakteristik; oder hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; ruhiges Deckenbild durch zurückversetzte Leuchtenebene; reduzierte Lichtaustrittsfläche - nur ø10 mm (DOWNLIGHT) bzw. ø13 mm (WALLWASHER/FLOOR); keine Mehrfachschatten; energieeff. LEDs - sehr gute Farbwiedergabe

Quickinfo

2700 K, 3000 K
CRI ≥ 90, 3 SDCM
up to 70 lm/W
L95 @ 50 000 h
non DIM, DALI-2

Types




Colours



Light distributions






version with trim available


10 mm light ouput area



trimless installation



paintable cover



LFO lens technology



wallwasher floor

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR COLOUR

● jet black RAL 9005

paintable cover

BEAM ANGLE

flood 35°	F
wide flood 44°	W

Options on request

COLOUR RENDERING INDEX

CRI ≥ 95, 2 SDCM

COLOUR TEMPERATURE

4000 K

CONCRETE HOUSING

primed concrete ceiling
exposed concrete ceiling

REFLECTOR COLOUR

○ traffic white* RAL9016

*only for wallwasher / floor



INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, lens wide flood, 2700 K -3 %

SPIO 20 downlight

DOWNLIGHT TRIMLESS

INSET POWER	LUMINOUS FLUX	ORDER CODE
6.5 W 12 Vf 600 mA	435 lm	048-171010

TRIMLESS MOUNTING SET for plasterboard ceilings 9–25 mm

COLOUR	ORDER CODE
○ traffic white RAL9016	048-1698107

DOWNLIGHT TRIM

INSET POWER	LUMINOUS FLUX	ORDER CODE
6.5 W 12 Vf 600 mA	435 lm	048-161013

SPIO 20 wallwasher / floor

WALLWASHER / FLOOR TRIMLESS

INSET POWER	LUMINOUS FLUX	ORDER CODE
5.9 W 5.6 Vf 1050 mA	414 lm	048-173010 8W

TRIMLESS MOUNTING SET for plasterboard ceilings 9–25 mm

COLOUR	ORDER CODE
○ traffic white RAL9016	048-1698107

WALLWASHER / FLOOR TRIM

INSET POWER	LUMINOUS FLUX	ORDER CODE
5.9 W 5.6 Vf 1050 mA	414 lm	048-163018W

Mounting accessories

SPECIAL MOUNTING TOOL

TYPE	Ø·H (mm)	ORDER CODE
SPIO 20	73·107	048-1690000

necessary to install mounting housing trimless

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, ⧈ PC II

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
600 mA | max. 43 V | non DIM	η 85 %	147·44·22	002-90783
600 mA | max. 46 V | DALI-2	η 85 %	143·43·30	002-90784
1050 mA | max. 25 V | non DIM	η 85 %	111·38·28	002-90787
1050 mA | max. 42 V | DALI-2	η 85 %	143·43·30	002-90788

revision opening required

DIN RAIL COMPONENTS

TYPE	W·H·D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W | 48V DC constant voltage	72·90·63	005-652021 0
LED DRIVER DALI-2 DT6 1–2 addr. 200–1050 mA settable const. current 2×42 W | 48 V DC | U_{OUT} 10–40 V	36·88·59	005-612103 0

for more details and components see XAL 22 catalog, page 980

Private Residence
Visualisation





reddot winner 2022

DESIGN AWARD 2022

SPIO 60

recessed

EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set with ball catch system or with magnetic attachment; for trimless installation in plasterboard ceilings; paintable cover; shadow joint between cover and mounting set optionally fillable; or with trim; choice of adjustable or fixed symmetric radiation characteristic; high quality lens system; uncluttered ceiling look through recessed lighting level; reduced light-emitting surface (only ø 10 mm); no multiple shadows; efficient LEDs with very good colour rendering


DE Runder Einbaustrahler aus Aluminiumdruckguss; werkzeuglose Montage im Montageset durch Kugelschnappsystem oder mittels Magnetbefestigung; für randlosen Einbau in Gipskartondecken; überstreichbare Abdeckplatte; Schattenfuge zwischen Abdeckplatte und Montageset optional verspachtelbar; oder mit umlaufendem Rand; wahlweise einstellbar oder starr symmetrische Abstrahlcharakteristik; hochwertige Linsenoptik; ruhiges Deckenbild durch zurückversetzte Leuchtenebene; reduzierte Lichtaustrittsfläche (nur ø 10 mm); keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo


2700 K, 3000 K
CRI ≥ 90, 3 SDCM
up to 60 lm/W
L95 @ 50 000 h
non DIM, DALI-2

Types

downlight



adjustable



Colours



Light distributions



flood wide flood

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5

MATERIAL COLOUR

○ traffic white RAL9016

paintable cover

BEAM ANGLE ▲

flood 35°	F
wide flood 44°	W

Options on request


COLOUR TEMPERATURE


4000 K

CONCRETE HOUSING


primed concrete ceiling
exposed concrete ceiling














SPIO 60 downlight

CRI ≥90 | DALI 1 ADDR. | 1050 mA | pending | CB pending | X-PERT | X-PERT

DOWNLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
11.9 W 12 Vf 1050 mA	718 lm	048-1510::17▲

Mounting accessories

TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25 mm

COLOUR	ORDER CODE
○ traffic white RAL9016	048-2696117

MOUNTING SET WITH TRIM for intermediate ceilings 2–25 mm

COLOUR	ORDER CODE
○ traffic white RAL9016	048-1597207
● jet black RAL 9005	048-1597208

SPIO 60 adjustable

360° | 30° | CRI ≥90 | DALI 1 ADDR. | 1050 mA | pending | CB pending | X-PERT | X-PERT

ADJUSTABLE

INSET POWER	LUMINOUS FLUX	ORDER CODE
11.9 W 12 Vf 1050 mA	685 lm	048-1520::17▲

Mounting accessories

TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25 mm

COLOUR	ORDER CODE
○ traffic white RAL9016	048-1598107

MOUNTING SET WITH TRIM for intermediate ceilings 2–25 mm

COLOUR	ORDER CODE
○ traffic white RAL9016	048-1597107
● jet black RAL 9005	048-1597108

Electrical accessories

POWER SUPPLY 220-240 V AC, 50-60 Hz, ⧈ PC II

TYPE	EFFICIENCY	L·W·H (mm)	ORDER CODE
1050 mA | non DIM	η 85 %	111·38·28	002-90787
1050 mA | DALI-2	η 85 %	143·43·30	002-90788

DIN RAIL COMPONENTS

TYPE	W·H·D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W | 48 V DC constant voltage	72·90·63	005-6520210
LED DRIVER DALI-2 DT6 1–2 addr. 200–1050 mA settable const. current 2×42 W | 48 V DC | U_{OUT} 10–40 V	36·88·59	005-6121030

for more details and components see XAL 22 catalog, page 980




version with trim available




10 mm light ouput area



trimless installation



paintable cover




LFO lens technology

INSET POWER is the current consumption excluding any ballast
LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, lens wide flood, 2700 K -5 %

Private Residence
Visualisation



High-precision shelf lighting



SQUADRO

EN SQUADRO is a track-mounted and recessed spotlight, in a two-lamp single- or double-sided version, for the retail sector that bundles six essential retail requirements in one luminaire. Free-form reflectors with faceted optics make a polished presentation of goods possible. These reflectors direct the light precisely into shelves or aisle zones. Directed light creates a modelling effect on the products and delivers attractive staging. Swivelling light modules illuminate specific shelf levels or billboards while providing plenty of basic lighting. SQUADRO spotlights are completely glare-free, both transversely and longitudinally. They are highly efficient in their energy balance with an efficiency of over 90 %.


DE SQUADRO ist ein Stromschienen- und Einbaustrahler, in zweiflammiger einseitiger oder zweiseitiger Ausführung, für den Retailbereich, der sechs wichtige Retail-Anforderungen in einer Leuchte bündelt. Die brillante Präsentation von Waren gelingt dank Freiformflächenreflektoren mit Facettenoptik: Diese lenken das Licht punktgenau und hochpräzise in Regale oder Gangzonen. Gerichtetes Licht erzeugt einen Modelling-Effekt auf den Waren und schafft eine attraktive Inszenierung. Schwenkbare Lichtmodule beleuchten gezielt Regalebenen oder Plakatwände und sorgen gleichzeitig für ausreichende Grundbeleuchtung. SQUADRO Strahler sind dabei komplett quer- und längsentblendet und dennoch in ihrer Energiebilanz mit einem Wirkungsgrad von über 90 % höchst effizient.

Types




single-sided 1×2 | double-sided 2×2 | single-sided 1×2 | double-sided 2×2

Mountings




recessed | track

Light distributions



wall floor | shelf floor | wall / shelf floor

6-in-1 Lighting solution



EN SQUADRO combines all the advantages of traditional retail lighting solutions in one luminaire. The spotlights are transversely and longitudinally glare-free and direct the light precisely onto the goods – into the heights and depths of the shelves. This achieves a strong product presentation. Thanks to proper light distribution, no additional light source is required for basic lighting.

DE SQUADRO bündelt alle Vorteile klassischer Retail-Lichtlösungen in einer Leuchte. Die Strahler sind quer- und längsentblendet und richten das Licht präzise auf die Ware – bis in die Höhen und Tiefen der Regale. Das erzielt eine starke Produktpräsentation. Dank guter Lichtverteilung ist keine zusätzliche Lichtquelle für die Grundbeleuchtung nötig.

1 EN The highest illuminance is on the upper two presentation levels.

DE Die höchste Beleuchtungsstärke liegt auf den oberen beiden Präsentationsebenen.

2 EN Highlights on premium goods create a brilliant staging.

DE Speziell exklusive Ware wird durch Glanzpunkte attraktiv inszeniert.

3 EN Directed light creates accents on billboards and subjects.

DE Gerichtetes Licht erzeugt Akzente auf Werbetafeln und Sujets.

4 EN The high depth effect gives food high colour contrasts and attractiveness.

DE Durch die hohe Tiefenwirkung erhalten Lebensmittel hohe Farbkontraste und Glanzpunkte.

5 EN Due to longitudinal glare control, the lighting system is barely perceptible to the customer in the direction of the aisle.

DE Durch die Längsentblendung ist die Beleuchtungsanlage für den Kunden in Gangrichtung kaum wahrnehmbar.


6 EN Transverse glare control additionally prevents glare from any viewing direction.

DE Die Querentblendung verhindert zusätzlich Blendung aus jeder Blickrichtung.


Five versions

EN SQUADRO's five variants with diverse beam characteristics respond to different shop layouts and requirements. Perfect alignment ensures that minimal luminaires radiate as much light as possible onto the merchandise. SQUADRO adapts to the conditions and illuminates selectively and without scatter loss. All goods are thus attractively presented regardless of the size or interior design of the shop.


DE SQUADRO antwortet auf unterschiedliche Shop-Layouts und Anforderungen mit fünf Varianten mit verschiedenen Abstrahlcharakteristiken. Damit wenige Leuchten so viel Licht wie möglich auf die Ware strahlen, zählt die perfekte Ausrichtung. SQUADRO passt sich den Gegebenheiten an und beleuchtet punktuell und ohne Streuverluste. So werden alle Waren, unabhängig von Größe oder Innenarchitektur des Shops, ansprechend in Szene gesetzt.




Wall Floor (single-side)




Shelf Floor (single-side)




Wall Floor (double-side)



Shelf Floor (double-side)



Shelf / Wall Floor



Unique reflector technology


EN Custom free-form reflectors ensure high-precision light control; each SQUADRO achieves an efficiency of over 90 per cent. The spotlights enjoy optimum glare control through the curved shape and secondary reflector technology.


DE Spezielle Freiflächenreflektoren sorgen für hochpräzise Lichtlenkung; jeder SQUADRO erzielt einen Wirkungsgrad von über 90 Prozent. Optimale Entblendung gelingt durch die gekrümmte Form und Sekundärreflektortechnik der Strahler.

Effective lighting

EN Branches of the same chain often differ in their shop architecture. Shelf heights and aisle widths may vary from one location to another. The solution is step-adjustable light modules. The elements can be tilted from -15° to +20°. Each module can be tilted asymmetrically, allowing precise alignment and thus optimum light control.

DE Filialen derselben Kette unterscheiden sich häufig in der Shop-Architektur. Regalhöhen und Gangbreiten können sich je nach Standort unterscheiden. Die Lösung: stufenverstellbare Lichtmodule. Die Elemente sind von -15° bis zu +20° kippbar. Jedes Modul kann asymmetrisch geneigt werden und ermöglicht eine präzise Ausrichtung und damit eine optimale Lichtlenkung.







SQUADRO wallwasher

recessed

EN Recessed ceiling spotlight in die cast aluminium in two different types (2 lamps or 2×2 lamps) and with 2 types of light modules (for shelf floor washer and wall floor washer); with trim; surface powder coated; installation without tools using snap spring closure; aisle spotlight with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone, adjustable light modules; COB (Chip on Board) technology for maximum efficiency; efficient LEDs with very good colour rendering; IP 40 protection glass available as an accessory

DE Deckeneinbaustrahler aus Aluminium-druckguss in 2 verschiedenen Varianten (2-flammig bzw. 2×2-flammig) und mit 2 verschiedenen Lichtmodulen (für shelf floor washer und wall floor washer); mit umlaufendem Rand; Oberfläche pulverbeschichtet; werkzeuglose Montage mittels Schnappfederverschluss; Gangzonenstrahler mit speziellen Multi-Freiformflächenreflektoren mit Facettenoptik zur äußerst präzisen Lichtlenkung; punktgenaue Regal- und Gangzonenausleuchtung, optimale Längsentblendung für hohen Sehkomfort in der Gangzone, einstellbare Lichtmodule; COB (Chip on Board) Technologie für höchste Effizienz; effiziente LEDs mit sehr guter Farbwiedergabe; IP 40-Schutzglas als Zubehör erhältlich




DiiA® standards 251, 252, 253



up to 134 lm/W (high efficiency)



glare-free reflector longitudinally & transversely




+20° up to -10° tiltable

Quickinfo

3000 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 134 lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types



Colours



Light distributions



Order options

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

non DIM	1
DALI-2	3


MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR

shelf floor washer	S
wall floor washer	A
1×shelf / 1×wall floor washer*	B

*only for 2×2 lamps




Options on request


COLOUR RENDERING INDEX

CRI ≥ 80	


Light distributions




1×2 lamps
shelf floor washer



1×2 lamps
wall floor washer




2×2 lamps
1×shelf / 1×wall floor washer



2×2 lamps
wall floor washer

LUMINOUS FLUX value calculated for 4000 K
CRI ≥ 90, colour white, wall floor washer
3000 K -5 %

SQUADRO wallwasher trim





1×2 LAMPS SINGLE-SIDED

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
36 W	4720 lm	049-2012





2×2 LAMPS DOUBLE-SIDED

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
72 W	2×4720 lm	049-2020


Optical accessories

IP 40 PROTECTION GLASS


TYPE	ORDER CODE
1×2 lamps / single-sided	049-2910010
2×2 lamps / double-sided	049-2920010

Technical data

SQUADRO 1×2 lamps, shelf wall washer, trim, 36 W, 3000 K




SQUADRO 1×2 lamps, wall floor washer, trim, 36 W, 3000 K



ROOM VALUES		CALCULATION SURFACE	
Wall dimensions	H = 3.5 m | W = 10.8 m	Surface dimensions	10.8 × 3.5 m
Distance to wall	B = 1.3 m	Surface height	0 – 3.5 m
Aisle width	2.6 m		
Reflection factor	0.7 | 0.7 | 0.2	Eye level	1.35 m – 1.75 m
Maintenance factor	0.9		

Euroshop Dusseldorf, DE –
by blocher partners





SQUADRO wallwasher

track


EN Track light in die cast aluminium in two different types (2 lamps or 2×2 lamps) and with 2 types of light modules (for shelf floor washer and wall floor washer); surface powder coated; aisle spotlight with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone, adjustable light modules; COB (Chip on Board) technology for maximum efficiency; efficient LEDs with very good colour rendering; IP 40 protection glass available as an accessory; including attachment for linear alignment of the spotlights

DE Stromschienenstrahler aus Aluminiumdruckguss in 2 verschiedenen Varianten (2-flammig bzw. 2×2-flammig) und mit 2 verschiedenen Lichtmodulen (für shelf floor washer und wall floor washer); Oberfläche pulverbeschichtet; Gangzonenstrahler mit speziellen Multi-Freiformflächenreflektoren mit Facettenoptik zur äußerst präzisen Lichtlenkung; punktgenaue Regal- und Gangzonenausleuchtung, optimale Längsentblendung für hohen Sehkomfort in der Gangzone, einstellbare Lichtmodule; COB (Chip on Board) Technologie für höchste Effizienz; effiziente LEDs mit sehr guter Farbwiedergabe; IP 40-Schutzglas als Zubehör erhältlich; inklusive Aufsatz zur linearen Ausrichtung der Strahler

Quickinfo

3000 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 134 lm/W
L80 @ 50 000 h
non DIM, DALI-2

Types



Colours

Light distributions






DiiA® standards 251, 252, 253



up to 134 lm/W (high efficiency)



glare-free reflector longitudinally & transversely



+20° up to -10° tiltable

Order options

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

non DIM	1
DALI-2	3


MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR

shelf floor washer	S
wall floor washer	A
1×shelf/1×wall floor washer*	B

*only for 2×2 lamps



Options on request


COLOUR RENDERING INDEX

CRI ≥ 80


CONTROL

DALI-2 (2×2 lamps)


Light distributions




1×2 lamps
shelf floor washer



1×2 lamps
wall floor washer




2×2 lamps
wall floor washer



2×2 lamps
1×shelf/1×wall floor washer


LUMINOUS FLUX value calculated for 4000 K
CRI ≥ 90, colour white, wall floor washer
3000 K -5 %

SQUADRO wallwasher track



1×2 LAMPS SINGLE-SIDED

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
36 W	4720 lm	149-2210



2×2 LAMPS DOUBLE-SIDED

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
72 W	2×4720 lm	149-2220 1


Optical accessories

IP 40 PROTECTION GLASS


TYPE	ORDER CODE
1×2 lamps/single-sided	049-2910010
2×2 lamps/double-sided	049-2920010

Technical data

SQUADRO 1×2 lamps, shelf wall washer, trim, 36 W, 3000 K



SQUADRO 1×2 lamps, wall floor washer, trim, 36 W, 3000 K




ROOM VALUES		CALCULATION SURFACE	
Wall dimensions	H = 3.5 m | W = 10.8 m	Surface dimensions	10.8 × 3.5 m
Distance to wall	B = 1.3 m	Surface height	0 – 3.5 m
Aisle width	2.6 m		
Reflection factor	0.7 | 0.7 | 0.2	Eye level	1.35 m – 1.75 m
Maintenance factor	0.9		

Jelmoli Store
Zurich, CH



Oasis Store Melbourne, AU –
by Sync Design

In the spotlight




BO intrack

EN Elegant and flexible – this is what characterises the BO track spotlight series. Several sizes and different beam angles offer enormous freedom in setting the scene. The Intrack versions are available as one-, two-, or three-flame spotlights. In addition, the spots can be rotated and pivoted at different angles, making BO an ideal spotlight for shops and staging areas. Different housing and light colours (2700 K, 3000 K, or 4000 K) offer flexibility in different architectural concepts and promise very good colour rendering of up to CRI ≥ 95 (2-SDCM).

DE Formschön und flexibel: das zeichnet die Stromschienenstrahlerserie BO aus. Durch mehrere Größen und verschiedene Ausstrahlwinkel haben Sie große Freiheit bei der Inszenierung. Die Intrack Varianten sind als ein-, zwei- oder dreiflammiger Strahler erhältlich. Zusätzlich sind die Spots in verschiedenen Winkeln dreh- und schwenkbar und machen BO zu einem idealen Strahler für Shops und Präsentationsflächen. Verschiedene Gehäuse- und Lichtfarben (2700 K, 3000 K oder 4000 K) bieten Flexibilität in unterschiedlichen architektonischen Konzepten und versprechen eine sehr gute Farbwiedergabe von bis zu CRI ≥ 95 (2-SDCM).

Types



32 45 55

Mounting



track

Light distribution




spotlight

Matched proportions

EN Elegance in the right measure: All BO product family spotlights are characterised by their decorative and simple aesthetics. Thanks to their reduced design and precisely coordinated proportions, all BO models can be combined with each other.

DE Eleganz im richtigen Maß: Alle Strahler der BO Produktfamilie zeichnen sich durch ihre dekorative und schlichte Ästhetik aus. Dank ihres reduzierten Designs und den exakt aufeinander abgestimmten Proportionen sind sämtliche BO-Varianten miteinander kombinierbar.



Colour variety

EN BO is available in standard white and black. For even more design freedom, additional colour options are available so that you can tailor BO to your individual project. Learn more about our colour palette at xal.com/colours.

DE BO ist in den Standardfarben Weiß und Schwarz erhältlich. Für noch mehr Gestaltungsfreiraum stehen weitere Farbvarianten zur Verfügung – so können Sie BO Ihrem individuellen Projekt anpassen. Mehr zu unserer Farbpalette erfahren Sie auf xal.com/colours.




xal.com/colours

Variety

EN The BO Intrack versions are available as single-, double-, or triple-flame spotlights. The spotlight heads are available in three different diameters and different housing and light colours (2700 K, 3000 K, or 4000 K), offering even more flexibility for unique projects. The multi-flame version of the Inset requires only one control gear, which means that the individual spotlights are closer together. This makes these variants not only space-saving but also more cost-efficient.

DE Die BO Intrack Varianten sind als ein-, zwei- oder dreiflammiger Strahler erhältlich. Die Strahlerköpfe in drei unterschiedlichen Durchmessern und verschiedene Gehäuse- und Lichtfarben (2700 K, 3000 K oder 4000 K) bieten noch mehr Flexibilität für einzigartige Projekte. Die mehrflammige Ausführung des Insets benötigt lediglich ein Betriebsgerät, wodurch die einzelnen Strahler näher beieinander sitzen. Dadurch sind diese Varianten nicht nur platzsparend, sondern auch kosteneffizienter.






Intrack

EN Flexible adjustment – easy installation: In the track version, BO combines different sizes and beam angles. Thus, ever new lighting scenarios can be implemented: from the selective presentation of goods and products to the staging of art objects and home accessories. The converter disappears elegantly into the track.


DE Flexible Adjustierung – einfache Montage: In der Track-Variante vereint BO unterschiedliche Größen und Ausstrahlwinkel. So lassen sich immer wieder neue Lichtinszenierungen realisieren: von der punktuellen Waren- und Produktpräsentation bis zur Inszenierung von Kunstobjekten und Wohnaccessoires. Der Konverter verschwindet elegant in der Schiene.



Flexible adjustment

EN BO adapts to the requirements to ensure that objects are presented in the best possible light. The spotlight comes in different beam angles and is rotatable by at least 360°, as well as 90° tiltable.

DE Damit Objekte bestmöglich in Szene gesetzt sind, passt sich BO den Anforderungen an. Der Strahler ist nicht nur in verschiedenen Ausstrahlwinkeln verfügbar sondern auch um mindestens 360° dreh- sowie 90° schwenkbar.



BO 32 / 45 / 55

intrack


EN Track light made of die-cast aluminium; powder coated; spotlight head rotates 360° and tilts 90°; choice of single lamp, double lamps or triple lamp; converter in the adapter; with optional high quality lens system with precise radiation characteristic; or high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristics with different beam angles; good glare reduction due to recessed light point plane; optical attachments as accessories; COB (Chip on Board) technology or high power LEDs - maximum efficiency; no multiple shadows; energy-eff. LEDs - very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter flush with the power track

DE Stromschienenstrahler aus Aluminiumdruckguss; pulverbeschichtet; Strahlerkopf 360° dreh- und 90° schwenkbar; wahlweise ein-, zwei- oder dreiflammig; Konverter im Adapter; wahlweise mit hochwertiger Linsenoptik mit präziser Abstrahlcharakteristik; oder hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; gute Entblendung durch zurückversetzte Lichtpunktebene; optische Aufsätze als Zubehör; COB (Chip on Board) Technologie bzw. High-Power-LEDs - höchste Effizienz; keine Mehrfachschatten; energieeff. LEDs - sehr gute Farbwiedergabe; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Stromschienen; Adapter bündig mit Stromschiene abschließend

Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90, 2 SDCM
BO 32 up to 69 lm/W
BO 45 up to 91 lm/W
BO 55 up to 85 lm/W
L80 @ 50 000 h
DALI-2

Types



Colours



standard xal.com/colours

Light distributions





only one adapter with 2 or 3 lamps



360° rotatable 90° tiltable



glare control via honeycomb louver



oval lens for oval light illumination



CRI ≥ 95 2 SDCM

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

DALI-2

MATERIAL COLOUR

traffic white RAL 9016	7
jet black RAL 9005	8
special colours	X

BEAM ANGLE BO 32

spot 18°	S
medium 23°	M
flood 37°	F

BEAM ANGLE BO 45

super spot 8°	V
spot 14°	S
medium 24°	M
flood 39°	F

BEAM ANGLE BO 55


spot 17°	S
medium 23°	M
flood 37°	F

Options on request

COLOUR RENDERING INDEX

CRI ≥ 95, 2 SDCM

LUMINOUS FLUX value calculated for 3000 K, CRI ≥ 90, colour white, flood 2700 K -5 %, 4000 K +7 %




BO 32 intrack

360° 90° | CRI ≥ 90 | 2-SDCM | DALI 1 ADDR. | 220-240 V | X-PERT | X-PERT

TRACK LIGHT

TYPE	SYS. POWER	LUMINOUS FLUX	ORDER CODE
2 lamps	20.5 W	1440 lm	180-7140 :: 3 ◪ ▲
3 lamps	28.8 W	2020 lm	180-7150 :: 3 ◪ ▲




BO 45 intrack

360° 90° | CRI ≥ 90 | 2-SDCM | DALI 1 ADDR. | 220-240 V | X-PERT | X-PERT

TRACK LIGHT

TYPE	SYS. POWER	LUMINOUS FLUX	ORDER CODE
2 lamps	14.2 W	super spot 2 × 320 lm	180-7240 :: 3 ◪ V
	30 W	spot 2 × 1020 lm	180-7240 :: 3 ◪ S
	32 W	med., flood 2 × 1330 lm	180-7240 :: 3 ◪ ▲
3 lamps	45 W	spot 3 × 1020 lm	180-7250 :: 3 ◪ S
	42 W	med., flood 3 × 1180 lm	180-7250 :: 3 ◪ ▲



BO 55 intrack

360° 90° | CRI ≥ 90 | 2-SDCM | DALI 1 ADDR. | 220-240 V | X-PERT | X-PERT

TRACK LIGHT

TYPE	SYS. POWER	LUMINOUS FLUX	ORDER CODE
1 lamp	24.8 W	1940 lm	180-7330 :: 3 ▲
2 lamps	43 W	3460 lm	180-7340 :: 3 ▲

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø·H (mm)	ORDER CODE
BO 32	30·3	007-1965168
BO 45	42·3	007-1965188
BO 55	50·3	007-1965598

OVAL LENS

TYPE	Ø·H (mm)	ORDER CODE
BO 32	30·3	007-1965860
BO 45	42·3	007-1965880
BO 55	50·3	007-1965890

SOFT LENS

TYPE	Ø·H (mm)	ORDER CODE
BO 32	30·3	007-1965960
BO 45	42·3	007-1965980
BO 55	50·3	007-1965990

Euroshop
Dusseldorf, DE –
by blocher partners






Oberpollinger | The KaDeWe Group
Munich, DE – by Licht Kunst Licht AG
including lighting design



Universal expert



VARO

EN As a track-mounted spotlight, VARO focuses on the essentials and can be used universally. It is available in two different sizes and, thanks to its 355° rotation and 90° swivelling capability, is extremely flexible in use. This flexibility is supported by the fact that the spotlights can be inserted and moved along the track without tools. It is ideal for use in shops whose interior design is continually evolving. In addition, the powerful VARO provides maximum efficiency for the illumination of products. The high-quality reflector from VARO ensures a particularly precise beam characteristic at different angles, all with an excellent colour rendering up to CRI ≥ 90. Depending on the desired spatial effect, you can choose between the 3000 K and 4000 K light colours.

DE Als Stromschienenstrahler fokussiert VARO auf das Wesentliche und ist universell einsetzbar. Er ist in zwei verschiedenen Größen verfügbar und durch 355° Dreh- und 90° Schwenkbarkeit höchst beweglich im Einsatz. Unterstützt wird diese Flexibilität durch werkzeugloses Einsetzen und Verschieben der Strahler in der Stromschiene: ideal für den Einsatz in Shops, deren Innenarchitektur sich immer wieder verändert. Zudem bietet der leistungsstarke VARO höchste Effizienz bei der Beleuchtung von Waren. Der hochwertige Reflektor von VARO sorgt für eine besonders präzise Abstrahlcharakteristik in verschiedenen Winkeln – und das bei sehr guter Farbwiedergabe von bis zu CRI ≥ 90. Je nach gewünschter Raumwirkung haben Sie die Wahl zwischen den Lichtfarben 3000 K und 4000 K.

Types



80 110

Mounting



track

Light distribution



spotlight



VARO 80 S

track


EN Track light made of die-cast aluminium; surface powder coated; spotlight head 355° rotatable and 90° tiltable; integrated converter in the plastic adapter; high quality reflector with spherical facet finish; precise radiation characteristics with different beam angles; installed and exchanged without tools; optical attachments as accessories; optical attachments can be combined; COB (Chip on Board) technology for maximum efficiency; variants with >120 lm/W available; no multiple shadows; energy-efficient LEDs with very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks

DE Stromschienenstrahler aus Aluminium-druckguss; Oberfläche pulverbeschichtet; Strahlerkopf 355° dreh- und 90° schwenkbar; Konverter im Kunststoffadapter integriert; hochwertiger Reflektor mit sphärischer Facet-tenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; werkzeuglos einsetz- bzw. austauschbar; optische Aufsätze als Zubehör; optische Aufsätze miteinan-der kombinierbar; mit COB (Chip on Board) Technologie für höchste Effizienz; Varianten mit >120 lm/W verfügbar; keine Bildung von Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Stromschienen

Quickinfo

3000 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 129 lm/W
L95 / 50 000 h
non DIM, DALI-2

Type



Colours

Light distributions

spot med. flood

Order options

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE

spot 17°	S
medium 28°	M
flood 38°	F

Options on request


COLOUR RENDERING INDEX

CRI ≥ 80

CONTROL

Casambi
DALI-2 (high efficiency)





VARO 80 S track



TRACK LIGHT

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
28.5 W	2600 lm	180-6420
45 W	3610 lm	180-6421


HIGH EFFICIENCY

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
21.3 W	2730 lm	180-6422 1
25.4 W	3160 lm	180-6423 1

Optical accessories

LENSES AND HONEYCOUMB LOUVER

TYPE	Ø·H (mm)	ORDER CODE
linear prismatic lens	75·9	080-6402110P
honeycomb louver	75·9	080-6401118



SNOOT

TYPE	Ø·H (mm)	ORDER CODE
short	66·23	080-6403118
medium	66·38	080-6403218
angle	66·38	080-6403318






possibility to combine different optical accessories (max. 2 pieces)



up to 129 lm / W (high efficiency)



355° rotatable 90° tiltable



optical accessories



combine 2 optical accessories

LUMINOUS FLUX value calculated for 4000 K, CRI ≥ 90, colour white, flood 3000 K -7%

s.Oliver Store Munich, DE –
by Kitzig Interior Design GmbH
including lighting design







VARO 110 S

track


EN Track light made of die-cast aluminium; surface powder coated; spotlight head 355° rotatable and 90° tiltable; integrated converter in the plastic adapter; high quality reflector with spherical facet finish; precise radiation characteristics with different beam angles; installed and exchanged without tools; optical attachments as accessories; optical attachments can be combined; COB (Chip on Board) technology for maximum efficiency; variants with >120 lm/W available; no multiple shadows; energy-efficient LEDs with very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks

DE Stromschienenstrahler aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; Strahlerkopf 355° dreh- und 90° schwenkbar; Konverter im Kunststoffadapter integriert; hochwertiger Reflektor mit sphärischer Facettenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; werkzeuglos einsetz- bzw. austauschbar; optische Aufsätze als Zubehör; optische Aufsätze miteinander kombinierbar; mit COB (Chip on Board) Technologie für höchste Effizienz; Varianten mit >120 lm/W verfügbar; keine Bildung von Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Stromschienen

Quickinfo

3000 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 132 lm/W
L95 / 50 000 h
non DIM, DALI-2

Type




Colours

Light distributions




up to 132 lm / W (high efficiency)


355° rotatable 90° tiltable


optical accessories


combine 2 optical accessories

Order options

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

non DIM	1
DALI-2	3

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE

spot 17°	S
medium 28°	M
flood 38°	F
wide flood 65°	W

Options on request


LUMINOUS FLUX

>5000 lm

CONTROL

Casambi
DALI-2 (high efficiency)

LUMINOUS FLUX value calculated for 4000 K, CRI ≥ 90, colour white, flood 3000 K -7%



VARO 110 S track

TRACK LIGHT

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
29.6 W	3370 lm	180-6520
39 W	4300 lm	180-6521

HIGH EFFICIENCY

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
25.7 W	3400 lm	180-6530
36 W	4520 lm	180-6531


Optical accessories

LENSES AND HONEYCOUMB LOUVER

TYPE	Ø·H (mm)	ORDER CODE
oval lens	106·9	080-650221 0
wide flood lens	106·9	080-650211 0W
honeycomb louver	106·9	080-650111 8

SNOOT

TYPE	Ø·H (mm)	ORDER CODE
short	97·23	080-650311 8
medium	97·38	080-650321 8
angle	97·38	080-650331 8




possibility to combine different optical accessories (max. 2 pieces)

Kastner & Öhler, Kaufhaus Tyrol
Innsbruck, AT – by DIOMA AG /
WHIR3 / K&Ö Bauabteilung
with lighting design by
VEDDER.LICHTMANAGEMENT



Versatile profile



MILA system

EN The MILA system luminaire was specially designed for use with slat ceilings and blends seamlessly into the respective room concept in entrance halls and office buildings. In meeting rooms and offices, the luminaire creates an ideal, screen-appropriate work light thanks to the optional addition of reflectors. In the opal cover variant, MILA is suitable for homogeneous room illumination; a reduced glare value is achieved with the optional microprismatic cover. For continuous lighting systems, the flexible Continuous Cover is the best choice. By adding special sensors, the MILA system luminaire becomes a smart lighting system. The sensors can be freely placed in the slatted ceiling and quickly integrated at a later stage. The collected room utilisation data helps to save energy over the long term.

DE Die MILA Systemleuchte wurde speziell für den Einsatz von Lamellendecken konzipiert und fügt sich in Eingangshallen sowie Bürogebäuden nahtlos in das jeweilige Raumkonzept ein. In Meetingräumen und Büros schafft die Leuchte ein ideales bildschirmtaugliches Arbeitslicht dank der wahlweisen Ergänzung durch Reflektoren. In der Opal-Cover-Variante eignet sich MILA für eine homogene Raumausleuchtung, ein reduzierter Blendwert wird mit der optionalen mikroprismatischen Abdeckung erreicht. Für durchgängige Lichtsysteme ist das flexible Continues Cover die beste Wahl. Durch die Erweiterung mit speziellen Sensoren wird die MILA Systemleuchte zum smarten Beleuchtungssystem. Die Sensoren können in der Lamellendecke frei platziert und nachträglich schnell integriert werden. Die hier gesammelten Daten zur Raumnutzung.

Type

38

Mounting




ceiling

Configuration

linear

Light distributions



opal | micro-prismatic | reflector (UGR ≤ 19) | direct



Advanced sensor technology


EN By adding special sensors, the MILA system luminaire becomes a smart lighting system. The sensors can be placed freely and flexibly in the slatted ceiling, and can also be integrated quickly and easily at a later stage. With the ESSENTIAL sensor, the lighting dynamically adapts to the ambient brightness and room activity. In addition, the SENSE sensor measures values for temperature, air quality, humidity, and noise level. These data not only provide important insights into the ambient conditions, but also support energy savings over the long term.

DE Durch die Erweiterung mit speziellen Sensoren wird die MILA Systemleuchte zum smarten Beleuchtungssystem. Die Sensoren können in der Lamellendecke frei und flexibel platziert werden und auch nachträglich schnell und einfach integriert werden. Mittels ESSENTIAL Sensor passt sich die Beleuchtung dynamisch an die Umgebungshelligkeit und Raumaktivität an. Ergänzend werden, mit dem SENSE Sensor, Werte zu Temperatur, Luftqualität, Luftfeuchtigkeit und Geräuschpegel gemessen. Diese Daten liefern nicht nur wichtige Erkenntnisse über die Umgebungsbedingungen, sondern unterstützen langfristig Energieeinsparungen.

Continuous Cover

EN Both the opal and the microprismatic cover are available as continuous versions for the MILA system luminaires. This results in remarkable flexibility, as the length of the cover can be adapted exactly to the system. During installation, the Continuous Cover is simply integrated into the profile, avoiding interfering joints, and creating a pleasantly continuous lighting system.


DE Sowohl das opale als auch das mikroprismatische Cover stehen für die MILA Systemleuchten als Continuous Version zur Verfügung. Dadurch ergibt sich eine besondere Flexibilität, denn die Länge des Covers kann exakt an das System angepasst werden. Bei der Montage wird das Continuous Cover einfach in das Profil integriert, wodurch störende Stoßstellen vermieden werden und ein angenehm durchgehendes Lichtsystem entsteht.



Inset variety

EN Whether workplace lighting or general building areas – the MILA system luminaire can be adapted depending on the area of application. For screen-appropriate task lighting, the UGR ≤ 19 glare-reduced reflectors are the right choice. The optionally available opal cover is suitable for homogeneous ambient illumination. The microprismatics with reduced glare value are ideal for pleasantly illuminating entrance areas and corridors.

DE Ob Arbeitsplatzbeleuchtung oder allgemeine Gebäudebereiche – die MILA Systemleuchte lässt sich je nach Einsatzgebiet variieren. Für die bildschirmtaugliche Arbeitsplatzbeleuchtung sind die UGR ≤ 19 entblendeten Reflektoren die richtige Wahl. Das wahlweise erhältliche Opal-Cover ist für eine homogene Grundausleuchtung geeignet. Die Mikroprismatik mit reduziertem Blendwert ist ideal, um Eingangsbereiche und Gänge angenehm zu beleuchten.



MILA reflector






MILA opal




MILA microprismatic



Mounting

EN MILA can provide the right lighting in any room via sturdy mounting brackets that are hooked into the slatted ceiling. The brackets can be flexibly moved along the luminaire and can thus be positioned as required, or subsequently adjusted. Converters with wiring-through function facilitate electrical installation, as wiring can thus be carried out easily and quickly from one luminaire to another. In addition, the free movement of the converter allows a flexible response to ceiling conditions.

DE Über stabile Befestigungsklammern, welche an der Lamellendecke eingehängt werden, kann MILA in jedem Raum für die passende Beleuchtung sorgen. Die Klammern sind entlang der Leuchte flexibel verschiebbar und können so bedarfsorientiert platziert oder nachträglich angepasst werden. Konverter mit through wiring Funktion erleichtern die elektrische Montage, da die Verdrahtung so einfach und schnell von Leuchte zu Leuchte durchgeführt werden kann. Außerdem kann durch die freie Verschiebbarkeit des Konverters flexibel auf die Deckengegebenheiten reagiert werden.



HAUFE
DECKENSYSTEME

MILA system

ceiling

EN Luminaire housing from extruded aluminium profile, angular design; designed for continuous lighting systems; suitable for installation in the HAUFE louvre ceiling system; surface powder coated; HPO (High Performance Opal) cover or microprismatic cover in the length of the light inset or continuous cover (both separately available); optional high gloss reflector with faceted design; converter flexible positionable on the luminaire profile; converter suitable for through-wiring; energy-efficient LEDs with very good colour rendering; optionally sensor inset (ESSENTIAL or SENSE) available as accessory


DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; ausgelegt für durchgehende Lichtsysteme; geeignet für den Einbau in das HAUFE Lamellendeckensystem; Oberfläche pulverbeschichtet; HPO (High Performance Opal) Abdeckung oder mikroprismatische Abdeckung in Lichteinsatzlänge oder durchgängige Abdeckung (beide separat zu bestellen); optional hochglänzender Reflektor mit Facettenoptik; Konverter flexibel am Leuchtenprofil positionierbar; Konverter für Weiterverdrahtung geeignet; energieeffiziente LEDs mit sehr guter Farbwiedergabe; wahlweise Sensor-Einsatz (ESSENTIAL oder SENSE) als Zubehör erhältlich

Quickinfo


3000 K, 4000 K
CRI ≥ 90, 3 SDCM
UGR ≤ 19 / 65° ≤ 1500 cd/m²
up to 115 lm/W
up to 103 lm/m
L90 @ 50 000 h
DALI-2
opal, microprismatic
reflector (UGR ≤ 19)

Types

opal / microprismatic



reflector



Colours



Light distribution




direct



DiiA® standards
251, 252, 253



suitable for
HAUFE ceilings



continuous
lighting system



sensor for
single mounting




DIN EN 12464-1
UGR ≤ 19



up to 115 lm / W
(high efficiency)



tunable white
2700 – 6500 K



CRI ≥ 98
XPECTRUM

Order options

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

LIGHT OPTIC COVER

opal	H
microprismatic	Z
reflector (UGR ≤ 19)	

Options on request

COLOUR RENDERING INDEX


CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

tunable white 2700 – 6500 K

SLAT CEILING SOLUTION

Hunter Douglas
Interalu SAPPceiling



MILA opal / microprismatic ceiling

CRI ≥ 90 | RG0 IEC 62471 | DALI 1 ADDR. | 220-240V | X-PERT | X-PERT


SYSTEM LUMINAIRE

SYSTEM POWER	L (mm)	ORDER CODE
15.8 W	750	045-9022 ⁘ 3 ◪
21 W	1000	045-9023 ⁘ 3 ◪
25 W	1250	045-9024 ⁘ 3 ◪
31 W	1500	045-9025 ⁘ 3 ◪

COVER

TYPE	L (mm)	ORDER CODE
linear	750	006-4107510 ◘
linear	1000	006-4110010 ◘
linear	1250	006-4112510 ◘
linear	1500	006-4115010 ◘
continuous linear	6000	006-2106010 ◘
continuous linear	25000	006-2125010 ◘

LIGHT OPTIC COVER	COLOUR TEMPERATURE	SYSTEM POWER	DELIVERED LUMENS	EFFICACY
opal	3000 K	21 W/m	2200 lm/m	105 lm/W
	4000 K		2420 lm/m	115 lm/W
microprismatic	3000 K	21 W/m	2090 lm/m	100 lm/W
	4000 K		2300 lm/m	110 lm/W



MILA reflector ceiling

CRI ≥ 90 | UGR ≤19 | cd/m² ≤1500 | RG0 IEC 62471 | DALI 1 ADDR. | 220-240V | X-PERT | X-PERT

SYSTEM LUMINAIRE

SYSTEM POWER	L (mm)	ORDER CODE
11 W	504	045-9121 ⁘ 3 ◪ R
22 W	1004	045-9123 ⁘ 3 ◪ R

LIGHT OPTIC COVER	COLOUR TEMPERATURE	SYSTEM POWER	DELIVERED LUMENS	EFFICACY
reflector (UGR ≤ 19)	3000 K	22 W/m	2790 lm/m	126 lm/W
	4000 K		2950 lm/m	133 lm/W

Accessories

END CAPS

TYPE	ORDER CODE
end caps (pair)	045-909001 ◪


LINEAR CONNECTOR

TYPE	ORDER CODE
mechanical linear connector	045-9091010

SENSOR DALI-2

TYPE	ORDER CODE
ESSENTIAL (brightness & presence)	045-909601 ◪
SENSE (brightness, presence, temperature, sound pressure, humidity, CO_2)	045-909602 ◪


Viega GmbH Attersee, AT –
by ATP Planungs- und Beteiligungs AG with
lighting design by Andreas Haidegger







Spotlight your profile



FRAME / MINO 40 system

EN The FRAME 40 and MINO 40 system luminaires set no limits on profile-based ambient lighting. Thanks to special Flex Insets, the system luminaires can be shortened on-site and thus adapted to all conditions. Corner connectors create continuous lighting systems. For particularly uniform room illumination, the profile luminaires are fitted with an opal cover. In addition, spotlight insets can be selected for elegant accent lighting in corridors or entrance areas. Select a light colour of 3000 K, 4000 K, or optionally Tunable White, and a colour rendering of up to CRI ≥ 98 (XPECTRUM).

DE Mit der FRAME 40 und MINO 40 Systemleuchte sind Ihnen in puncto profilbasierter Grundausleuchtung keine Grenzen gesetzt. Aufgrund spezieller Flex-Insets können die Systemleuchten vor Ort gekürzt und somit an alle Gegebenheiten angepasst werden. Durch Eckverbinder entstehen so durchgängige Lichtsysteme. Für eine besonders einheitliche Raumausleuchtung wurden die Profilleuchten mit einer Opal-Abdeckung ausgestattet. Zusätzlich können Spots Insets zur eleganten Akzentuierung in Gängen oder Eingangsbereichen gewählt werden. Die Lichtfarbe ist aus 3000 K, 4000 K und wahlweise Tunable White und einer Farbwiedergabe von bis zu CRI ≥ 98 (XPECTRUM) wählbar.

Type

40

Mountings



with trim recessed



surface



suspended

Configurations

linear



corner

Light distributions



opal




direct




spotlight



wallwasher floor







Easy Mounting

EN MINO 40 / FRAME 40 is based on a profile with an integrated track, which makes only one power feed point necessary.

(1) Two profiles are connected to each other with mechanical and electrical connectors.

(2) The patent-pending snap-in system allows the inset to be quickly and easily mounted in the profile. This simplifies the installation and maintenance of the system.

(3) The flexible Continuous Cover can be adjusted exactly to the length of the system and simply installed in the profile during mounting. This creates a continuous lighting system without disturbing joints.

DE MINO 40 / FRAME 40 basiert auf einem Profil mit integrierter Stromschiene, wodurch lediglich eine Einspeisungsstelle benötigt wird.

(1) Mittels mechanischen und elektrischen Steckverbindern werden zwei Profile einfach miteinander verbunden.

(2) Durch das, zum Patent angemeldete, Snap-In System lässt sich das Inset schnell und unkompliziert in das Profil einsetzen. Dies vereinfacht die Montage und Wartung des Systems.

(3) Das flexible Continuous Cover kann exakt auf die Länge des Systems angepasst und einfach bei der Montage in das Profil eingebaut werden. Dadurch entsteht ein durchgängiges Lichtsystem ohne störende Stoßstellen.

Precise planning with flex insets

EN Your lighting system can be easily adapted to existing room dimensions. You can determine bespoke lengths for MINO 40 / FRAME 40. The special flex insets are precisely and flexibly adapted on-site during assembly. Boards are simply cut off at prefabricated breakpoints. These are positioned at 62.5 mm or 125 mm, depending on the length of the profile. This gives you a free hand and minimal restrictions in the lighting design.

DE Ihr Lichtsystem lässt sich einfach an vorhandene Raumdimensionen anpassen. Für MINO 40 / FRAME 40 können Sie individuelle Längen bestimmen. Die speziellen Flex-Insets werden vor Ort bei der Montage exakt und flexibel angepasst: Platinen werden einfach an vorgefertigten Bruchstellen abgetrennt. Diese befinden sich je nach Länge des Profils bei 62,5 mm oder 125 mm. Dadurch haben Sie freie Hand und kaum Einschränkungen bei der Lichtplanung.




Full-spectrum LED


EN XAL's new XPECTRUM LEDs deliver healthy, biologically effective light. The reduced blue light component and increased cyan values reduce the blue light hazard for the eye to daylight-equivalent levels. The resulting non-visual, so-called melanopic light effect, improves concentration and increases sleep quality. The excellent colour rendering of IES TM 30–15 R_f = 98 and R_g = 101 further helps visual comfort.

DE Die neue XPECTRUM LED von XAL sorgt für gesundes, biologisch wirksames Licht. Der reduzierte Blaulichtanteil sowie die erhöhten Cyan-Werte minimieren die Blaulichtgefahr für das Auge auf ein tageslichtähnliches Niveau. Die daraus resultierende nichtvisuelle, auch melanopische Lichtwirkung genannt, fördert die Konzentration und steigert die Schlafqualität. Die hervorragende Farbwiedergabe von IES TM 30–15 R_f = 98 und R_g = 101 ermöglicht zudem einen verbesserten Sehkomfort.

XPECTRUM LED



Commercially available LED 4000 K





Spot Insets

EN Elegant room accentuation and reduced design: with the new Spot Insets, the system luminaires become convertible luminaires for stylish wall, floor, and ceiling accentuation. In addition, the Wallwasher Floor light inset is perfect for uniform illumination of a blackboard in the classroom, or a corridor. The tool-free installation of the insets is completed in one move, the spotlights can be simply unlocked and snapped into place.

DE Elegante Raumakzentuierung und reduziertes Design: Mit den neuen Spot Insets werden die Systemleuchten zu wandelbaren Leuchten für eine stilvolle Wand-, Boden- und Deckenakzentuierung. Zudem eignet sich der Wallwasher Floor Lichteinsatz perfekt für eine gleichmäßige Ausleuchtung einer Tafel im Klassenzimmer oder eines Korridors. Die werkzeuglose Montage der Insets erfolgt durch einen Handgriff, die Strahler können einfach entriegelt und eingerastet werden.



FRAME 40 system

recessed with trim


EN Luminaire housing made of extruded aluminium; recessed luminaire with trim; designed for continuous lighting systems; suitable for ceiling thickness of 8-25 mm; surface powder coated; luminaire profile for mounting available in advance; remaining luminaire components mounted without tools; HPO (High Performance Opal) cover in the length of the light inset or continuous cover (both separately available); pre-assembled power rail for power supply in luminaire profile; voltage tap of the light inset on the power rail; light inset consisting of highly reflective coated extruded profile for improved thermal management; energy-efficient LEDs with very good colour rendering; optionally spotlight modules can be installed

DE Leuchtenkörper aus Aluminiumstrangpressprofil; Einbauleuchte mit umlaufendem Rand; ausgelegt für durchgehende Lichtsysteme; geeignet für Deckenstärken von 8-25 mm; Oberfläche pulverbeschichtet; Leuchtenprofil für Montage vorab lieferbar; restliche Leuchtenkomponenten werkzeuglos montierbar; HPO (High Performance Opal) Abdeckung in Lichteinsatzlänge oder durchgängige Abdeckung (beide separat zu bestellen); vormontierte Stromschiene zur Spannungsversorgung im Leuchtenprofil; Lichteinsatz-Spannungsabgriff an der Stromschiene; Lichteinsatz bestehend aus hochreflektierend lackiertem Strangpressprofil für verbessertes Thermomanagement; energieeffiziente LEDs mit sehr guter Farbwiedergabe; wahlweise Strahlereinsätze einsetzbar

Quickinfo

3000 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 2420 lm/m
up to 123 lm/W
L85 @ 50 000 h
DALI-2

Types



Colours



Light distributions





DiiA® standards 251, 252, 253




snap-in system (patent pending)




spotlight insets (p. 130)



breakable flex insets



tunable white 2700 – 6500 K



CRI ≥ 98 XPECTRUM

Order options

LED TYPE

mid lumen	1
high lumen	2

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8

LENGTH L

1000 mm	1
2000 mm	2
3000 mm	3

LIGHT OPTIC COVER

opal high performance

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE


tunable white 2700 – 6500 K

LIGHT OPTIC COVER

microprismatic

LUMINOUS FLUX value calculated for 4000 K, CRI ≥ 90, colour white, cover opal 3000 K -5 %

FRAME 40 trim




INSTALLATION CHANNEL

TYPE	L (mm)	ORDER CODE
channel	1000	042-700201
channel	2000	042-700401
channel	3000	042-700601
channel corner 90° / opal cover	500 × 500	042-700C01H

LIGHT OPTIC COVER 40

TYPE	L (mm)	ORDER CODE
linear cover	see left	006-42L0010H
continuous linear cover	6000	006-2206010H
continuous linear cover	30000	006-2230010H
blind cover	see left	006-42L001B





LIGHT INSET 40

SYSTEM POWER (MID / HIGH LUMEN)	L (mm)	ORDER CODE
12.4 / 20.1 W	1000	042-01 2 37
24.8 / 40 W	2000	042-01 4 37
37 / 60 W	3000	042-01 6 37
12.4 / 20.1 W flex	500 – 1000	042-01 F 37
24.8 / 40 W flex	1500 – 2000	042-01 G 37

LED TYPE / COVER	SYSTEM POWER	DELIVERED LM	EFFICACY
mid lumen / opal / 4000 K	12.4 W/m	1430 lm/m	116 lm/W
high lumen / opal / 4000 K	20.1 W/m	2240 lm/m	112 lm/W

Spotlight Insets


see page 130

Accessories




END CAPS

TYPE	ORDER CODE
end caps (pair)	042-709001



POWER FEEDER UNIT

TYPE	ORDER CODE
power feeder unit	042-1093230



LINEAR CONNECTOR

TYPE	ORDER CODE
mechanical linear connector	042-7091110
mechanical & electrical linear connector	042-7091230
opal cover linear connector	042-1091910


MOUNTING BRACKET

TYPE	CEILING THICKNESS (mm)	ORDER CODE
mounting bracket (1 piece)	8-25	042-7092110
mounting bracket (25 pieces)	8-25	042-7092110.25

number of brackets required: length of your system in metres+1

Psychiatrische Klinik Königshof Krefeld, DE –
by a|sh sander.hofrichter architekten GmbH





MINO 40 system

ceiling / suspended


EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; for lighting systems; powder coated; luminaire profile for mounting available in advance; remaining luminaire components mounted without tools; HPO (High Performance Opal) cover in the length of the light inset or continuous cover (both separately available); pre-assembled power rail for power supply in luminaire profile; voltage tap of the light inset on the power rail; ceiling surface mounting or suspended mounting; height adjustment without tools; with transparent feeder cable; light inset consisting of highly reflective coated extruded profile, improved thermal management; energy-eff. LEDs - very good colour rendering; optionally spotlight modules can be installed

DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; für Lichtsysteme; pulverbeschichtet; Leuchtenprofil für Montage vorab lieferbar; restliche Leuchtenkomponenten werkzeuglos montierbar; HPO (High Performance Opal) Abdeckung in Lichteinsatzlänge oder durchgängige Abdeckung (beide separat zu bestellen); vormontierte Stromschiene zur Spannungsversorgung im Leuchtenprofil; Lichteinsatz-Spannungsabgriff an der Stromschiene; Deckenanbau oder abgehängte Montage; werkzeuglose Höhenverstellung; inkl. transp. Einspeiseleitung; Lichteinsatz aus hochreflektierend lackiertem Strangpressprofil, verbessertes Thermomanagement; energieeff. LEDs - sehr gute Farbwiedergabe; wahlweise Strahlereinsätze einsetzbar

Quickinfo

3000 K, 4000 K
CRI ≥ 90, 3 SDCM
up to 2420 lm/m
up to 123 lm/W
L85 @ 50 000 h
DALI-2

Types



Colours



standard xal.com/colours

Light distributions



opal spot med. flood wall floor



DiiA® standards 251, 252, 253




snap-in system (patent pending)




spotlight insets (p. 130)



breakable flex insets



tunable white 2700 – 6500 K



CRI ≥ 98 XPECTRUM

Order options

LED TYPE

mid lumen	1
high lumen	2

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

DALI-2

MATERIAL COLOUR

○ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
special colours	X

LENGTH L

1000 mm	1
2000 mm	2
3000 mm	3

LIGHT OPTIC COVER

opal high performance

ACCESSORY COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8

Options on request

COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE

tunable white 2700 – 6500 K

LIGHT OPTIC COVER

microprismatic

LUMINOUS FLUX value calculated for 4000 K, CRI ≥ 90, colour white, cover opal 3000 K -5 %

MINO 40 ceiling / suspended



INSTALLATION CHANNEL


TYPE	L (mm)	ORDER CODE
channel	1000	042-100201
channel	2000	042-100401
channel	3000	042-100601
channel corner 90° / opal cover	500 × 500	042-100C01H



LIGHT OPTIC COVER 40

TYPE	L (mm)	ORDER CODE
linear cover	see left	006-42L0010H
continuous linear cover	6000	006-2206010H
continuous linear cover	30000	006-2230010H
blind cover	see left	006-42L001B





LIGHT INSET 40

SYSTEM POWER (MID / HIGH LUMEN)	L (mm)	ORDER CODE
12.8 / 21 W	1000	042-01 2 37
25.6 / 42 W	2000	042-01 4 37
38 / 63 W	3000	042-01 6 37
12.8 / 21 W flex	500 – 1000	042-01 F 37
25.6 / 42 W flex	1500 – 2000	042-01 G 37

LED TYPE / COVER	SYSTEM POWER	DELIVERED LM	EFFICACY
mid lumen / opal / 4000 K	12.8 W/m	1560 lm/m	122 lm/W
high lumen / opal / 4000 K	21 W/m	2420 lm/m	115 lm/W

Spotlight Insets

see page 130

Accessories



END CAPS

TYPE	ORDER CODE
end caps (pair)	042-109001




POWER FEEDER UNIT

TYPE	ORDER CODE
power feeder unit	042-1093230



LINEAR CONNECTOR


TYPE	ORDER CODE
mechanical linear connector	042-7091110
mechanical & electrical linear connector	042-7091230
opal cover linear connector	042-1091910



CEILING FASTENER / CABLE SUSPENSION / CANOPY

TYPE	L (mm)	ORDER CODE
ceiling fastener	10	050-204111
cable suspension	1500	005-2152110
canopy		005-231121
feeder cable (transparent)		005-2412410

for electrical system configuration see luminaire data sheet at xal.com



SPOTLIGHT insets

profiles 40

EN Cylindrical spotlight made of aluminium; powder coated; spotlight can be installed without tools in MINO 40 system or FRAME 40 system; choice of single lamp or double lamps; spotlight head rotatable (WALLWASHER / FLOOR) or rotatable and tiltable (SPOTLIGHT); converter in the adapter; with optional high quality lens system with precise radiation characteristic; or high quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristics with different beam angles; optional asym. light distribution; good glare reduction due to recessed light point plane; optical attachments as accessories; COB (Chip on Board) technology or high power LEDs - maximum efficiency; no multiple shadows; energy-eff. LEDs - very good colour rendering


DE Zylindrischer Strahler aus Aluminium; pulverbeschichtet; Strahler in MINO 40 system oder FRAME 40 system werkzeuglos einsetzbar; wahlweise einflammig oder zweiflammig; Strahlerkopf drehbar (WALLWASHER / FLOOR) bzw. dreh- und schwenkbar (SPOTLIGHT); Konverter im Adapter; wahlweise mit hochwertiger Linsenoptik mit präziser Abstrahlcharakteristik; oder hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; optional asym. Lichtverteilung; gute Entblendung durch zurückversetzte Lichtpunktebene; optische Aufsätze als Zubehör; COB (Chip on Board) Technologie bzw. High-Power-LEDs - höchste Effizienz; keine Mehrfachschatten; energieeff. LEDs - sehr gute Farbwiedergabe

Quickinfo


3000 K, 4000 K
CRI ≥ 90, 2 SDCM
spotlight 32 up to 79 lm/W
spotlight 45 up to 85 lm/W
L80 @ 50 000 h
DALI-2

Types


SPOTLIGHT 32



SPOTLIGHT 45



SPOTLIGHT 45 wallwasher floor



Colours



Light distributions





DiiA® standards 251, 252, 253



snap-in system (patent pending)



wallwasher floor 360° rotatable



wallwasher floor

Order options

COLOUR TEMPERATURE

3000 K	0
4000 K	1

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE SPOTLIGHT 32


spot 18°	S
medium 23°	M
flood 37°	F

BEAM ANGLE SPOTLIGHT 45

spot 14°	S
medium 24°	M
flood 39°	F

SPOTLIGHT 32

360° · 90° | CRI ≥ 90 | 2-SDCM | 1 ADDR. | 220-240 V | X-PERT | X-PERT




2 LAMPS

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
20.6 W	2 × 810 lm	042-0610 ⁘ 3 ◪ ▲
honeycomb louver		007-1965168


SPOTLIGHT 45

360° · 90° | CRI ≥ 90 | 2-SDCM | 1 ADDR. | 220-240 V | X-PERT | X-PERT



1 LAMP

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
15 W	spot 1060 lm	042-0520 ⁘ 3 ◪ S
15.9 W	medium, flood 1340 lm	042-0520 ⁘ 3 ◪ ▲
honeycomb louver		007-1965188




2 LAMPS

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
30 W	spot 2 × 1060 lm	042-0620 ⁘ 3 ◪ S
32 W	medium, flood 2 × 1340 lm	042-0620 ⁘ 3 ◪ ▲
honeycomb louver		007-1965188


SPOTLIGHT 45 wallwasher / floor

360° | CRI ≥ 90 | 2-SDCM | 1 ADDR. | 220-240 V | X-PERT | X-PERT



1 LAMP

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
9 W	659 lm	042-0520 ⁘ 3 ◪ W



2 LAMPS

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
15.9 W	2 × 659 lm	042-0620 ⁘ 3 ◪ W

LUMINOUS FLUX value calculated for 4000 K, CRI ≥ 90, colour white, medium 3000 K -5 %

Corridor
Visualisation



Get in contact

EN We develop and perfect projects in dialogue with the architects and planners to make them unique. We see ourselves as your partner. From lighting design, the right product selection and control system to commissioning and maintenance, we are at your side throughout your project. Let's talk about your project: **office@xal.com**

DE Wir haben es uns zu unserer Aufgabe gemacht, gemeinsam mit den ArchitektInnen und PlanerInnen die Projekte im Dialog zu entwickeln, zu perfektionieren und sie einzigartig zu machen. Wir sehen uns als Ihr Partner. Von der Lichtplanung über die richtige Produktauswahl und von der Steuerung bis hin zur Inbetriebnahme und Wartung stehen wir Ihnen in allen Phasen Ihres Projektes zur Seite. Reden wir über Ihr Projekt: **office@xal.com**

XAL Headquarters

XAL GmbH
Auer-Welsbach-Gasse 36
8055 Graz
AUSTRIA
T +43.316.3170
office@xal.com

All locations:
xal.com/contacts

List of photographers

Kris Dekeijser (Cover), Kurt Kuball (p. 52-53 | 86-87 | 98-99 | 118-119), Tim Ertl (p. 66-67), Z. Gataric Fotografie (p. 90), Dan Preston (p. 91), Oberpollinger | The KaDeWe Group (p. 95 | 100-101), Jens Pfisterer (p. 110-111), Huy Nguyen (p. 106-107), Markus Bachmann (p. 126-127)

Legal notices

EN Information in this catalogue was valid at the time of printing, is non-binding, and should be used for information purposes only. We are not liable for products that differ from illustrations or information. We reserve the right to make changes to our products at any time. All orders will be accepted exclusively in accordance with our general terms and conditions of business and delivery. The latest version of these terms and conditions is available at www.xal.com.

DE Die Angaben in diesem Katalog entsprechen dem Stand bei Drucklegung, sind unverbindlich und sollen ausschließlich Informationszwecken dienen. Für Abweichungen eines Produkts von Abbildungen oder Angaben wird keine Haftung übernommen. Wir behalten uns vor, jederzeit Änderungen an unseren Produkten vorzunehmen. Alle Aufträge werden ausschließlich zu unseren Allgemeinen Geschäfts- und Lieferbedingungen, die unter www.xal.com eingesehen werden können, in der gültigen Fassung entgegengenommen.

© 2023-04