



SPADO 100 / 150 round

recessed


EN Round or square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; symmetric radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system

DE Runder oder quadratischer Leuchtenkörper aus Aluminiumdruckguss; mit umlaufendem Rand; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; werkzeu-glose Montage mittels Schnappfederver-schluss; Reflektor aus Polycarbonat, chrom poliert; symmetrische Abstrahlcharakteristik; Leuchtenebene zurückversetzt; energieeffiziente LEDs mit sehr guter Farbwiedergabe; externer Konverter für Deckeneinwurf, für Weit-erverdrahtung geeignet; Betriebsgerät geeignet für den Betrieb an einem Zentralbatterie-Sys-tem

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
UGR $\leq$ 19
up to 116 lm/W
L80 / 50000 h, L90 / 50000 h
DALI-2, non DIM
front IP44, back IP20

Types



Colour



Light distributions



DiiA® standards
251, 252, 253



glare control
(UGR $\leq$ 19)



splash water
protection
(IP44)





SPADO 100 round downlight trim



WIDE FLOOD CRI ≥ 80, traffic white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
9.3 W	3000 K	934 lm	100 lm/W	0 4 9 - 3 1 1 1 5 7 0
	4000 K	989 lm	106 lm/W	0 4 9 - 3 1 1 1 6 7 0




SPADO 150 round downlight trim



WIDE FLOOD CRI ≥ 80, traffic white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
16.4 W	3000 K	1810 lm	110 lm/W	0 4 9 - 3 1 2 1 5 7 0
	4000 K	1910 lm	116 lm/W	0 4 9 - 3 1 2 1 6 7 0
27.5 W	3000 K	2950 lm	107 lm/W	0 4 9 - 3 1 2 3 5 7 0
	4000 K	3130 lm	114 lm/W	0 4 9 - 3 1 2 3 6 7 0



Mounting accessories (optional)

EXPOSED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
295·295·160	0 4 9 - 3 1 9 1 2 1 0

PRIMED CONCRETE MOUNTING HOUSING

L·W (mm)	ORDER CODE
310·170	0 4 9 - 3 1 9 1 4 1 0

Order options

CONTROL		COLOUR	
non DIM	1	traffic white	RAL 9016
DALI-2	3		