

## MINO 60 CIRCLE

suspended


**EN** Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; surface powder coated; pendant fitting with cable suspension; with integrated toolless suspension height adjustment; incl. feeder cable; light inset consisting of highly reflective coated die-cast aluminium for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; optional with direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; sound absorbing elements available

**DE** Ringförmiger Leuchtenkörper aus gerolltem Aluminiumstrangpressprofil nahtlos verschweißt; Oberfläche pulverbeschichtet; abgependelt mit Seilabhängung; werkzeuglose Höhenverstellung an der Leuchte; inkl. Einspeiseleitung; Lichteinsatz bestehend aus hochreflektierend lackiertem Aluminiumdruckguss für verbessertes Thermomanagement; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; mikroprismatische PMMA-Abdeckung inkl. Diffusorfolie zur Reduktion der Leuchtdichte bei homogener Ausleuchtung; optional mit direkt/indirekter Abstrahlcharakteristik für zusätzliche Akzentuierung der Decke und mehr Sehkomfort; energieeffiziente LEDs mit sehr guter Farbwiedergabe; schallabsorbierende Elemente erhältlich

### Quickinfo

3000 K, 4000 K  
CRI  $\geq$  80 / 3 SDCM  
UGR  $\leq$  19  
up to  $\downarrow$  12,000 lm /  $\uparrow$  5,490 lm  
up to 154 lm/W  
L90 / 50000 h  
DALI-2  
High Performance Opal,  
Microprismatic  
IP20

### Types



### Colour




### Light distributions



DiiA® standards  
251, 252, 253




direct / indirect  
illumination




microprismatic



acoustic  
elements



\*canopy central version



## MINO 60 CIRCLE 1000 suspended



### OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
53.0 W	3000 K	6570 lm	124 lm/W	0 3 4 - 2 5 1 2 5 3 H
	4000 K	7480 lm	141 lm/W	0 3 4 - 2 5 1 2 6 3 H

### MICROPRISMATIC | DIRECT CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
53.0 W	3000 K	5710 lm	108 lm/W	0 3 4 - 2 5 1 2 5 3 Z
	4000 K	6500 lm	123 lm/W	0 3 4 - 2 5 1 2 6 3 Z

### OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	↓6570/↑3010 lm	135 lm/W	0 3 4 - 2 5 1 3 5 3 H
	4000 K	↓7480/↑3430 lm	154 lm/W	0 3 4 - 2 5 1 3 6 3 H

### MICROPRISMATIC | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	↓5710/↑3010 lm	123 lm/W	0 3 4 - 2 5 1 3 5 3 Z
	4000 K	↓6500/↑3430 lm	140 lm/W	0 3 4 - 2 5 1 3 6 3 Z



\*canopy central version



## MINO 60 CIRCLE 1500 suspended



### OPAL | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
83.0 W	3000 K	10500 lm	127 lm/W	0 3 4 - 2 5 1 0 5 3 H
	4000 K	12000 lm	145 lm/W	0 3 4 - 2 5 1 0 6 3 H

### MICROPRISMATIC | DIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
83.0 W	3000 K	9130 lm	110 lm/W	0 3 4 - 2 5 1 0 5 3 Z
	4000 K	10400 lm	125 lm/W	0 3 4 - 2 5 1 0 6 3 Z

### OPAL | DIRECT / INDIRECT CRI ≥ 80, DALI-2


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
114.0 W	3000 K	↓10500/↑4820 lm	134 lm/W	0 3 4 - 2 5 1 1 5 3 H
	4000 K	↓12000/↑5490 lm	154 lm/W	0 3 4 - 2 5 1 1 6 3 H

### MICROPRISMATIC | DIRECT / INDIRECT CRI ≥ 80, DALI-2

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
114.0 W	3000 K	↓9130/↑4820 lm	122 lm/W	0 3 4 - 2 5 1 1 5 3 Z
	4000 K	↓10400/↑5490 lm	139 lm/W	0 3 4 - 2 5 1 1 6 3 Z

## Order options

MOUNTING		COLOUR	
cable 1500 mm	2	pure white RAL 9010	7
cable 1500 mm / canopy central	4	jet black RAL 9005	8
		white aluminium RAL 9006	G
		special colours	X





### MINO 60 CIRCLE 3000 suspended



**OPAL | DIRECT** CRI ≥ 80, cable 1500 mm, DALI-2, pure white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
167.0 W	3000 K	21200 lm	127 lm/W	0 3 4 - 2 2 1 4 5 3 7 H
	4000 K	24100 lm	144 lm/W	0 3 4 - 2 2 1 4 6 3 7 H




### MINO 60 CIRCLE 6000 suspended




**OPAL | DIRECT** CRI ≥ 80, cable 1500 mm, DALI-2, pure white

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
334.0 W	3000 K	42300 lm	127 lm/W	0 3 4 - 2 2 1 6 5 3 7 H
	4000 K	48100 lm	144 lm/W	0 3 4 - 2 2 1 6 6 3 7 H




### Acoustic accessories (optional)

#### MINO CIRCLE ACOUSTIC 1000 inlay



COLOUR	Ø-H (mm)	ORDER CODE
anthracite	937-24	0 3 4 - 2 7 0 1 1 1 B
marble grey	937-24	0 3 4 - 2 7 0 1 1 1 D
black	937-24	0 3 4 - 2 7 0 1 1 1 L
limestone	937-24	0 3 4 - 2 7 0 1 1 1 S
white	937-24	0 3 4 - 2 7 0 1 1 1 W

#### MINO CIRCLE ACOUSTIC 1500 inlay



COLOUR	Ø-H (mm)	ORDER CODE
anthracite	1434-24	0 3 4 - 2 7 0 2 1 1 B
marble grey	1434-24	0 3 4 - 2 7 0 2 1 1 D
black	1434-24	0 3 4 - 2 7 0 2 1 1 L
limestone	1434-24	0 3 4 - 2 7 0 2 1 1 S
white	1434-24	0 3 4 - 2 7 0 2 1 1 W

# Vifor Pharma

Switzerland

## Architect

Aroma Architecture,  
Alessandro Nicotra

## Lighting Design

SLG Lichtdesigner

## Photographer

Z. Gataric Fotografie



## Used products



**MINO 60 CIRCLE**  
suspended







# Porr Bau GmbH, Vienna

Austria

## Architect

Mayr & Gratzl

## Photographer

Gabriel Büchelmeier  
Fotografie



## Used products



**MINO 60 CIRCLE**  
suspended





