



TASK

free standing


EN Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

DE Stehleuchte mit rechteckigem Leuchtenkopf aus Aluminium und abgerundeten Kanten; extrem flache Bauform (nur 15 mm); Standrohr rechteckig; Standfuß mit Ausnehmung für Tischfuß; Oberfläche pulverbeschichtet; direkt/indirekte Lichtverteilung durch LGP-Body (Light Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach oben und unten gelenkt; optional: Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom; optional: Indirektlichtanteil mit eigenen, schräg gerichteten Platinen für asymmetrische Abstrahlcharakteristik; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schalter im Standrohr verbaut; inkl. Anschlussleitung (3m) mit Schutzkontaktstecker

Quickinfo

3000 K, 4000 K
 CRI $\geq$ 90 / 3 SDCM
 UGR $\leq$ 10, UGR $\leq$ 13, UGR $\leq$ 19
 up to ↓ 4,370 lm / ↑ 11,000 lm
 up to 137 lm/W
 L90 / 50000 h
 Loxone Air / ESSENTIAL sensor,
 Loxone Air / touch DIM on pole,
 stand alone ESSENTIAL sensor,
 touch DIM on pole
 Microprismatic
 IP20

Types



Colour



Light distributions



suitable for
double
workstation




SENSE sensor
on request




lighting control
by touch DIM
on pole




tunable white
2700 – 6500 K



CRI $\geq$ 98
XPECTRUM
(optional)



TASK free standing U-shape



MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	↓4100/↑13350 lm	105 lm/W	0 5 9 - 2 9 4 3 0 Z
	4000 K	↓4370/↑13560 lm	112 lm/W	0 5 9 - 2 9 4 3 1 Z

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
80.0 W	3000 K	↓2400/↑7330 lm	122 lm/W	0 5 9 - 2 9 4 2 0 Z
	4000 K	↓2550/↑7800 lm	129 lm/W	0 5 9 - 2 9 4 2 1 Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
95.0 W	4000 K	↓2030/↑11000 lm	137 lm/W	0 5 9 - 2 9 4 1 1 Z
97.0 W	3000 K	↓1900/↑10300 lm	126 lm/W	0 5 9 - 2 9 4 1 0 Z



TASK free standing T-shape



MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	↓4100/↑13350 lm	105 lm/W	0 5 9 - 2 9 5 3 0 Z
	4000 K	↓4370/↑13560 lm	112 lm/W	0 5 9 - 2 9 5 3 1 Z

MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
80.0 W	3000 K	↓2400/↑7330 lm	122 lm/W	0 5 9 - 2 9 5 2 0 Z
	4000 K	↓2550/↑7800 lm	129 lm/W	0 5 9 - 2 9 5 2 1 Z

MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
95.0 W	4000 K	↓2030/↑11000 lm	137 lm/W	0 5 9 - 2 9 5 1 1 Z
97.0 W	3000 K	↓1900/↑10300 lm	126 lm/W	0 5 9 - 2 9 5 1 0 Z

Order options

CONTROL		COLOUR	
touch DIM on pole	5	white aluminium RAL 9006	6
stand alone ESSENTIAL sensor	7	pure white RAL 9010	7
Loxone Air / ESSENTIAL sensor	S	jet black RAL 9005	8
Loxone Air / touch DIM on pole	T	special colours	X

Office OMV, Vienna

Austria

Photographer
Kurt Kuball



Used products



TASK free standing

