



## TASK

free standing


**EN** Free standing luminaire with rectangular luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15mm); rectangular downpipe; pedestal with recess for table base; surface powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; optional: indirect component with special PCBs for increased luminous flux; optional: indirect component with special, inclined PCBs for asymmetric radiation characteristic; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

**DE** Stehleuchte mit rechteckigem Leuchtenkopf aus Aluminium und abgerundeten Kanten; extrem flache Bauform (nur 15mm); Standrohr rechteckig; Standfuß mit Ausnehmung für Tischfuß; Oberfläche pulverbeschichtet; direkt/indirekte Lichtverteilung durch LGP-Body (Light Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach oben und unten gelenkt; optional: Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom; optional: Indirektlichtanteil mit eigenen, schräg gerichteten Platinen für asymmetrische Abstrahlcharakteristik; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schalter im Standrohr verbaut; inkl. Anschlussleitung (3m) mit Schutzkontaktstecker

### Quickinfo

3000 K, 4000 K  
 CRI  $\geq$  90 / 3 SDCM  
 UGR  $\leq$  10, UGR  $\leq$  13, UGR  $\leq$  19  
 up to ↓ 4,370 lm / ↑ 11,000 lm  
 up to 137 lm/W  
 L90 / 50000 h  
 Loxone Air / ESSENTIAL sensor,  
 Loxone Air / touch DIM on pole,  
 stand alone ESSENTIAL sensor,  
 touch DIM on pole  
 Microprismatic  
 IP20

### Types



### Colour



### Light distributions



suitable for  
double  
workstation




SENSE sensor  
on request




lighting control  
by touch DIM  
on pole




tunable white  
2700 – 6500 K



CRI  $\geq$  98  
**XPECTRUM**  
(optional)



## TASK free standing U-shape



### MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	↓4100/↑13350 lm	105 lm/W	0 5 9 - 2 9 4 3 0   Z
	4000 K	↓4370/↑13560 lm	112 lm/W	0 5 9 - 2 9 4 3 1   Z

### MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90


SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
80.0 W	3000 K	↓2400/↑7330 lm	122 lm/W	0 5 9 - 2 9 4 2 0   Z
	4000 K	↓2550/↑7800 lm	129 lm/W	0 5 9 - 2 9 4 2 1   Z

### MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
95.0 W	4000 K	↓2030/↑11000 lm	137 lm/W	0 5 9 - 2 9 4 1 1   Z
97.0 W	3000 K	↓1900/↑10300 lm	126 lm/W	0 5 9 - 2 9 4 1 0   Z



## TASK free standing T-shape



### MICROPRISMATIC | DIRECT / INDIRECT SOFT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
71.0 W	3000 K	↓4100/↑13350 lm	105 lm/W	0 5 9 - 2 9 5 3 0   Z
	4000 K	↓4370/↑13560 lm	112 lm/W	0 5 9 - 2 9 5 3 1   Z

### MICROPRISMATIC | DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
80.0 W	3000 K	↓2400/↑7330 lm	122 lm/W	0 5 9 - 2 9 5 2 0   Z
	4000 K	↓2550/↑7800 lm	129 lm/W	0 5 9 - 2 9 5 2 1   Z

### MICROPRISMATIC | DIRECT / INDIRECT ASYMMETRIC POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
95.0 W	4000 K	↓2030/↑11000 lm	137 lm/W	0 5 9 - 2 9 5 1 1   Z
97.0 W	3000 K	↓1900/↑10300 lm	126 lm/W	0 5 9 - 2 9 5 1 0   Z

## Order options

CONTROL		COLOUR	
touch DIM on pole	5	white aluminium RAL 9006	6
stand alone ESSENTIAL sensor	7	pure white RAL 9010	7
Loxone Air / ESSENTIAL sensor	S	jet black RAL 9005	8
Loxone Air / touch DIM on pole	T	special colours	X

# Office OMV, Vienna

Austria

**Photographer**  
Kurt Kuball



## Used products



## TASK free standing



