



TASK square

free standing


^{EN} Free standing luminaire with square luminaire head made of aluminium and rounded edges; ultra low-profile design (only 15 mm); steel round downpipe; pedestal with recess for table base; surface powder coated; direct light distribution by LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect component with special PCBs for increased luminous flux and maximum ceiling illumination; completely homogeneous illumination; energy-efficient LEDs with very good colour rendering; switch installed in the downpipe; incl. connection cable (3m) with safety plug

^{DE} Stehleuchte mit quadratischem Leuchtenkopf aus Aluminium und abgerundeten Kanten; extrem flache Bauform (nur 15 mm); Stahlrohr rund; Standfuß mit Ausnehmung für Tischfuß; Oberfläche pulverbeschichtet; direkte Lichtverteilung durch LGP-Body (Light-Guiding-Prism); seitlich eingekoppeltes Licht durch Lasergravur nach unten gelenkt; Indirektlichtanteil mit eigenen Platinen für erhöhten Lichtstrom und maximale Deckenaufhellung; absolut homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Schalter im Standrohr verbaut; inkl. Anschlussleitung (3m) mit Schutzkontaktstecker

Quickinfo

3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM
UGR $\leq$ 10
up to ↓ 2,420 lm / ↑ 10,700 lm
up to 143 lm/W
L90 / 50000 h
stand alone ESSENTIAL sensor,
touch DIM on pole
Microprismatic
IP20

Types



Colour




Light distributions




suitable for
fourfold
workstation



lighting control
by touch DIM
on pole



CRI $\geq$ 98
XPECTRUM
(optional)




TASK square free standing



DIRECT / INDIRECT POWER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
92.0 W	3000 K	↓2280/↑10000 lm	133 lm/W	0 5 9 - 2 9 3 2 0 Z
	4000 K	↓2420/↑10700 lm	143 lm/W	0 5 9 - 2 9 3 2 1 Z

Planning Information



TASK square free standing
92 W, 4000 K, direct/indirect power

ROOM VALUES	
Room dimensions	7.2 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE	
Surface dimensions	4.8 × 0.6 m
Surface height	0.75 m
Average illuminance (E _m)	> 500 lx

GLARE EVALUATION	
Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19
65° ≤ 3000 cd/m²	

Order options

CONTROL		COLOUR	
touch DIM on pole	5	white aluminium RAL 9006	6
stand alone ESSENTIAL sensor	7	pure white RAL 9010	7
		jet black RAL 9005	8
		special colours	X

Office MyHammer

Germany

Architect

designfunktion
Gesellschaft für
moderne Einrichtung
Berlin mbH

Photographer

Werner Huthmacher



Used products



**TASK square free
standing**

