




Quickinfo

3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM
up to 102 lm/W
L80 / 50000 h
DALI-2, non DIM
IP20

Types



Colour



Light distributions



BO 55 / 70

track

EN Track light made of die-cast aluminium; surface powder coated; spotlight head 355° rotatable and 90° tiltable; converter integrated in the power track adapter; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristics with different beam angles; good glare reduction due to recessed light point plane; optical attachments as accessories; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks

DE Stromschienenstrahler aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; Strahlerkopf 355° dreh- und 90° schwenkbar; Konverter im Stromschienen-Adapter integriert; hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; gute Entblendung durch zurückversetzte Lichtpunktebene; optische Aufsätze als Zubehör; mit COB (Chip on Board) Technologie für höchste Effizienz; keine Bildung von Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Stromschienen



compatible with
MOVE IT PRO





355° rotatable,
90° tiltable



glare control
via honeycomb
louver



CRI ≥ 95 2
SDCM
(optional)



BO 55 track



SPOT CRI ≥ 90



SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
22.3 W	3000 K	2170 lm	97 lm/W	1 8 0 - 7 3 1 2 5 S
	3500 K	2220 lm	100 lm/W	1 8 0 - 7 3 1 2 7 S
	4000 K	2280 lm	102 lm/W	1 8 0 - 7 3 1 2 6 S

MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
22.3 W	3000 K	2140 lm	96 lm/W	1 8 0 - 7 3 1 2 5 M
	3500 K	2190 lm	98 lm/W	1 8 0 - 7 3 1 2 7 M
	4000 K	2240 lm	100 lm/W	1 8 0 - 7 3 1 2 6 M

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
22.3 W	3000 K	2130 lm	96 lm/W	1 8 0 - 7 3 1 2 5 F
	3500 K	2180 lm	98 lm/W	1 8 0 - 7 3 1 2 7 F
	4000 K	2230 lm	100 lm/W	1 8 0 - 7 3 1 2 6 F



BO 70 track



SPOT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
34.0 W	3000 K	3210 lm	94 lm/W	1 8 0 - 7 4 1 1 5 S
	3500 K	3290 lm	97 lm/W	1 8 0 - 7 4 1 1 7 S
	4000 K	3370 lm	99 lm/W	1 8 0 - 7 4 1 1 6 S

MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
34.0 W	3000 K	3090 lm	91 lm/W	1 8 0 - 7 4 1 1 5 M
	3500 K	3170 lm	93 lm/W	1 8 0 - 7 4 1 1 7 M
	4000 K	3240 lm	95 lm/W	1 8 0 - 7 4 1 1 6 M

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
34.0 W	3000 K	3150 lm	93 lm/W	1 8 0 - 7 4 1 1 5 F
	3500 K	3230 lm	95 lm/W	1 8 0 - 7 4 1 1 7 F
	4000 K	3310 lm	97 lm/W	1 8 0 - 7 4 1 1 6 F

WIDE FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
34.0 W	3000 K	2920 lm	86 lm/W	1 8 0 - 7 4 1 1 5 W
	3500 K	3000 lm	88 lm/W	1 8 0 - 7 4 1 1 7 W
	4000 K	3070 lm	90 lm/W	1 8 0 - 7 4 1 1 6 W

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8

Optical accessories (optional)



HONEYCOMB LOUVER			
TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 55 SASSO 100	jet black	50·3	0 0 7 - 1 9 6 5 5 9 8



HONEYCOMB LOUVER			
TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 70 PABLO	jet black	61·3	0 8 0 - 5 9 0 0 0 1 8

OVAL LENS

TYPE	Ø-H (mm)	ORDER CODE
for BO 55	50·3	0 0 7 - 1 9 6 5 8 9 0

SOFT LENS

TYPE	Ø-H (mm)	ORDER CODE
for BO 55	50·3	0 0 7 - 1 9 6 5 9 9 0

WALLWASHER LENS

TYPE	Ø-H (mm)	ORDER CODE
for BO 55	50·3	0 0 7 - 1 9 6 5 7 9 0