




Quickinfo

3000 K, 3500 K, 4000 K
 CRI \geq 90 / 2 SDCM
 up to 149 lm/W
 L80 / 50000 h
 DALI-2, non DIM
 IP20

Types



Colour



Light distributions



compatible with
MOVE IT PRO



up to 149 lm/W
(high efficiency)



optical
accessories



optical
accessories
can be
combined
(max. 2)



355° rotatable,
90° tiltable

VARO 80 S

^{EN} Track light made of die-cast aluminium; surface powder coated; spotlight head 355° rotatable and 90° tiltable; integrated converter in the plastic adapter; high quality reflector with spherical facet finish; precise radiation characteristics with different beam angles; installed and exchanged without tools; optical attachments as accessories; optical attachments can be combined; COB (Chip on Board) technology for maximum efficiency; variants with >120 lm/W available; no multiple shadows; energy-efficient LEDs with very good colour rendering; adapter for toolless insertion or movement on a variety of 3-phase power tracks



















^{DE} Stromschienenstrahler aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; Strahlerkopf 355° dreh- und 90° schwenkbar; Konverter im Kunststoffadapter integriert; hochwertiger Reflektor mit sphärischer Facettenoptik; präzise Abstrahlcharakteristik mit verschiedenen Ausstrahlwinkeln; werkzeuglos einsetz- bzw. austauschbar; optische Aufsätze als Zubehör; optische Aufsätze miteinander kombinierbar; mit COB (Chip on Board) Technologie für höchste Effizienz; Varianten mit >120 lm/W verfügbar; keine Bildung von Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Stromschienen




VARO 80 S track





















SPOT CRI ≥ 90



















SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.0 W	3000 K	1880 lm	145 lm/W	1 8 0 - 6 4 2 4 0   S
	3500 K	1900 lm	146 lm/W	1 8 0 - 6 4 2 4 2   S
	4000 K	1910 lm	147 lm/W	1 8 0 - 6 4 2 4 1   S
21.1 W	3000 K	2750 lm	130 lm/W	1 8 0 - 6 4 2 2 0   S
	3500 K	2780 lm	132 lm/W	1 8 0 - 6 4 2 2 2   S
	4000 K	2790 lm	132 lm/W	1 8 0 - 6 4 2 2 1   S
25.3 W	3000 K	3100 lm	123 lm/W	1 8 0 - 6 4 2 3 0   S
	3500 K	3140 lm	124 lm/W	1 8 0 - 6 4 2 3 2   S
	4000 K	3140 lm	124 lm/W	1 8 0 - 6 4 2 3 1   S



MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.0 W	3000 K	1920 lm	148 lm/W	1 8 0 - 6 4 2 4 0   M
	3500 K	1940 lm	149 lm/W	1 8 0 - 6 4 2 4 2   M
	4000 K	1940 lm	149 lm/W	1 8 0 - 6 4 2 4 1   M
21.1 W	3000 K	2800 lm	133 lm/W	1 8 0 - 6 4 2 2 0   M
	3500 K	2830 lm	134 lm/W	1 8 0 - 6 4 2 2 2   M
	4000 K	2840 lm	135 lm/W	1 8 0 - 6 4 2 2 1   M
25.3 W	3000 K	3150 lm	125 lm/W	1 8 0 - 6 4 2 3 0   M
	3500 K	3190 lm	126 lm/W	1 8 0 - 6 4 2 3 2   M
	4000 K	3200 lm	126 lm/W	1 8 0 - 6 4 2 3 1   M

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.0 W	3000 K	1890 lm	145 lm/W	1 8 0 - 6 4 2 4 0   F
	3500 K	1910 lm	147 lm/W	1 8 0 - 6 4 2 4 2   F
	4000 K	1920 lm	148 lm/W	1 8 0 - 6 4 2 4 1   F
21.1 W	3000 K	2760 lm	131 lm/W	1 8 0 - 6 4 2 2 0   F
	3500 K	2790 lm	132 lm/W	1 8 0 - 6 4 2 2 2   F
	4000 K	2800 lm	133 lm/W	1 8 0 - 6 4 2 2 1   F
25.3 W	3000 K	3110 lm	123 lm/W	1 8 0 - 6 4 2 3 0   F
	3500 K	3150 lm	125 lm/W	1 8 0 - 6 4 2 3 2   F
	4000 K	3160 lm	125 lm/W	1 8 0 - 6 4 2 3 1   F

Planning Information




possibility to combine different optical accessories (max. 2 pieces)

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8

Optical accessories (optional)


HONEYCOMB LOUVER



Ø-H (mm)	ORDER CODE
75-9	0 8 0 - 6 4 0 1 1 1 8



LINEAR PRISMATIC LENS	
Ø-H (mm)	ORDER CODE
75-9	0 8 0 - 6 4 0 2 1 1 0 P



SNOOT angle	
Ø-H (mm)	ORDER CODE
66-38	0 8 0 - 6 4 0 3 3 1 8



SNOOT medium	
Ø-H (mm)	ORDER CODE
66-38	0 8 0 - 6 4 0 3 2 1 8



SNOOT short	
Ø-H (mm)	ORDER CODE
66-23	0 8 0 - 6 4 0 3 1 1 8

On Running, Zurich

Switzerland

Architect

spillmann echsle
architekten ag

Lighting Design

Caduff & Stocker,
lichtplanung gmbh

Photographer

Eduardo Perez



Used products



VARO 80 S



MOVE IT 45 surface /
suspended system



L1 MOVE IT 45









Bank Raiffeisen, Founex

Switzerland

Architect

ABA PARTENAIRES SA

Photographer

Julie Masson



Used products



VARO 80 S



