




Quickinfo

3000 K, 4000 K
 CRI $\geq$ 90, CRI $\geq$ 95 / 2 SDCM, 3 SDCM
 up to 78 lm/W
 L85 / 50000 h, L90 / 50000 h
 DALI-2, DIM POTI
 IP20

Types



Colour



Light distributions



PABLO basic / focus

EN Track light made of die-cast aluminium; surface powder coated; 360° rotatable and 310° tiltable; converter in spotlight housing; COB (Chip on Board) technology - maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; PABLO basic: high quality aluminium reflector with spherical facet finish; high-gloss anodised; precise radiation characteristic with different light distributions (symmetric / asymmetric); installed and exchanged without tools; PABLO focus: incl. high quality plano-convex glass lens; precise object focusing through adjustable lens; adjustable beam angle of 17-47°; focusing by means of rubberised adjusting ring on the spotlight head; optical attachments as accessories; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation optionally without tools by means of knurled screw or set screw (screwdriver required); point outlet, either in surface mounted housing or recessed housing, available as an accessory

DE Stromschienenstrahler aus Aluminiumdruckguss; Oberfläche pulverbeschichtet; 360° dreh- und 310° schwenkbar; Konverter im Strahlergehäuse; COB (Chip on Board) Technologie - höchste Effizienz; keine Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; PABLO basic: hochwertiger Aluminiumreflektor mit sphärischer Facettenoptik; hochglänzend eloxiert; präzise Abstrahlcharakteristik mit unterschiedlichen Lichtverteilungen (symmetrisch / asymmetrisch); werkzeuglos einsetz- bzw. austauschbar; PABLO focus: inkl. hochwertiger plan-konvexer Glaslinse; exakte Objekt-Fokussierung durch justierbare Linse; Ausstrahlwinkel von 17-47° einstellbar; Fokussierung mittels gummiertem Verstellring am Strahlerkopf; optische Aufsätze als Zubehör; Adapter für werkzeugloses Einsetzen bzw. Verschieben in verschiedenen 3-Phasen Stromschienen; Adapter-Fixierung wahlweise werkzeuglos mittels Rändel- oder Feststellschraube (Schraubendreher erforderlich); Punktauslass, wahlweise in Anbaueinheit bzw. Einbaueinheit, als Zubehör erhältlich



compatible with
MOVE IT PRO



DiiA® standards
251, 252, 253



360° rotatable,
310° tiltable



DIM POTI /
rotation lock




PABLO basic track



SUPER SPOT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.9 W	3000 K	614 lm	56 lm/W	1 8 0 - 5 1 0 5 V
	4000 K	681 lm	62 lm/W	1 8 0 - 5 1 0 6 V

3-SDCM



SPOT CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.9 W	3000 K	986 lm	71 lm/W	1 8 0 - 5 1 0 0 S
	4000 K	1080 lm	78 lm/W	1 8 0 - 5 1 0 1 S
22.9 W	3000 K	1460 lm	64 lm/W	1 8 0 - 5 1 1 0 S
	4000 K	1610 lm	70 lm/W	1 8 0 - 5 1 1 1 S

MEDIUM CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.9 W	3000 K	946 lm	68 lm/W	1 8 0 - 5 1 0 0 M
	4000 K	1040 lm	75 lm/W	1 8 0 - 5 1 0 1 M
22.9 W	3000 K	1400 lm	61 lm/W	1 8 0 - 5 1 1 0 M
	4000 K	1540 lm	67 lm/W	1 8 0 - 5 1 1 1 M

FLOOD CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.9 W	3000 K	914 lm	66 lm/W	1 8 0 - 5 1 0 0 F
	4000 K	1000 lm	72 lm/W	1 8 0 - 5 1 0 1 F
22.9 W	3000 K	1360 lm	59 lm/W	1 8 0 - 5 1 1 0 F
	4000 K	1490 lm	65 lm/W	1 8 0 - 5 1 1 1 F

WIDE FLOOD CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.9 W	3000 K	900 lm	65 lm/W	1 8 0 - 5 1 0 0 W
	4000 K	988 lm	71 lm/W	1 8 0 - 5 1 0 1 W
22.9 W	3000 K	1340 lm	59 lm/W	1 8 0 - 5 1 1 0 W
	4000 K	1470 lm	64 lm/W	1 8 0 - 5 1 1 1 W

WALLWASHER CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
13.9 W	3000 K	891 lm	64 lm/W	1 8 0 - 5 1 0 0 A
	4000 K	978 lm	70 lm/W	1 8 0 - 5 1 0 1 A
22.9 W	3000 K	1320 lm	58 lm/W	1 8 0 - 5 1 1 0 A
	4000 K	1450 lm	63 lm/W	1 8 0 - 5 1 1 1 A

Order options

MOUNTING		CONTROL		COLOUR	
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POTI	8	jet black RAL 9005	8



PABLO focus track




FOCUS 17-47° CRI ≥ 95

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
14.0 W	3000 K	785 lm	56 lm/W	1 8 0 - 5 2 0 0
	4000 K	862 lm	62 lm/W	1 8 0 - 5 2 0 1
23.0 W	3000 K	1170 lm	51 lm/W	1 8 0 - 5 2 1 0
	4000 K	1280 lm	56 lm/W	1 8 0 - 5 2 1 1



Mounting accessories (optional)

RECESSED HOUSING / POINT OUTLET ceiling thickness, 1-30 mm



COLOUR	Ø-H (mm)	ORDER CODE
traffic white	151-60	1 8 6 - 0 7 2 2 7 7
jet black	151-60	1 8 6 - 0 7 2 2 7 8



SURFACE HOUSING / POINT OUTLET

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	120-32	1 8 6 - 0 7 2 2 8 7
jet black	120-32	1 8 6 - 0 7 2 2 8 8

Optical accessories (optional)

HONEYCOMB LOUVER



TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 70 PABLO	jet black	61-3	0 8 0 - 5 9 0 0 0 1 8



SNOOT

COLOUR	Ø-H (mm)	ORDER CODE
jet black	62-33	0 8 0 - 5 9 0 0 0 0 8

Order options

MOUNTING		CONTROL		COLOUR	
set screw (tool required)	1	DALI-2	3	traffic white RAL 9016	7
tool-free fixation	2	DIM POT	8	jet black RAL 9005	8

Schwedisches Nationalmuseum, Stockholm

Sweden

Architect
Wingårdhs

Lighting Design
Kardorff Ingenieure
Lichtplanung

Photographer
Linus Lintner



Used products



PABLO basic / focus



