

PABLO multilens

180-5710587 080-5900020



Project / Type


Notes

Count / Date



Track light made of die-cast aluminium; surface traffic white powder coated; 360° rotatable and 310° tiltable; converter installed in aluminium spotlight housing; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 16°x59° beam (oval filter); degree of protection IP20; PC1; 220-240 V; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation by means of set screw; incl. converter, dimmable with integrated potentiometer; point outlet, either in surface mounted housing or recessed housing, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



Light distribution



oval 16°

h (m)	E0° (lx)	ø (m)
1	2720	0.28
2	680	0.56
3	300	0.84
4	170	1.12
5	110	1.40

Product drawing



General

Ceiling | Track

tilt max 310°

rotation 360°

traffic white | RAL 9016

IP20

996 lm

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 98 | R_f: 91 | R₍₁₋₁₅₎: 89

MR 0.6 | MDER 0.55

Optical

oval | beam angle 16°x59°

PstLM $\leq 1.0^{1\ 2}$ | SVM $\leq 0.4^{1\ 2}$

Electrical

DIM POTI

PC1 | 220-240 V

system 14.7 W

system 68 lm/W³

Physical

diameter 70 mm | height 98 mm

0.92 kg

set screw (tool required)

¹ 59x16 degrees oval
² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

