

PABLO tunable white

180-5610D38F



Project / Type

Notes

Count / Date



Track light made of die-cast aluminium; surface jet black powder coated; 360° rotatable and 310° tiltable; converter installed in aluminium spotlight housing; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour: tunable white diodes (2700-5000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 98; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 38° beam; installed and exchanged without tools; optical attachments available as accessories; degree of protection IP20; PC1; 220-240 V; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation by means of set screw; incl. DALI-2 converter; point outlet, either in surface mounted housing or recessed housing, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling | Track

tilt max 310°

rotation 360°

jet black | RAL 9005

IP20

1080 lm

LED

tunable white | 2700 K - 5000 K

CRI ≥ 98

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 | R_f: 97 | R_{f(1-5)}: 98

MR 1.02 | MDER 0.93

Optical

flood | beam angle 38°

Electrical

DALI-2 | 2 DALI Addr.

DT8

PC1 | 220-240 V

system 26.6 W

system 41 lm/W ¹

Physical


diameter 70 mm | height 98 mm

0.95 kg

set screw (tool required)

¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency


Light distribution



flood 38°

h (m)	EO° (lx)	ø (m)
1	2410	0.69
2	600	1.39
3	270	2.08
4	150	2.78
5	100	3.47

Product drawing



Installation instructions



Lighting calculator

