

# PABLO tunable white


180-5610D37F



Project / Type

Notes

Count / Date



### General

Ceiling , Track

tilt max 310°

rotation 360°

white , RAL9016 <sup>1</sup>

IP20

904 lm

### LED

tunable white

2700 K - 5000 K

CRI ≥ 98

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

### Optical

flood

beam angle 38°

### Electrical

DALI-2

20.7 W

PC1 220-240V

44 lm/W

2 DALI Addr.

### Physical

diameter 70 mm


height 98 mm

0.95 kg

set screw (tool required)

<sup>1</sup> RAL code


### Light distribution



flood 38°

h (m)	E0° (lx)	ø (m)
1	2020	0.69
2	500	1.39
3	220	2.08
4	130	2.78
5	80	3.47

### Product drawing



### Installation instructions



### Lighting calculator



[180-5610D37F] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com