

SQUADRO 2 × 4 lamps wallwasher

track
149-2241637B



Project / Type _____

Notes _____

Count / Date _____



220-240V _____

X-PERT _____

X-PERT _____

General

Ceiling , Track _____

tilt min 15° _____

tilt max 15° _____

rotation 365° _____

white , RAL9016 ¹ _____

IP20 _____

12800 lm _____

LED

4000 K _____

CRI ≥ 80 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.74 _____

MDER 0.67 _____

Optical

shelf / wall floor washer _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

101 W _____

PC1 220-240V _____

127 lm/W _____

2 DALI Addr. _____

Physical

length 258 mm _____

width 204 mm _____

height 76 mm _____

2.5 kg _____


¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Tracked spotlight in die cast aluminium with 2x4-lamp design; converter integrated into spotlight head; heat sink integrated into luminaire geometry for optimum thermal management and passive cooling of LEDs; with COB (Chip on Board) technology for maximum efficiency; energy efficient LEDs with high CRI; Aisle spotlight 1x shelf / 1x wall floor washer with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone; adjustable light modules (tiltable +15° to -15°); IP 40 protection glass available as an accessory; accessories are listed separately; incl. converter, non dimmable; adapter for toolless insertion or movement on a variety of 3-phase power tracks; including attachment for linear alignment of the spotlights;

Light distribution



Product drawing

