

# SQUADRO 2 × 4 lamps wallwasher

track


149-2241637B



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



220-240V \_\_\_\_\_

\_\_\_\_\_

X-PERT \_\_\_\_\_

X-PERT \_\_\_\_\_

## General

Ceiling , Track \_\_\_\_\_

tilt min 15° \_\_\_\_\_

tilt max 15° \_\_\_\_\_

rotation 365° \_\_\_\_\_

white , RAL9016 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

12800 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

MR 0.74 \_\_\_\_\_

MDER 0.67 \_\_\_\_\_

## Optical

shelf / wall floor washer \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

101 W \_\_\_\_\_

PC1 220-240V \_\_\_\_\_

127 lm/W \_\_\_\_\_

2 DALI Addr. \_\_\_\_\_

## Physical

length 258 mm \_\_\_\_\_


width 204 mm \_\_\_\_\_

height 76 mm \_\_\_\_\_


2.5 kg \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



[“149-2241637B”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

# SQUADRO 2 × 4 lamps wallwasher

track  
149-2241637B



Project / Type

Notes

Count / Date

### Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	5
B13	6
B16	8
B20	10
C10	8
C13	10
C16	13
C20	17

### Optical accessories

#### IP40 PROTECTION GLASS

ARTICLE NUMBER(S)  
049-2940010

