

SQUADRO 2 × 4 lamps wallwasher

track
149-2241518A



Project / Type


Notes

Count / Date




Tracked spotlight in die cast aluminium with 2x4-lamp design; converter integrated into spotlight head; heat sink integrated into luminaire geometry for optimum thermal management and passive cooling of LEDs; with COB (Chip on Board) technology for maximum efficiency; energy efficient LEDs with high CRI; aisle spotlight wall floor washer with special, multi-free-form, facet effect surface reflectors for high precision light control; precise shelf and aisle zone lighting, optimum longitudinal glare control for high viewing comfort in the aisle zone; adjustable light modules (tiltable +15° to -15°); IP 40 protection glass available as an accessory; accessories are listed separately; incl. converter, non dimmable; adapter for toolless insertion or movement on a variety of 3-phase power tracks; including attachment for linear alignment of the spotlights;

Light distribution



Product drawing



General

Ceiling , Track

tilt min 15°

tilt max 15°

rotation 365°

black , RAL9005 ¹

IP20

12200 lm

LED

3000 K

CRI ≥ 80

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.58

MDER 0.52

Optical

wall floor washer

Electrical

non DIM

101 W

PC1 220-240V

121 lm/W

Physical

length 258 mm

width 204 mm

height 76 mm

2.5 kg

¹ RAL code

Installation instructions



Lighting calculator

