

# L2

MOVE IT 45


090-9L253RB001



Project / Type

Notes

Count / Date



## General

Ceiling , Track  
black , RAL9005 <sup>1</sup>  
Reflector chrome  
IP20  
624 lm

## LED

3000 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 100 , R<sub>f</sub>: 92 , R<sub>f(1-5)</sub>: 91  
MR 0.64  
MDER 0.58

## Optical

rectangular  
beam angle 30°x67°  
≥65° <3000 cd/m<sup>2</sup>

## Electrical

DALI-2  
6.7 W  
PC3 48V  
93 lm/W  
1 DALI Addr.


## Physical

length 81 mm  
width 43 mm  
height 48 mm  
0.2 kg

<sup>1</sup> RAL code

Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; equipped with two corridor light elements (rectangular medium); symmetrical light distribution with precise radiation characteristic, beam angle 30°x67°; high quality reflector with micro-faceted, aluminum-vaporised surface; Reflector chrome; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

