

SQUADRO 2 × 4 lamps wallwasher

track
149-2240637B



Project / Type _____

Notes _____

Count / Date _____



220-240V _____

X-PERT _____

X-PERT _____

General

Ceiling , Track _____

tilt min 15° _____

tilt max 15° _____

rotation 365° _____

white , RAL9016 ¹ _____

IP20 _____

11500 lm _____

LED

4000 K _____

CRI ≥ 80 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.74 _____

MDER 0.67 _____

Optical

shelf / wall floor washer _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

86 W _____

PC1 220-240V _____

134 lm/W _____

2 DALI Addr. _____

Physical

length 258 mm _____


width 204 mm _____

height 76 mm _____


2.5 kg _____

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



[“149-2240637B”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com