


# L1

MOVE IT 45

090-9L1D3EB001



Project / Type	
Notes	
Count / Date	



## General

Ceiling   Track	
black   RAL 9005 <sup>1</sup>	
chrome	
IP20	
111 lm	
optical inset 52 lm/W <sup>2</sup>	

## LED

tunable white   2700 K - 5000 K	
CRI ≥ 80	
L80 / 50000 h	
initial MacAdam ≤ 3 SDCM	
MR 0.55   MDER 0.5	

## Optical

medium square   beam angle 30°	
UGR ≤ 10	
PstLM ≤ 1.0 <sup>3</sup>   SVM ≤ 0.4 <sup>3</sup>	

## Electrical


DALI-2 DT8   1 DALI Addr.	
PC3   48 V	
fixture 2.5 W	
optical inset 2.1 W	

## Physical

length 43 mm   width 43 mm   height 48 mm	
0.1 kg	

Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; equipped with a medium square light element; symmetrical light distribution with precise radiation characteristic, beam angle 30°; high quality reflector with micro-faceted, aluminum-vaporised surface; UGR ≤ 10; passive cooling of the LEDs through improved heat sink geometry; light colour: tunable white diodes (2700-5000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 80% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator





Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.93	0.89	0.85	0.81
LSF	1	1	1	1	1

MF

MF

LMF<sup>a</sup>

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF<sup>a</sup>

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.