

# SQUADRO 2 × 4 lamps wallwasher

track  
149-2240617B



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



220-240V \_\_\_\_\_

\_\_\_\_\_

X-PERT \_\_\_\_\_

X-PERT \_\_\_\_\_

## General

Ceiling , Track \_\_\_\_\_

tilt min 15° \_\_\_\_\_

tilt max 15° \_\_\_\_\_

rotation 365° \_\_\_\_\_

white , RAL9016 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

11500 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

MR 0.74 \_\_\_\_\_

MDER 0.67 \_\_\_\_\_

## Optical

shelf / wall floor washer \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

non DIM \_\_\_\_\_

86 W \_\_\_\_\_

PC1 220-240V \_\_\_\_\_

134 lm/W \_\_\_\_\_

## Physical

length 258 mm \_\_\_\_\_


width 204 mm \_\_\_\_\_

height 76 mm \_\_\_\_\_


2.5 kg \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions

