

# UNICO Q9 basic

trim

090-7Q951G0021 090-7Q9020W



Project / Type


Notes

Count / Date




Square recessed multi-downlight made of die-cast aluminium; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; equipped with nine wide flood square light elements; symmetrical light distribution with precise radiation characteristic, beam angle 71°; high quality reflector with micro-faceted, aluminum-vaporised surface; chrome reflector; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC2; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source not replaceable; control gear replaceable by an authorized professional; clank-free;

## Light distribution



## Product drawing



## General

Ceiling , Recessed  
chrome reflector , RAL9016 <sup>1</sup>  
Mounting set traffic white  
IP20  
3240 lm

## LED

3000 K  
CRI  $\geq 90$   
L90 / 50000 h  
initial MacAdam  $\leq 3$  SDCM  
 $R_g: 100, R_f: 92, R_{f(1-15)}: 91$   
MR 0.64  
MDER 0.58

## Optical

wide flood square  
beam angle 71°  
 $\geq 65^\circ < 3000 \text{ cd/m}^2$

## Electrical

non DIM  
29.9 W  
PC2  
108 lm/W

## Physical

trim  
length 119 mm  
width 119 mm  
height 48 mm  
0.71 kg

## Cutout

length 130 mm  
width 130 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 90 mm

<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator

