



Project / Type


Notes

Count / Date




Linear light inset made of aluminium; surface white powder coated; for VITA system module; lighting module with specially computed, asymmetrical high gloss reflector, linear prismatic cover incl. foil; designed for use as indirect light component; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; energy efficient LEDs with high CRI; degree of protection IP20; PC1; with 2 plug-in terminals for through wiring; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall | Surface

white | RAL 9010 ¹

IP20

5750 lm

LED

4000 K

CRI ≥ 97

initial MacAdam ≤ 3 SDCM

R_g: 100 | R_f: 96 | R_{f(1-15)}: 98

MR 0.86 | MDER 0.78

Optical

Linear Prismatic | asymmetric

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical

DALI-2 | 1 DALI Addr.

PC1 | 220-240 V

system 65 W

system 88 lm/W ³

Physical

length 1006 mm | width 45 mm | height 22 mm

0.86 kg

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

