



Project / Type _____

Notes _____

Count / Date _____



General

Wall , Surface _____

white , RAL 9010 ¹ _____

IP20 _____

8970 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 98 , R_f: 90 , R_{i(1-15)}: 88 _____

MR 0.76 _____

MDER 0.69 _____

Optical

Linear Prismatic _____

asymmetric _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

220-240 V _____

system 78 W _____

system 115 lm/W³ _____

PC1 _____

1 DALI Addr. _____

Physical

length 1206 mm _____

width 45 mm _____

height 22 mm _____

1.15 kg _____

¹ RAL code ² Value of containing product at full load (undimmed)


³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Linear light inset made of aluminium; surface white powder coated; for VITA system module; lighting module with specially computed, asymmetrical high gloss reflector, linear prismatic cover incl. foil; designed for use as direct light component; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; with 2 plug-in terminals for through wiring; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

