

# UNICO Q4 basic

trimless

090-7Q443C0B21 090-7Q40100



Project / Type
Notes
Count / Date



## General

Ceiling , Recessed
black reflector
IP20
1280 lm

## LED

2700 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 101 , R <sub>r</sub> : 91 , R <sub>(1-5)</sub> : 89
MR 0.56
MDER 0.51

## Optical

flood round
beam angle 49°
UGR ≤ 16 , ≥65° <3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Electrical

DALI-2
220-240 V
system 13.1 W
system 98 lm/W <sup>2</sup>
PC2

## Physical


trimless
length 85 mm
width 85 mm
height 51 mm
0.52 kg

## Cutout

length 90 mm
width 90 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses  
& operating device efficiency

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

