

UNICO wall 2 lamps

trimless



090-6L263UB001 090-7Q40100



Project / Type _____

Notes _____

Count / Date _____



General

Wall , Recessed _____

black , RAL9005 ¹ _____

IP20 _____

1070 lm _____

LED

4000 K _____

CRI \geq 90 _____

L80 / 50000 h _____

initial MacAdam \leq 3 SDCM _____

R_g: 102 , R_f: 93 , R_{f(1-15)}: 92 _____

MR 0.81 _____

MDER 0.74 _____

Optical

wide floor _____

beam angle 148° _____

PstLM \leq 1.0 ² _____

SVM \leq 0.4 ² _____

Electrical

DALI-2 _____

17.3 W _____

PC2 _____

62 lm/W _____

Physical

length 85 mm _____

width 47 mm _____

height 131 mm _____

0.15 kg _____

Cutout

length 90 mm _____

width 90 mm _____

recessed depth 110 mm _____


¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Square wall recessed luminaire made from aluminium; surface black; installation without tools in mounting set due to patented ball catch system; square installation housing; for trimless installation; suitable for wall thickness of 12.5/15/20/25 mm; incl. external converter; high quality reflector with micro-faceted, aluminum-vaporised surface; asymmetrical light distribution with precise radiation characteristic; installation optionally for floor or ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 80% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC2; incl. DALI-2 converter; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing

