

UNICO wall 2 lamps

trimless

090-6L243UB001 090-7Q40100




Project / Type	
Notes	
Count / Date	




Square wall recessed luminaire made from aluminium; surface black; installation without tools in mounting set due to patented ball catch system; square installation housing; for trimless installation; suitable for wall thickness of 12.5/15/20/25 mm; incl. external converter; high quality reflector with micro-faceted, aluminum-vaporised surface; asymmetrical light distribution with precise radiation characteristic; installation optionally for floor or ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC2; incl. DALI-2 converter; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall , Recessed	
black , RAL9005 ¹	
IP20	
934 lm	

LED

2700 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 101 , R _f : 91 , R ₍₁₋₁₅₎ : 89	
MR 0.56	
MDER 0.51	

Optical

wide floor	
beam angle 148°	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Electrical

DALI-2	
17.3 W	
PC2	
54 lm/W	

Physical

length 85 mm	
width 47 mm	
height 131 mm	
0.15 kg	

Cutout

length 90 mm	
width 90 mm	
recessed depth 110 mm	

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

