

UNICO wall 2 lamps

trim

090-6L241UB001 090-7Q4020B



Project / Type	
Notes	
Count / Date	



General

Wall , Recessed
black , RAL9005 ¹
jet black
IP20
934 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 101 , R _f : 91 , R _{t(1-15)} : 89
MR 0.56
MDER 0.51

Optical

wide floor
beam angle 148°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

non DIM
17.3 W
PC2
54 lm/W

Physical


trim
length 80 mm
width 53 mm
height 80 mm
0.08 kg

Cutout


length 90 mm
width 90 mm
recessed depth 110 mm

Square wall recessed luminaire made from aluminium; surface black; installation without tools in mounting set due to patented ball catch system; square installation housing; with trim jet black; suitable for wall thickness of 2-25 mm; incl. external converter; high quality reflector with micro-faceted, aluminum-vaporised surface; asymmetrical light distribution with precise radiation characteristic; installation optionally for floor or ceiling illumination; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC2; incl. converter, non dimmable; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

