


UNICO wall 1 lamp

trim

090-6L143UB001 090-7L2020W



Project / Type	
Notes	
Count / Date	



General

Wall , Recessed
black , RAL9005 ¹
traffic white
IP20
492 lm

LED

2700 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 101 , R _f : 91 , R _{t(1-5)} : 89
MR 0.56
MDER 0.51

Optical

wide floor
beam angle 148°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrical

DALI-2
9.9 W
PC2
50 lm/W

Physical


trim
length 43 mm
width 53 mm
height 80 mm
0.09 kg

Cutout

length 90 mm
width 50 mm
recessed depth 150 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



[“090-6L143UB001 090-7L2020W”] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

09.05.2024