

# STREAMCUT

bollard surge protection  
088-284251DA



Project / Type


Notes

Count / Date




Bollard luminaire in aluminium in a simple, minimalist design; luminaire head with integrated cooling fins; can be swivelled plus/minus 90° and lockable every 30°; anodised surface and dark grey powder coated; partially printed safety glass, fixed with stainless steel screws; incl. high quality lens system; asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; surge protection typ 2 with nominal discharge current 3 kA; PC1 220-240V; shock resistance IK07; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; optional mounting on screw-on base or with anchorage unit (available as an accessory); accessories are listed separately; incl. converter, non dimmable;

## Light distribution



## Product drawing



IP65

IK 07

220-240V

### General

Floor , Standing

tilt max 180°

dark grey

IP65

IK07

2710 lm

### LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.6

MDER 0.54

### Optical

asymmetric

### Electrical

non DIM

35 W

PC1 220-240V

77 lm/W

### Physical

length 230 mm

width 135 mm

height 850 mm

4.5 kg

## Installation instructions

