

STREAMCUT

bollard surge protection
088-284251DA



Project / Type

Notes

Count / Date



General

Floor | Standing

tilt max 180°

dark grey

IP65

IK07

2710 lm

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 97 | R_f: 91 | R₍₁₋₁₅₎: 89

MR 0.6 | MDER 0.54

Optical

asymmetric

Electrical

non DIM

PC1 | 220-240 V

system 35 W

system 77 lm/W ¹

Physical


length 230 mm | width 135 mm | height 850 mm

4.5 kg


¹ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Bollard luminaire in aluminium in a simple, minimalist design; luminaire head with integrated cooling fins; can be swivelled plus/minus 90° and lockable every 30°; anodised surface and dark grey powder coated; partially printed safety glass, fixed with stainless steel screws; incl. high quality lens system; asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; surge protection typ 2 with nominal discharge current 3 kA; PC1; 220-240 V; shock resistance IK07; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; optional mounting on screw-on base or with anchorage unit (available as an accessory); accessories are listed separately; incl. converter, non dimmable;

Light distribution



Product drawing



Installation instructions



[‘088-284251DA’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

STREAMCUT

bollard surge protection
088-284251DA



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.98 | 0.94 | 0.91 | 0.88 | 0.85 |
| LSF | 1 | 1 | 1 | 1 | 1 |

| | | | |
|------------------|------------------------------|-------------------|---------------------------------|
| MF | LMF × RSMF × LLMF × LSF | RSMF ^a | Room Surface Maintenance Factor |
| MF | Maintenance Factor | LLMF | Lamp Lumens Maintenance Factor |
| LMF ^a | Luminaire Maintenance Factor | LSF | Lamp Survival Factor |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

ANCHORAGE UNIT

| | |
|------------|-------------------|
| L·W·H (MM) | ARTICLE NUMBER(S) |
| 84·32·590 | 088-2893110 |

