

STREAMCUT

wall

088-283151D



Project / Type

Notes

Count / Date



General

Wall | Recessed

dark grey | RAL 9007 ¹

IP65

IK08

293 lm

LED

3000 K

CRI ≥ 80

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

Optical

asymmetric

Electrical

non DIM

PC1 | 220-240 V

system 8.4 W

system 35 lm/W ²

Physical

length 150 mm | width 70 mm | height 200 mm

1.3 kg


Cutout

length 188 mm | width 140 mm


recessed depth 70 mm

Recessed wall light in aluminium in a simple, minimalist design; anodised surface and dark grey powder coated; partially printed safety glass, fixed with stainless steel screws; reflector in matt anodised aluminium with asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; PC1; 220-240 V; shock resistance IK08; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



STREAMCUT

wall

088-283151D



Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	80
B13	127
B16	157
B20	200
B25	254
C10	265
C13	210
C16	317
C20	437
C25	550

Mounting accessories

MOUNTING HOUSING

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
concrete and solid walls	290-100-200	088-2891110

