

# STREAMCUT

wall

088-283151D



Project / Type


Notes

Count / Date




Recessed wall light in aluminium in a simple, minimalist design; anodised surface and dark grey powder coated; partially printed safety glass, fixed with stainless steel screws; reflector in matt anodised aluminium with asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; PC1; 220-240 V; shock resistance IK08; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Wall | Recessed

dark grey | RAL 9007 <sup>1</sup>

IP65

IK08

293 lm

## LED

3000 K

CRI  $\geq 80$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.56 | MDER 0.51

## Optical

asymmetric

## Electrical

non DIM

PC1 | 220-240 V

system 8.4 W

system 35 lm/W <sup>2</sup>

## Physical

length 150 mm | width 70 mm | height 200 mm

1.3 kg

## Cutout

length 188 mm | width 140 mm

recessed depth 70 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions

