

STREAMCUT

surface

088-282151DF



Project / Type


Notes

Count / Date





Luminaire in aluminium in a simple, minimalist design; lamp head with integrated cooling fins; anodised surface and dark grey powder coated; suitable as surface mounted lights (wall, floor) can be swivelled plus/minus 90° and lockable every 30°; partially printed safety glass, fixed with stainless steel screws; incl. high quality lens system; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; PC1; 220-240 V; shock resistance IK07; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; optional mounting screwed on or with ground spike (available as an accessory); accessories are listed separately; incl. converter, non dimmable; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Floor / Wall | Surface

tilt max 180°

dark grey | RAL 9007 ¹

1217 lm

Beam Angle Correspondence Narrow cone (90°)

Sorgente luminosa direzionale

IP65

IK07

1300 lm

Chromaticity Coordinate X: 0.435

Chromaticity Coordinate Y: 0.403

LED

3000 K

CRI ≥ 80

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

Optical

flood

UGR ≤ 19

Electrical

non DIM

PC1 | 220-240 V

system 13.5 W

system 96 lm/W ²

classe isolamento 2

15 W

TRIAC Dim

min 500 mA

max 500 mA

min 198 V

max 264 V

Constant Current

min 50 Hz

max 60 Hz

Physical

length 286 mm | width 135 mm | height 40 mm

1.9 kg

¹ RAL code

² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

