

STREAMCUT

surface

088-282151DA



Project / Type


Notes

Count / Date




Luminaire in aluminium in a simple, minimalist design; lamp head with integrated cooling fins; anodised surface and dark grey powder coated; suitable as surface mounted lights (wall, floor) can be swivelled plus/minus 90° and lockable every 30°; partially printed safety glass, fixed with stainless steel screws; incl. high quality lens system; asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; PC1; 220-240 V; shock resistance IK07; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; optional mounting screwed on or with ground spike (available as an accessory); accessories are listed separately; incl. converter, non dimmable; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Floor / Wall | Surface

tilt max 180°

dark grey | RAL 9007 ¹

978 lm

Beam Angle Correspondence Wide cone (120°)

Sorgente luminosa direzionale

IP65

IK07

1180 lm

Chromaticity Coordinate X: 0.435

Chromaticity Coordinate Y: 0.403

LED

3000 K

CRI ≥ 80

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

Optical

asymmetric

Electrical

non DIM

PC1 | 220-240 V

system 13.5 W

system 87 lm/W ²

classe isolamento 2

15 W

TRIAC Dim

min 500 mA

max 500 mA

min 198 V

max 264 V

Constant Current

min 50 Hz

max 60 Hz

Physical

length 286 mm | width 135 mm | height 40 mm

1.9 kg

¹ RAL code

² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



STREAMCUT

surface

088-282151DA



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.97	0.96	0.96	0.95
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	50
B13	65
B16	80
B20	100
C10	50
C13	65
C16	80
C20	100

Mounting accessories

EARTH SPIKE

ARTICLE NUMBER(S)
088-2892110

