

STREAMCUT

bollard surge protection
088-281251DA



Project / Type

Notes

Count / Date



General

Floor | Standing

tilt max 180°

grey aluminium | RAL 9007 ¹

IP65

IK07

1180 lm

LED

3000 K

CRI ≥ 80

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

Optical

asymmetric

Electrical

non DIM

PC1 | 220-240 V

system 13.5 W

system 87 lm/W ²


Physical

length 230 mm | width 135 mm | height 850 mm


4.5 kg

Bollard luminaire in aluminium in a simple, minimalist design; luminaire head with integrated cooling fins; can be swivelled plus/minus 90° and lockable every 30°; anodised surface and grey aluminium powder coated; partially printed safety glass, fixed with stainless steel screws; incl. high quality lens system; asymmetric radiation characteristic; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP65; with pressure equalisation valve; surge protection typ 2 with nominal discharge current 3 kA; PC1; 220-240 V; shock resistance IK07; ambient temperatures from -20°C to + 50°C; separate luminaire wiring compartment, suitable for through wiring; optional mounting on screw-on base or with anchorage unit (available as an accessory); accessories are listed separately; incl. converter, non dimmable; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions

