

VARO 80

track
080-6210517M



Project / Type

Notes

Count / Date



General

Ceiling | Track

tilt max 90°

rotation 355°

traffic white | RAL 9016 ¹

IP20

2560 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 98 | R_f: 91 | R₍₁₋₁₅₎: 89

MR 0.62 | MDER 0.56

Optical

medium | beam angle 28°

Electrical

non DIM

PC1 | 220-240 V

system 28.8 W

system 89 lm/W ²


Physical

diameter 87 mm | height 145 mm

1 kg


Track light made of die-cast aluminium; surface traffic white powder coated; 355° rotatable and 90° tiltable; converter integrated into spotlight head; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 28° beam; installed and exchanged without tools; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC1; 220-240 V; incl. converter, non dimmable; adapter for toolless insertion or movement on a variety of 3-phase power tracks; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



medium 28°			
h (m)	EO° (lx)	ø (m)	
1	8990	0.49	
2	2250	0.99	
3	1000	1.48	
4	560	1.97	
5	360	2.46	

Product drawing



Installation instructions



Lighting calculator

