

UNICO wall 2 lamps

surface

090-0L241TW001



Project / Type

Notes

Count / Date




Rectangular wall surface mounted multi-uplight made of aluminium; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface white powder coated; equipped with two light insets; high quality reflector with micro-faceted, aluminum-vaporised surface; homogeneous wall or ceiling illumination through uniform light distribution; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy-efficient high power LEDs with very good colour rendering; degree of protection IP20; PC1; suitable for through wiring; incl. converter, non dimmable; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall , Surface

white , RAL9016 ¹

IP20

650 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 101 , R_f: 91 , R_{f(1-5)}: 89

MR 0.56

MDER 0.51

Optical

wide floor

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

17.3 W

PC1

38 lm/W

Physical

length 93 mm

width 53 mm

height 96 mm

0.75 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

