

BETO circle 1600 direct

suspended

074-7404D38B



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

black , RAL9005 ¹ _____

Reflector dark chrome _____

IP20 _____

9110 lm _____

LED

tunable white _____

2700 K - 6500 K _____

CRI \geq 80 _____

L80 / 50000 h _____

initial MacAdam \leq 3 SDCM _____

MR 0.47 _____

MDER 0.42 _____

Optical

Reflector _____

Symmetric _____


UGR < 16 , $\geq 65^\circ < 1500$ cd/m² _____

PstLM ≤ 1.0 ² _____


SVM ≤ 0.4 ² _____

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; extremely slim design (only 42 x 42 mm); suspended luminaire with 1500mm cable suspension (canopy central); with integrated tool-less suspension height adjustment; incl. transparent feed; extruded profile for improved thermal management; light colour: tunable white diodes (2700-6500 K); energy efficient LEDs with high CRI; high gloss reflector with faceted design; internal wiring in light halogen free; incl. converter, non dimmable; converter included in canopy;

Light distribution



Product drawing



Electrical

DALI-2 _____

101 W _____

PC1 220-240V _____

90 lm/W _____

2 DALI Addr. _____

Physical

diameter 1569 mm _____

height 42 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

