

BETO circle 1600 direct

suspended

074-7404D37B



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

white , RAL9010 ¹ _____

Reflector dark chrome _____

IP20 _____

9110 lm _____

LED

tunable white _____

2700 K - 6500 K _____

CRI ≥ 80 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.47 _____

MDER 0.42 _____

Optical

Reflector _____

Symmetric _____

UGR < 16 , ≥65° <1500 cd/m² _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; extremely slim design (only 42 x 42 mm); suspended luminaire with 1500mm cable suspension (canopy central); with integrated tool-less suspension height adjustment; incl. transparent feed; extruded profile for improved thermal management; light colour: tunable white diodes (2700-6500 K); energy efficient LEDs with high CRI; high gloss reflector with faceted design; internal wiring in light halogen free; incl. converter, non dimmable; converter included in canopy;

Electrical

DALI-2 _____


101 W _____

PC1 220-240V _____


90 lm/W _____

2 DALI Addr. _____

Light distribution



Product drawing



Physical

diameter 1569 mm _____

height 42 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

