

BETO circle 1600 direct

suspended

074-7404638R



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL9005 ¹

Reflector chrome

IP20

14600 lm

LED

4000 K

CRI \geq 80

L90 / 50000 h

initial MacAdam \leq 3 SDCM

MR 0.72

MDER 0.65

Optical

Reflector

Symmetric

UGR $<$ 19 , \geq 65° $<$ 1500 cd/m²

PstLM \leq 1.0 ²

SVM \leq 0.4 ²

Electrical

DALI-2

91 W

PC1 220-240V

160 lm/W

1 DALI Addr.

Physical


diameter 1569 mm

height 42 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Ring-shaped light fitting in rolled and seamlessly welded extruded aluminium profile; extremely slim design (only 42 x 42 mm); suspended luminaire with 1500mm cable suspension (canopy central); with integrated tool-less suspension height adjustment; incl. transparent feed; extruded profile for improved thermal management; energy efficient LEDs with high CRI; high gloss reflector with faceted design; internal wiring in light halogen free; incl. converter, non dimmable; converter included in canopy;

Light distribution



Product drawing



Installation instructions



Lighting calculator

