

# HEX-O MODULE 1000

suspended group  
073-693710X



Project / Type	
Notes	
Count / Date	



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; high quality visual and tactile surface, acoustic special colours; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (1 cable); height adjustment without tools; suitable for group installation; including rear rail for alignment of the housings; can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements;

### General

Ceiling   Suspended	
acoustic special colours	

### Physical

cable 1500 mm (min. 500 mm)	
length 1000 mm   width 866 mm   height 100 mm	
7.6 kg	

### Acoustics


Alpha w ( $\alpha_w$ ) up to 0.9 <sup>1</sup>	
SAC (sound absorption class) up to A <sup>1</sup>	
NRC up to 0.85 <sup>1</sup>	
SAA up to 0.88 <sup>1</sup>	

<sup>1</sup> Acoustic data calculations based on HEX-O MODULE 750, cavity 1cm

### Installation instructions



### Product drawing



# HEX-O MODULE 1000

suspended group  
073-693710X



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.27	0.54	0.91	0.97	0.86	0.97

## Sound absorption coefficient ( $\alpha_p$ )

