

# HEX-O MODULE 1000

suspended group  
073-693710W



Project / Type

Notes

Count / Date



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; high quality visual and tactile surface, white; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (1 cable); height adjustment without tools; suitable for group installation; including rear rail for alignment of the housings; can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements;

### General

Ceiling | Suspended

white

### Physical

cable 1500 mm (min. 500 mm)

length 1000 mm | width 866 mm | height 100 mm

7.6 kg

### Acoustics

Alpha w ( $\alpha_w$ ) up to 0.9 <sup>1</sup>

SAC (sound absorption class) up to A <sup>1</sup>

NRC up to 0.85 <sup>1</sup>


SAA up to 0.88 <sup>1</sup>

<sup>1</sup> Acoustic data calculations based on HEX-O MODULE 750, cavity 1cm

### Installation instructions



### Product drawing



# HEX-O MODULE 1000

suspended group  
073-693710W



Project / Type

Notes

Count / Date

## Equivalent sound absorption area ( $A_{eq}$ )

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.27	0.54	0.91	0.97	0.86	0.97

## Sound absorption coefficient ( $\alpha_p$ )

