

HEX-O MODULE FLAT 1000


suspended single
073-692720G



Project / Type

Notes

Count / Date



Hexagonal acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; high quality visual and tactile surface, felt grey; foreign fiber inclusions possible; pendant fitting with 1500mm cable suspension (3 cables); height adjustment without tools; suitable for single installation;

Product drawing



General

Ceiling , Suspended

felt grey

Physical

cable 1500 mm (min. 500 mm)

length 1000 mm

width 866 mm

height 40 mm

7.5 kg

Acoustics

Alpha w (α_w) up to 0.5 ¹

SAC (sound absorption class) up to D ¹

NRC up to 0.7 ¹

SAA up to 0.69 ¹

¹ Acoustic data calculations based on HEX-O FLAT 750, cavity 1cm

Installation instructions



[073-692720G] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

HEX-O MODULE FLAT 1000

suspended single
073-692720G



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.06	0.17	0.45	0.67	0.84	0.72

Sound absorption coefficient (α_p)

