

# HEX-O 750

ceiling

073-61615370



Project / Type
Notes
Count / Date



## General

Ceiling   Surface
pure white   RAL 9010 <sup>1</sup>
IP20
4510 lm

## LED

3000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.54   MDER 0.49

## Optical

Opal   opal (lambertsch)
PstLM ≤ 1.0 <sup>2</sup>   SVM ≤ 0.4 <sup>2</sup>

## Electrical


DALI-2   1 DALI Addr.
PC1   220-240 V
system 35 W
system 129 lm/W <sup>3</sup>
minimum cable length on-site 0.5m

## Physical


length 750 mm   width 650 mm   height 100 mm
10 kg

Hexagonal light fitting from aluminium profile; seamlessly welded; surface pure white powder coated; suitable for ceiling mounting; convenient quick mounting system without tools; suitable for single or group installation; can be combined with all HEX-O ceiling and TRIG-O ceiling luminaires and acoustic elements; highly reflective coating for improved efficiency; completely homogeneously illuminated, satinised PMMA cover; same luminance for all size versions; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; luminaire with 2 cable openings and plug-in terminal for through wiring; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing HEX-O ABSORBER available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

