


BETO direct / indirect

free standing T-shape
074-6945618R




Free standing luminaire from extruded aluminium profile in angular design; extremely slim design (only 42 x 42 mm); square downpipe; pedestal with recess for table base (T-shape); surface jet black powder coated; direct/indirect illumination characteristic; direct light component with high gloss reflector + faceted design and asymmetric radiation characteristic; Reflector chrome; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; UGR ≤ 13 ; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Project / Type _____

Notes _____

Count / Date _____



General

Floor | Standing _____

jet black | RAL 9005 ¹ _____

Reflector chrome _____

IP20 _____

indirect 5710 lm | direct 2030 lm _____

total 7740 lm _____

LED

4000 K _____

CRI ≥ 80 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

MR 0.72 | MDER 0.65 _____

Optical

Reflector | asymmetric _____

UGR ≤ 13 _____

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ² _____

Electrical

touch DIM on pole _____

PC1 | 220-240 V _____

system 51 W _____

system 152 lm/W ³ _____

Physical

T-shape _____

length 1055 mm | width 42 mm | height 2100 mm _____

10.9 kg _____

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

