

# BETO direct / indirect

free standing T-shape

074-694551XR



Project / Type

Notes

Count / Date



## General

Floor | Standing

special colours

Reflector chrome

IP20

indirect 5020 lm | direct 1790 lm

total 6810 lm

## LED

3000 K

CRI  $\geq$  80

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

MR 0.56 | MDER 0.51

## Optical

Reflector | asymmetric

UGR  $\leq$  13

PstLM  $\leq$  1.0<sup>1</sup> | SVM  $\leq$  0.4<sup>1</sup>

## Electrical

touch DIM on pole

PC1 | 220-240 V

system 51 W

system 134 lm/W<sup>2</sup>

## Physical


T-shape

length 1055 mm | width 42 mm | height 2100 mm


12.4 kg

Free standing luminaire from extruded aluminium profile in angular design; extremely slim design (only 42 x 42 mm); square downpipe; pedestal with recess for table base (T-shape); surface special colours powder coated; direct/indirect illumination characteristic; direct light component with high gloss reflector + faceted design and asymmetric radiation characteristic; Reflector chrome; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; UGR  $\leq$  13; light colour 3000 K; binning initial MacAdam  $\leq$  3 SDCM; CRI  $\geq$  80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> Value of containing product at full load (undimmed)

<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions

